

# WOODLIFE®

## MILLTREAT TYPE-E CONCENTRATE

DILUTE WITH 10 PARTS BY VOLUME  
OF PETROLEUM DISTILLATE

### WATER REPELLENT PRESERVATIVE FOR WOOD

#### WARNING!

**KEEP OUT OF REACH OF CHILDREN.  
HARMFUL OR FATAL IF SWALLOWED OR  
ABSORBED THROUGH SKIN.**

Contains Xylene. Keep contents and freshly treated articles away from flame, food and living plants. Do not use, pour, spill or store near heat or open flame. Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place away from water supplies.

**Causes skin irritation. Do not breathe vapor or spray mist. Do not get in eyes or on skin or clothing. Use only in well ventilated area.**

**Wear rubber gloves and protective clothing when handling the freshly treated lumber. Not for use or storage in or around the home.**

**This product is toxic to fish and wildlife. Keep out of lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this product only as specified on this label.**

**FIRST AID:** External—Wash with soap and water. Internal—Call a physician immediately. Force vomiting by drinking warm water mixed with a tablespoon of salt, milk or egg white. Lie down and keep warm.

ACTIVE INGREDIENTS:	
Bis (tributyltin) oxide	2.5%
Pentachlorophenol	14.9%
Other chlorophenols	1.7%
Xylene	19.6%
INERT INGREDIENTS	
	61.3%
TOTAL	100.0%

**NOTICE:** SELLER MAKES NO WARRANTIES, EXPRESSED OR IMPLIED, IN LAW OR IN FACT, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND FITNESS FOR PARTICULAR USE, except that specifically set forth on this label. Buyer assumes all risks of use, handling or storage of this product when such use, handling or storage is not in strict accordance with the provisions of this label.


 **Roberts Consolidated Industries**  
Subsidiary of Champion International

Net Contents: 55 Gallons  
U.S. Measure  
(208.2 Liters)

CITY OF INDUSTRY CA. 91749

**DO NOT REUSE CONTAINER — DESTROY WHEN EMPTY**

EPA Est. 1409-MI-1  
EPA Reg. No. 1409-47  
Made in U.S.A. / Printed in U.S.A.



#### DESCRIPTION

WOODLIFE MILLTREAT is a clean, penetrating non-swelling paintable water repellent preservative for wood.

**PRODUCT USES:** A fast drying, water repellent preservative for the treatment of millwork in factory production to protect it from wood destroying fungi, staining fungi, and dimension change.

**DILUTION:** Dilute each gallon of concentrate with 10 gallons of petroleum distillate.

#### DIRECTIONS (AFTER DILUTION)

**PREPARATION:** Machine, cut, glue and sand wood as desired before treating. Wood must be clean, dry and free from previous finishes. Do not use steel wool.

**APPLICATION:** Use only at 40° F. surrounding temperature or above. Apply by immersion. Dri-Vac vacuum, roller-coater, flood spray or brush.

**IMMERSION:** Millwork or other items to be painted or finished. Apply by 3 minute immersion (30 seconds for plywood) for batch or bundle treating, 15 second immersion for treating individual parts or units, or by Dri-Vac vacuum process. Treatment should be in accordance with Industrial Standard 4-70 (I.S. 4-70).

**FINISHING:** Before glazing, painting or varnishing, treatment should be completely dry and odor free. Allow 24-48 hours under average temperature and humidity conditions. Can be heat-dried for plant production. Use a sealer such as shellac before using lacquers.

**CLEAN-UP:** Use mineral spirits to clean immersion tanks, spray equipment and surrounding area. Lacquer thinner may be required to remove dried WOODLIFE MILLTREAT from floors and equipment.