

Weldwood<sup>®</sup>  
**WOODLIFE<sup>®</sup>**  
 (WATER BASED)  
 WATER REPELLENT PRESERVATIVE FOR WOOD  
 (PATENT PENDING)

ACCEPTED

**CONCENTRATE - CLEAR**

**DIRECTIONS (After Dilution)**

Apply this product only as specified on this label. Wood treated with this product is intended only for exterior use. It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

**DESCRIPTION:** WOODLIFE (Water Based) is a clear, penetrating paintable, water repellent preservative for wood. It protects against decay fungi (like brown or white rot), staining fungi (like blue stain), surface mold (like a black, brown or other colored mildew) and dimensional change.

**PRODUCT USES:** Millwork, shingles, siding, plywood, hardboard, sheetrock, structural lumber, fences and outdoor furniture. **DO NOT USE ON WOOD WHICH WILL COME IN CONTACT WITH FOOD. DO NOT USE ON WOOD WHICH WILL COME IN CONTINUOUS CONTACT WITH THE SKIN UNLESS THE WOOD IS SEALED WITH PAINT, VARNISH OR SHELLAC AFTER TREATMENT.** Keep container closed when not in use.

**RETENTION:** 3-minute immersion — 5-10 gallons per MBF. 30 minute immersion — 10-15 gallons per MBF. Brush application — 150 sq. ft. per gallon but varies by species and condition of the substrate.

**PREPARATION:** Machine cut, glue and sand wood as desired before treating. Do not use over previously finished or stained wood without stripping off old finish. Do not use steel wool. Wood must be clean and dry.

**APPLICATION:** Treating solution, wood and surrounding air must be above 40°F (4°C). Apply by immersion, roller, coat, flood spray or brush. Any surface cut after first treatment should be re-treated.

**IMMERSION:** Millwork or other items to be painted 3 minutes. Treatment should be in accordance with Industrial Standard IS-4. Use only on items for above ground exposure.

**FINISHING:** Before glazing, painting or varnishing, treatment should be completely dry and odor-free. Allow 4-8 hours under average temperature and humidity conditions. Can be heat-dried for plant production. Use a sealer such as shellac before using lacquers.

**CLEAN-UP:** Use water and detergent to clean immersion tanks, spray equipment and surrounding area. Mineral spirits or Weldwood Cleaner & Thinner may be required to remove dried Woodlife (Water Based).

**CAUTION!**

**KEEP OUT OF REACH OF CHILDREN  
 HARMFUL IF SWALLOWED OR  
 ABSORBED THROUGH SKIN  
 AVOID CONTACT WITH EYES OR SKIN.**

Keep contents and freshly treated articles away from food and drinking water. Use only in well-ventilated area. Do not breathe vapors or spray mist. Do not get in eyes or on skin or clothing. Wear a mask, rubber gloves and protective clothing when applying or handling freshly treated lumber.

**STORAGE AND DISPOSAL**

Not for use or storage in and around the home. Do not contaminate water, food or feed by storage or disposal. All waste, spillage, residue or material should be disposed of in an approved manner. Do not reuse waste containers from water supplies. Reseal containers immediately to prevent evaporation. Dispose of in an approved manner. For more information, consult Federal, State or Local authorities for a complete list of procedures.

**ENVIRONMENTAL HAZARDS**

This product is toxic to fish and wild life. Keep out of lakes, streams or ponds.

LM 657  
 EPA REG. No. 1409-50  
 EPA Est. No. 1409-CA-1  
 EPA Est. No. 1409-GA-1  
 EPA Est. No. 1409-M-1  
 EPA Est. No. 1409-PA-1  
 EPA Est. No. 1409-TX-1  
 EPA Est. No. 1409-WA-1

Manufactured by  
**Roberts Consolidated Industries**  
 City of Industry, CA 91749  
**FOR INDUSTRIAL USE ONLY**

**FIRST AID:**

IF SWALLOWED call a physician immediately.  
 IF ON SKIN wash with soap and water.  
 IF IN EYES flood with water for 15 minutes.  
 NOTE TO PHYSICIAN: This product is a cholinesterase inhibitor. If signs of cholinesterase inhibition appear, atropine only by injection is antidote.

ACTIVE INGREDIENTS	
3 IODO-2 PROPYNYL BUTYL CARBAMATE	2.4%
INERT INGREDIENTS	97.6%
TOTAL	100.0%

Weldwood Woodlife is a registered trademark of Roberts Consolidated Industries. All other trademarks are the property of their respective owners. © 1998 Roberts Consolidated Industries. Printed in the U.S.A.

Weldwood®

# WOODLIFE®

(WATER BASED)

WATER REPELLENT PRESERVATIVE FOR WOOD

(PATENT PENDING)

ACCEPTED

CONCENTRATE - CLEAR

127  
1409-50  
1/21

### DIRECTIONS (After Dilution)

Apply this product only as specified on this label. Wood treated with this product is intended only for exterior use. It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

**DESCRIPTION:** WOODLIFE (Water Based) is a clean, penetrating paintable, water repellent preservative for wood. It protects against fungi (like brown or white rot), staining fungi (like blue stain), surface mold (like a black, brown or other colored mildew) and dimensional change.

**PRODUCT USES:** Millwork, shingles, siding, plywood, wood, hardboard, flakeboard, structural lumber, fences and outdoor furniture. DO NOT USE ON WOOD WHICH WILL COME IN CONTACT WITH FOOD. DO NOT USE ON WOOD WHICH WILL COME IN CONTINUOUS CONTACT WITH THE SKIN UNLESS THE WOOD IS SEALED WITH PAINT, VARNISH OR SHELLAC AFTER TREATMENT. Keep container closed when not in use.

**RETENTION:** 3-minute immersion — 5-10 gallons per MBF, 30-minute immersion — 10-15 gallons per MBF. Brush application — 150 sq. ft. per gallon but varies by species and condition of the substrate.

**PREPARATION:** Machine, cut, glue and sand wood as desired before treating. Do not use over previously finished or stained wood without stripping off old finish. Do not use steel wool. Wood must be clean and dry.

**APPLICATION:** Treating solution, wood and surrounding air must be above 40°F (4.4°C). Apply by immersion, roller coater, flood spray or brush. A surface cut after first treatment should be re-treated.

**IMMERSION:** Millwork or other items to be painted 3 minutes. Treatment should be in accordance with Industrial Standard IS-4. Use only on items for above ground exposure.

**FINISHING:** Before glazing, painting or varnishing treatment should be completely dry and odor-free. Allow 4-8 hours under average temperature and humidity conditions. Can be heat-dried for production. Use a sealer such as shellac before using lacquers.

**CLEAN-UP:** Use water and detergent to clean immersion tanks, spray equipment and surrounding area. Mineral spirits or Weldwood Cleaner Thinner may be required to remove dried Woodlife (Water Based).

### CAUTION!

KEEP OUT OF REACH OF CHILDREN  
HARMFUL IF SWALLOWED OR  
ABSORBED THROUGH SKIN.  
AVOID CONTACT WITH EYES OR SKIN.

Keep contents and freshly treated articles away from food and living plants. Use only in well ventilated area. Do not breathe vapor or spray mist. Do not get in eyes or on skin or clothing. Wear goggles, rubber gloves and protective clothing when applying or handling freshly treated lumber.

### STORAGE AND DISPOSAL

Not for use or storage in and around the home. Do not contaminate water, food or feed by storage or disposal of waste. Leftover pesticide or rinsate should be disposed of in an approved landfill or buried in a safe place away from water supplies. Reseal container and return to drum conditioner or dispose of in an approved landfill or bury in a safe place. Consult Federal, State or Local authorities for alternate disposal procedures.

### ENVIRONMENTAL HAZARDS

This product is toxic to fish and wildlife. Keep out of lakes, streams or ponds.

- LM 657
- EPA REG. No. 1409-50
- EPA Est. No. 1409-CA-1
- EPA Est. No. 1409-GA-1
- EPA Est. No. 1409-MI-1
- EPA Est. No. 1409-PA-1
- EPA Est. No. 1409-TX-1
- EPA Est. No. 1409-WA-1

Manufactured by



**Roberts Consolidated Industries**  
City of Industry, CA 91749

**FOR INDUSTRIAL USE ONLY**

### FIRST AID:

IF SWALLOWED call a physician immediately.  
IF ON SKIN wash with soap and water.  
IF IN EYES flood with water for 15 minutes.  
NOTE TO PHYSICIAN: This product is a cholinesterase inhibitor. If signs of cholinesterase inhibition appear, atropine only by injection is antidotal.

### ACTIVE INGREDIENTS:

3-iodo-2-propynyl butyl carbamate	2.4%
INERT INGREDIENTS	97.6%
TOTAL	100.0%

### IMPORTANT NOTICE TO PURCHASER

Buyer assumes all risk of use, handling and storage. Product not in strict accordance with label directions. No express warranties are given. Should defect occur, Seller's sole liability is to replace product or refund purchase price. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR PARTICULAR USE IS LIMITED TO ONE YEAR FROM DATE OF PURCHASE. LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGE OR LOSS IS SPECIFICALLY EXCLUDED AT ALL TIMES. If used for other than personal, family or household purposes, any implied warranty of MERCHANTABILITY or FITNESS FOR PARTICULAR USE is excluded.

- Stock No. 0949
- Stock No. 0950
- Net 5 U.S. Gallons (18.9 liters)
- Net 55 U.S. Gallons (208.2 liters)
- Made and Printed in U.S.A.