

# Weldwood<sup>®</sup>

TM

# WOODLIFE

**A Water Repellent  
Preservative Treatment  
For Exterior Wood**  
(Patent Pending)

**Clear • Paintable • Stainable**

**USES:** A water repellent preservative for plywood, hard board, flake board, dimensional lumber, manufactured wood items and siding. Used where a degree of dimensional stabilization, preservative qualities and paintability are required for above ground application.

**KEEP OUT OF REACH OF CHILDREN**

## CAUTION

SEE SIDE PANEL FOR ADDITIONAL  
PRECAUTIONARY STATEMENTS

**ACCEPTED**  
SEP 11 1981  
Under the Federal Insecticide,  
Fungicide, and Rodenticide Act,  
as amended, for the pesticide  
registered under  
EPA Reg. No. 1409-51

E.P.A. (Environmental  
Protection Agency) Registered Under

EPA Reg. No. 1409-51  
EPA Est. No. 1409-Mi-1

**STOCK NO. 0946**

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

## CAUTION

**HARMFUL IF SWALLOWED  
OR ABSORBED THROUGH SKIN  
AVOID CONTACT WITH EYES OR SKIN**

**STATEMENT OF  
PRACTICAL TREATMENT**

IF SWALLOWED call a physician immediately. IF ON SKIN wash with soap and water. IF IN EYES flood with water for 15 minutes. **NOTE TO PHYSICIAN:** This product is a cholinesterase inhibitor. If signs of cholinesterase inhibition appear, atropine only by injection is antidotal.

Keep contents and freshly treated articles away from food and living plants. Use only in well ventilated area. Do not breathe vapor or spray mist. Do not get in eyes, or on skin or clothing. Wear goggles, rubber gloves and protective clothing when applying or handling treated lumber.

**DO NOT USE ON WOOD WHICH WILL COME IN CONTACT WITH FOOD. DO NOT USE ON WOOD WHICH WILL COME IN CONTINUOUS CONTACT WITH THE SKIN UNLESS THE WOOD IS SEALED WITH PAINT, VARNISH OR SHELLAC AFTER TREATMENT.**  
If a clear natural finish is desired, for best results allow the treated wood to weather 3-6 months, then apply WOODLIFE<sup>®</sup> CLEAR WOOD FINISH

**ENVIRONMENTAL HAZARDS**

This product is toxic to fish and wildlife. Do not apply directly to lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of waste.

**STORAGE AND DISPOSAL**


Do not use or store inside the home. Do not reuse empty can. Wrap can and put in trash collection.

**IMPORTANT NOTICE TO PURCHASER:** Buyer assumes all risk of use, handling and storage of product not in strict accordance with label directions. No express warranties are given. Should defect occur, Seller's sole liability is to replace product or refund purchase price.  ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR PARTICULAR USE IS LIMITED TO ONE YEAR FROM DATE OF PURCHASE. LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGE OR LOSS IS SPECIFICALLY EXCLUDED AT ALL TIMES.  If used for other than personal, family or household purposes, any implied warranty of MERCHANTABILITY or FITNESS FOR PARTICULAR USE is excluded.  
© Roberts Consolidated Industries 1976

1409-51

09/11/1981

1/2

<p><b>OUTSTANDING FEATURES</b></p> <ul style="list-style-type: none"> <li>● Water repellent . . . reduces swelling and shrinking</li> <li>● Protects against mildew, decay, rot and stain</li> <li>● Odorless, colorless when dry</li> <li>● Easy water clean-up</li> <li>● Dries in 4-8 hours</li> <li>● Can be painted, stained, or finished</li> <li>● Will not crack, peel, or blister</li> <li>● Finishes cover easier . . . last longer</li> </ul>
<p><b>PREPARATION</b></p> <p>All cutting, glueing and sanding should be done before applying WOODLIFE®II. Wood must be clean, dry and free from foreign material. Do not use over previously finished or stained wood without stripping off the old finish. Do not use steel wool. No thinning is required.</p>
<p><b>DIRECTIONS FOR USE</b></p> <p>Apply this product only as specified on the label. It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Keep container closed when not in use.</p>
<p><b>APPLICATIONS</b></p> <ol style="list-style-type: none"> <li>1. This product must be applied out-of-doors to wood intended only for exterior use.</li> <li>2. Stir well before using.</li> <li>3. Temperature of lumber and WOODLIFE®II should be 40°F (4.4C) or above.</li> <li>4. Treating may be done by roller coating, brushing to refusal or flood spraying.</li> <li>5. Flood wood with solution until puddles remain on the surface.</li> <li>6. Coat side and end grain with 3 or more consecutive coats to give full protection.</li> <li>7. Any surface cut after first treatment should be retreated.</li> </ol> <p>By following these application directions effective control can be obtained against decay fungi (like brown or white rot), staining fungi (like blue stain), surface mold (like a black, brown or other colored mildew) and dimensional change.</p>
<p><b>COVERAGE</b></p> <p>150 sq. ft. (14 sq. m) – 250 sq. ft. (23 sq. m) per gallon with brush or roller application.</p>
<p><b>DRYING TIME</b></p> <p>A minimum of 4-8 hours air drying is required before finishing, depending on conditions and method of application. On humid days, longer drying time may be required.</p>
<p><b>THINNING</b></p> <p>No thinning is required.</p>
<p><b>CLEAN UP</b></p> <p>Use water to remove wet WOODLIFE®II from all surfaces, brushes and rollers. Mineral spirits or WELDWOOD CLEANER &amp; THINNER may be required to remove dried product from glass and other areas.</p>
<p>Manufactured by:</p> <p> <b>Roberts Consolidated Industries</b> City of Industry, CA 91749</p> <p style="text-align: right;">MADE AND PRINTED IN U.S.A.</p>



Active Ingredients:  
 3-Iodo-2-Propynyl  
 Butyl Carbamate . . . . . 0.5%  
 Inert Ingredients . . . . . 99.5%  
 Total . . . . . 100.0%

**Net Contents**  
**1 U.S. gallon**  
**(3.78 liters)**