

OUTSTANDING FEATURES

WOODLIFE II Stain and Wood Preservative is a unique blend of natural and synthetic pigments that combines the attractive finish of a semi-transparent stain with the protection of an effective water-repellent wood preservative.

The pigments have been carefully selected to enhance the natural beauty of the wood or wood surfaces and to provide an effective screen against the damaging effects of the sun's rays.

WOODLIFE II Stain and Wood Preservative penetrates into wood and inhibits the growth of decay fungi, bark beetles, white rot, staining fungi, blue stain, mold, surface mold-like black, brown or other colored mold, and various water-growth stains. It also protects against the effects of moisture and reduced dimensional change that can cause swelling, warping and splitting.

DIRECTIONS FOR USE

Apply this product only as specified on the label in a violation of Federal Law. Use this product in a manner consistent with its labeling.

In order to assure satisfaction with the color hue in the wood being used, a wet-dry brush-out is advised. Wood in continuous contact with the ground should first be treated with original WOODLIFE Wood Preservative and allowed to weather prior to staining. This product must be applied only to woods intended only for outdoor use. Note to User: Keep container closed when not in use.

PREPARATION

For best results, a cutting, planing and sanding should be done before applying WOODLIFE II Stain and Wood Preservative. Wood must be clean, dry and free from foreign material. This product can be used on unfinished new wood, old or weathered wood and on wood previously stained with a semi-transparent stain. Stains and paints should be stripped to bare wood. Do not use steel wool. If old stains are present, remove by washing with a buffer or old-fashioned beach towel and clean water. If extra staining has occurred, scrub with a scrub brush and clean water. Rinse thoroughly with clean water and then wash again with clean water. Always use caution when using power tools. Always use proper safety precautions. Always use proper safety precautions. Always use proper safety precautions.

APPLICATION

Apply before using. No priming is required. The temperature of the wood and the WOODLIFE II Stain and Wood Preservative should be 40° to 90° F. The product may be applied by roller or brush. When roller coating, use a brush to touch up staining areas. Be sure to brush stain through wood that has surface irregularities, knots and other defects. Coats should be applied in the direction of the grain. The first coat should be applied to the wood. The second coat should be applied to the wood. The second coat should be applied to the wood. The second coat should be applied to the wood.

COVERAGE


20 to 30 sq. ft. per gallon, depending on the porosity of the wood.

DRYING TIME

A minimum of 4 to 6 hours depending on conditions and method of application. Two days of drying time may be required.

CLEAN UP

Use water to remove WOODLIFE II Stain and Wood Preservative from surfaces. Do not use mineral spirits. Do not use mineral spirits. Do not use mineral spirits. Do not use mineral spirits.



Manufactured by

Roberts Consolidated Industries

1000 Roberts Road, P.O. Box 1000, Piquette, Michigan 48864

USES

- ✓ Siding
- ✓ Fences
- ✓ Decks
- ✓ Patios
- ✓ Exterior Wood Products

Net Contents
1 U.S. gallon
(3.78 liters)

Forest Green 
Weldwood

Woodlife I[®]

Stain and Wood Preservative

Semi-Transparent
(Patent Pending)

KEEP OUT OF REACH OF CHILDREN
CAUTION

g
es
S
S
rior
ucts

nts
(on
rs)

✓ PRESERVES & PROTECTS

- Excellent Water Repellent
- Reduces Swelling and Shrinking
- Inhibits Mildew Rot and Decay

✓ DECORATIVE FINISH

- Provides Long Lasting Color
- Will Not Crack, Blister or Peel

✓ EASY TO USE

- Cleans Up With Water
- No Unpleasant Odor

See instructions on back of container for application and maintenance.

STOCK NO. 0971

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION

HARMFUL IF SWALLOWED
AVOID CONTACT WITH EYES

STATEMENT OF PRACTICAL TREATMENT

IF SWALLOWED call a physician immediately. IF ON SKIN wash with soap and water. IF IN EYES flood with water for 15 minutes. NOTE TO PHYSICIAN: This product is a cholinesterase inhibitor. If signs of cholinesterase inhibition appear, atropine only or injection is antidote.

... ..

... ..

ENVIRONMENTAL HAZARDS

STORAGE AND DISPOSAL

... ..

Forest Green
Weldw

INTENDED USES

DIRECTIONS FOR USE


PREPARATION

APPLICATION

OVERPAKE

NET WEIGHT

NET CONTENTS



Roberts Chemical Industries

USES

- ✓ Siding
- ✓ Fences
- ✓ Decks
- ✓ Patios
- ✓ Exterior Wood Products

Net Contents
1 US quart
(32 fl. oz.)
(946 ml)

WOOD
Stain and Wood
(Semi-Transparent)
Patent

KEEP OUT OF REACH
CAUTION

Forest Green 
Weldwood

Woodlife II™

Stain and Wood Preservative
(Semi-Transparent)
Patent Pending

USES

- ✓ Siding
- ✓ Fences
- ✓ Decks
- ✓ Patios
- ✓ Exterior Wood Products

Net Contents
1 U.S. quart
(32 fl. oz.)
(946 ml)

- ✓ Water Repellent
- ✓ Dries in 4 to 8 hours
- ✓ Easy to Use
- ✓ Long-Lasting Color

KEEP OUT OF REACH OF CHILDREN
CAUTION

STOCK NO. 0970

CAUTION

READ AND OBEY DIRECTIONS
NEVER USE IN UNVENTILATED SPACES

STATEMENT OF FACTS
WOOD PRESERVATIVE
CONTAINS COPPER NANO PARTICLES
WHICH ARE TOXIC TO AQUATIC LIFE
IF RELEASED INTO THE ENVIRONMENT

ENVIRONMENTAL HAZARDS
DO NOT DISPOSE OF THIS PRODUCT
IN SEWER OR WATERWAY

STORAGE AND DISPOSAL
KEEP IN ORIGINAL CONTAINER
TIGHTLY CLOSED