

<p style="text-align: center;">U.S. ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (HH-562) WASHINGTON, D.C. 20460</p> <p>NOTICE OF PESTICIDE: <input checked="" type="checkbox"/> REGISTRATION <input type="checkbox"/> REREISTRATION</p> <p style="text-align: center;"><i>Under the Federal Insecticide, Fungicide and Rodenticide Act, as amended</i></p>	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 50%;">EPA REGISTRATION NO. 1409-58</td> <td style="width: 50%;">DATE OF ISSUANCE MAR 12 1985</td> </tr> <tr> <td colspan="2">TERM OF ISSUANCE</td> </tr> <tr> <td colspan="2">NAME OF PESTICIDE PRODUCT E-1000 Wood Preservative</td> </tr> </table>	EPA REGISTRATION NO. 1409-58	DATE OF ISSUANCE MAR 12 1985	TERM OF ISSUANCE		NAME OF PESTICIDE PRODUCT E-1000 Wood Preservative	
EPA REGISTRATION NO. 1409-58	DATE OF ISSUANCE MAR 12 1985						
TERM OF ISSUANCE							
NAME OF PESTICIDE PRODUCT E-1000 Wood Preservative							
<p>NAME AND ADDRESS OF REGISTRANT (Include ZIP code)</p> <div style="display: flex; justify-content: space-between;"> <div style="width: 60%;"> <p><input type="checkbox"/> <i>[Faint address text]</i></p> <p><input type="checkbox"/> <i>[Faint address text]</i></p> </div> <div style="width: 35%; text-align: right;"> <p>160 13567 18 1</p> </div> </div>							
<p>NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.</p> <p>On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.</p> <p>A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.</p> <p>Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.</p> <p>This product is conditionally registered in accordance with FIFRA sec. 4(e)-7 (A) provided that you:</p> <ol style="list-style-type: none"> 1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data. 2. Make the labeling changes listed below before you release the product for shipment: <ol style="list-style-type: none"> a. Add the phrase "EPA Registration No. 1409-58." b. Delete the claim to control blue stain. c. Add a "Physical and Chemical Hazards" heading with the statement, "Keep away from heat or open flame." d. The statement of contents (left back panel) should separate active ingredients with "and" or a "comma" for clearance as follows: <i>Chlorophos 0-(2,5-dichloro-1-(ethoxythio)ethyl)-phosphorothioate</i> and <i>petroleum spirits</i>. e. The second active ingredient in the formulation, "Dursban 4" should be stated as follows: "Chlorothiophos o-(2,5-dichloro-1-(ethoxythio)ethyl)-phosphorothioate and the 2,4,6 and 4,5,2 isomers." 							
<p><input type="checkbox"/> ATTACHMENT IS APPLICABLE</p>							
<p>SIGNATURE OF APPROVING OFFICIAL</p> <p style="text-align: center;"><i>[Signature]</i></p>	<p>DATE</p> <p style="text-align: center;">3/12/85</p>						

-2-

3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 Enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Henry M. Jacoby
Product Manager (21)
Fungicide-Herbicide Branch
Registration Division (TS-767)

JOB-50863:Noles:2/26/85:Del:3/6/85:Kendrick:898-1270:DAA

FRONT PANEL

ACCEPTED
with COMMENTS
to EPA Letter Dated

WELDWOOD

MAR 12 1985

GUARANTEED FOR
LIFE
See Lid

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
as amended, for the pesticide
registered under EPA Reg. No.

WOODLIFE^R B

1409-58

WOOD PRESERVATIVE

A WATER REPELLENT PRESERVATIVE TREATMENT

FOR EXTERIOR WOOD

Protects Against Mildew,
Decay, Rot and Stain

Can Be Painted,
Stained or Finished

USES - SID 1G
FENCES
DECKS
EXTERIOR
WOOD
PRODUCTS

KEEP OUT OF REACH OF CHILDREN

WARNING!

KEEP AWAY FROM HEAT OR OPEN FLAME

HARMFUL OR FATAL IF SWALLOWED OR ABSORBED

THROUGH SKIN-CAUSES EYE AND SKIN IRRITATION

(Read Caution and First Aid Statements on Side Panels
Carefully)

EPA Re. #1409
EPA Est. #1409-MI-1

Active Ingredients:

Methylene bis(thiocyanate) .20%

2-(thiocyanomethylthio)benzo-
thiazole .20%

O-O-diethyl O-(3,5,6-trichloro-

2-pyridyl) phosphorothioate .10%

Inert Ingredients: 99.50%

Total 100.00%

LEFT BACK PANEL

PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS (AND DOMESTIC ANIMALS)

WARNING!

KEEP OUT OF REACH OF CHILDREN
HARMFUL OR FATAL IF SWALLOWED
OR ABSORBED THROUGH SKIN
CAUSES EYE AND SKIN IRRITATION

WOODLIFE^R B WOOD PRESERVATIVE contains methylene bis (thiocyanate) 2-(thiocyanomethylthio)benzothiazole, 0,0-diethyl 0-(3,5,6-Trichloro-2-pyridyl) phosphorothioate and petroleum spirits. Keep contents and freshly treated articles away from flame, food and living plants. Exposure to vapors can be harmful to plant life. All plants up to 30 feet away should be covered with a tarp or plastic sheet until application is dry (24-48 hours). Do not use, pour, spill or store near heat or open flame. Use only in a well ventilated area. Do not breathe vapor. Do not get in eyes, or on skin or clothing. Wear tightly woven coveralls and use gloves impervious to the chemicals (for example, gloves that are vinyl coated or rubber) when applying or handling freshly treated lumber. When sawing and machining, wear a dust mask. Avoid frequent or prolonged inhalation of sawdust from treated wood. Wash thoroughly after skin contact, especially before eating, drinking, or use of tobacco products. Treated wood should not be burned in open fires, fireplace or wood stoves.

STATEMENT OF PRACTICAL TREATMENT

If on skin, wash with soap and water. Remove and wash contaminated clothing before reuse. If in eyes, immediately flood with water at least 15 minutes. Call a physician. If swallowed, do not induce vomiting. Call a physician immediately.

NOTE TO PHYSICIAN: This product is a cholinesterase inhibitor. If signs of cholinesterase inhibition appear, atropine only by injection is antidotal.

ENVIRONMENTAL HAZARDS

This product is toxic to fish, birds, wildlife and plantlife. This product is highly toxic to bees exposed to direct treatment or residue on plants. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of waste.

STORAGE AND DISPOSAL

Do not use or store inside the home. Store in original container in locked storage area. Do not reuse empty container. Securely wrap container in several layers of newspaper and discard in trash.

IMPORTANT NOTICE TO PURCHASER: Buyer assumes all risk of use, handling and storage of product not in strict accordance with label directions. No expressed warranties are given. Should defect occur, Seller's sole liability is to replace product or refund purchase price. ☐ ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR PARTICULAR USE IS LIMITED TO ONE YEAR FROM DATE OF PURCHASE. LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGE OR LOSS IS SPECIFICALLY EXCLUDED AT ALL TIMES. ☐ If used for other than personal, family or household purposes, any implied warranty of MERCHANTABILITY or FITNESS FOR PARTICULAR USE is excluded.

Manufactured by
ROBERTS Consolidated Industries
City of Industry, CA 91749

Printed in USA

RIGHT BACK PANEL

USES

WOODLIFE is a clean, penetrating, paintable, water repellent and preservative for use on above ground exterior wood. It will protect and lengthen the life of millwork, shingles, siding, windows, doors, structural lumber, fences and outdoor furniture. WOODLIFE acts as an excellent base for paint, varnish, enamel and solid coat stains and increases their resistance to blistering and peeling. Use a sealer such as shellac after treatment before using lacquers. WOODLIFE is an excellent protector of wood when a clear exterior natural finish is desired.

With adequate retention, WOODLIFE^R Wood Preservative will protect wood against termites and wood destroying insects.

Keep solution and freshly treated wood away from plastics, asphalt shingles and tiles. DO NOT USE ON WOOD WHICH WILL COME IN CONTACT WITH FOOD. DO NOT USE ON INTERIOR WOOD.

OUTSTANDING FEATURES:

Water repellent . . . Reduces swelling and shrinking

Protects against decay, warping and fungi stain.

Ready-to-Use.

Adds years of life to wood.

Colorless . . . Odorless when dry.

When used as a base coat, finishes last longer.

DIRECTIONS FOR USE

Apply this product only as specified on this label. It is a violation of Federal law to use this product in a manner inconsistent with its labelling.

PREPARATION

All cutting, gluing and sanding should be done before applying WOODLIFE. Wood must be clean and dry. Do not use over previously finished or stained wood without stripping off the old finish. Do not use steel wool.

APPLICATION

1. Temperature of lumber and WOODLIFE must be above 40°F (4.4°C)
2. Treating may be done with brush or roller. Do not spray.
3. Flood wood with WOODLIFE until puddles remain on surface.
4. Coat side and end grains with three or more consecutive coats to give full protection.

Application - continued

5. Two coats must be given to any wood that will be exposed to severe conditions of decay, staining, fungi or water (see fungi listing below). Apply second coat before first coat is dry.
6. Any surface cut after first treatment should be retreated.

By following these application directions effective control can be obtained against wood destroying decay fungi (like brown or white rot) staining fungi (like blue stain), surface mold (like black, brown or other colored mildew) and dimensional change.

COVERAGE

100 to 150 sq. ft. (9.29 to 13.94 sq. m) per gallon with brush or roller application.

DRYING TIME

Allow 24 to 48 hours of air drying time before applying finish. Before glazing, painting, or varnishing, the treatment should be completely dry and odor free.

THINNING

No thinning required.

CLEAN UP

Use Weldwood^R Cleaner and Thinner or nonflammable solvent to remove wet WOODLIFE^R Wood Preservative from all surfaces, brushes and rollers. Lacquer Thinner may be used to remove dried product from glass and other surfaces.

LID

WELDWOOD

CHEMICAL
PRODUCTS

GUARANTEE

The original Woodlife^R Wood Preservative, when used to treat exterior wood in accordance with the directions on the label, is guaranteed to keep wood serviceable for the life of the structure. To qualify for this guarantee, the applicator/purchaser must supply to ROBERTS Consolidated Industries within 30 days of construction, the following information: A) Proof of Purchase, (store cash register tape); B) Type of wood and date treated (Pine, Cedar, Redwood, etc); C) End use of wood (Deck, Fence, Siding), and D) Location of structure. The above information will be recorded and registered and the structure guaranteed. In order for the guarantee to remain in effect, treatment must be repeated every 3 years with proof of treatment to be made available upon request. If treatment cannot be renewed due to the application of a finish coat of paint, stain, varnish, etc., the wood is guaranteed to remain serviceable for 10 years, with no express guarantee given for the condition of the finish. This guarantee excludes wood in standing water or in direct contact with the ground. This guarantee is non-transferable.

ROBERTS CONSOLIDATED INDUSTRIES
600 North Baldwin Park Boulevard - P.O.Box 1250
City of Industry, CA 91749
Attn Dept 64