

1209-60 P. 31 1054

U.S. ENVIRONMENTAL PROTECTION AGENCY OFFICE OF PESTICIDES PROGRAMS REGISTRATION DIVISION (WH-567) WASHINGTON, D.C. 20460 NOTICE OF PESTICIDE: <input checked="" type="checkbox"/> REGISTRATION <input type="checkbox"/> REREGISTRATION (Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended)	EPA REGISTRATION NO. 1409-60	DATE OF ISSUANCE AUG 9 1985
	TERM OF ISSUANCE	
NAME OF PESTICIDE PRODUCT Weldwood Woodlife D Concentrate		

NAME AND ADDRESS OF REGISTRANT (Include ZIP code) Roberts Consolidated Industries 2305 Superior Avenue Kalamazoo, MI 49001	<table border="0"> <tr> <td style="border: 1px solid black; padding: 5px;">160</td> <td style="border: 1px solid black; padding: 5px;">153794</td> </tr> <tr> <td style="border: 1px solid black; padding: 5px;">18</td> <td style="border: 1px solid black; padding: 5px;">1</td> </tr> </table>	160	153794	18	1
160	153794				
18	1				

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.


Registration is in no way to be construed as an endorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c)(7)(A) provided that you:

1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data.
 2. Make the labeling changes listed below before you release the product for shipment:
 - a. Add the phrase "EPA Registration No. 1409-60."
 - b. Delete the claim to control blue stain or include appropriate directions for use. Blue stain is a problem only on fresh cut lumber and treatment must be made within 24 hours of cutting to effectively prevent staining. If the product is to be applied to fresh cut lumber, indicate that treatment must be made within 24 hours of cutting for prevention of blue stain.
 3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 Enclosure for a further description of final printed labeling.
- If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.
 A stamped copy of the label is enclosed for your records.

Henry M. Jacoby
 Product Manager (21)
 Fungicide-Herbicide Branch
 Registration Division (TS-767)

ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL 	DATE 9/8/85
---	----------------

Weldwood®

WOODLIFE® D

WATER REPELLENT PRESERVATIVE FOR WOOD

CONCENTRATE - CLEAR

Active Ingredients:

3-iodo-2-propynyl butyl carbamate..... 2.4%

Inert Ingredients:..... 97.6%

Total..... 100.0%

**KEEP OUT OF REACH OF CHILDREN.
WARNING**

ACCEPTED
with COMMENTS

In EPA Letter Dated

AUG 9 1985

Under the Federal Insecticide,
Fungicide, and Rodenticide Act
as amended, for the pesticide
registered under EPA Reg. No.

1709-60

See Side Panel for Additional Precautionary Statements

IMPORTANT NOTICE TO PURCHASER

Buyer assumes all risk of use, handling and storage of product not in strict accordance with label directions. No express warranties are given. Should defect occur, Seller's sole liability is to replace product or refund purchase price. ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR PARTICULAR USE IS LIMITED TO ONE YEAR FROM DATE OF PURCHASE. LIABILITY FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGE OR LOSS IS SPECIFICALLY EXCLUDED AT ALL TIMES. If used for other than personal, family or household purposes, any implied warranty of MERCHANTABILITY or FITNESS FOR PARTICULAR USE is excluded.

Roberts Consolidated Industries

- LM
- EPA REG. No.
- EPA EM. No. 1409-CA-1
- EPA EM. No. 1409-GA-1
- EPA EM. No. 1409-M-1
- EPA EM. No. 1409-PA-1
- EPA EM. No. 1409-TX-1
- EPA EM. No. 1409-WA-1

Manufactured by



Roberts Consolidated Industries
City of Industry, CA 91749

FOR INDUSTRIAL USE ONLY

- Stock No.
 - Stock No.
 - Net 5 U.S. Gallons (18.9 liters)
 - Net 55 U.S. Gallons (208.2 liters)
- Made and Printed in U.S.A.

PRECAUTIONARY STATEMENT
HAZARDS TO HUMAN AND DOMESTIC ANIMALS

WARNING: CONTAINS PETROLEUM DISTILLATES. Use only with adequate ventilation. Avoid prolonged breathing of vapor or spray mist. Harmful if swallowed. Causes substantial but temporary eye injury. Do not get in eyes, on skin or on clothing. Wear goggles and rubber gloves when handling, and rubber gloves and protective clothing when handling freshly treated lumber. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before re-use.

STATEMENT OF PRACTICAL TREATMENT

IF ON SKIN: Wash with plenty of soap and water. Get medical attention if irritation persists.

IF SWALLOWED: Do not induce vomiting. Promptly drink a large quantity of milk, egg whites or gelatin solution; if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention immediately.

IF INHALED: Remove victim to fresh air.

IF IN EYES: Flush with plenty of water. Get medical attention.

ENVIRONMENTAL HAZARDS

This product is toxic to fish. Do not apply directly to water. Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL AND CHEMICAL HAZARDS

COMBUSTIBLE: Do not use, pour, or spill near heat or open flame. In case of fire, use water spray, foam, carbon dioxide or dry chemical.

STORAGE AND DISPOSAL

STORAGE: Do not contaminate water, food or feed by storage or disposal. Do not store near excessive heat.

PESTICIDE DISPOSAL. Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label directions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL. Triple rinse (or equivalent), Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Before Using, Dilute by Adding
4 Parts of Mineral Spirits
to
1 Part Concentrate

Description: WOODLIFE is a clean, penetrating paintable, water repellent preservative for wood. It protects against decay fungi (like brown or white rot), staining fungi (like blue stain), surface mold (like a black, brown or other colored mildew) and dimensional change.

Product Uses: Millwork, shingles, siding, plywood, hardboard, flakeboard, structural lumber, fences and outdoor furniture. DO NOT USE ON WOOD WHICH WILL COME IN CONTACT WITH FOOD. DO NOT USE ON WOOD WHICH WILL COME IN CONTINUOUS CONTACT WITH THE SKIN UNLESS THE WOOD IS SEALED WITH PAINT, VARNISH OR SHELLAC AFTER TREATMENT. Keep container closed when not in use.

Retention: 3 minute immersion -- 5-10 gallons per MBF, 30 minute immersion--10-15 gallons per MBF. Brush application--150 sq. ft. per gallon but varies by species and condition of the substrate.

Preparation: Machine, cut, glue and sand wood as desired before treating. Do not use over previously finished or stained wood without stripping off old finish. Do not use steel wool. Wood must be clean and dry.

Application: Treating solution, wood and surrounding air must be above 40° F (4.4° C). Apply by immersion, roller coater, flood spray or brush. Any surface cut after first treatment should be retreated.

Immersion: Millwork or other items to be painted-3 minutes. Treatment should be in accordance with Industrial Standard IS-4. Use only on items for above ground exposure.

Finishing: Before glazing, painting or varnishing, treatment should be completely dry and odor-free. Allow 24 to 48 hours under average temperature and humidity conditions. Can be heat-dried for plant production. Use a sealer such as shellac before using lacquers.

Clean-Up: Use Mineral Spirits to clean immersion tanks, spray equipment and surrounding area. Mineral spirits or Weldwood Cleaner & Thinner may be required to remove dried Woodlife.