

Buckman Laboratories, Inc.
1256 North McLean Boulevard
Memphis, TN 38108

DEC 2 1988

Attention: Kevin D. Drake

Gentlemen:

Subject: MTC-10
EPA Registration No. 1448-34
Your Application Dated June 23, 1988
EPA Received Date June 27, 1988


The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA), is acceptable provided that you revise the phrase under the Statement of Practical Treatment "... and then give 1 or 2 glasses of water or milk to drink" to read "... and then give 1 or 2 glasses of water to drink."

Submit five (5) copies of your final printed labeling before you release the product for shipment.

A stamped copy of the labeling is enclosed for your records.

If you have any questions concerning this letter, please contact Karen Leavy at (703) 557-3966.

Sincerely yours,

John B. Lee 
Product Manager (31)
Antimicrobial Program Branch
Registration Division (TS-767C)

Enclosure

50358; I:Leavy:L-10;FENCO:11/30/88;1/12/89;CL;EK;aw

CONCURRENCES

SYMP								
SURNA								
DATE								

With 100% active ingredient
in each gallon of concentrate

DEC 03 1988

MTC-10

Reg no: 1448-34

PM-31

ACTIVE INGREDIENT

Methylmercaptopyruvate

10.0%

INERT INGREDIENTS

90.0%

TOTAL 100.0%

EPA REG. NO. 1448-34

KEEP OUT OF REACH OF CHILDREN

DANGER

STATEMENT OF PRACTICAL TREATMENT

If product gets in eyes, flush with plenty of water for at least 15 minutes. Call a physician. In case of skin contact, wash thoroughly with soap and water. Wash and flush contaminated clothing before reuse. If product is swallowed, call a physician. If inhaled, get fresh air. If inhaled, call a physician. If inhaled, call a physician. If inhaled, call a physician.

NOTE TO PHYSICIAN: First aid measures should primarily concentrate use of artificial respiration. Measures against circulatory shock, respiratory depression, and convulsions may be needed.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes eye and skin damage. This product is a potent skin irritant. Do not get in eyes, on skin, or on clothing. Wear goggles and gloves when handling. Harmful or fatal if swallowed.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not apply to surface waters or to any other aquatic life. Do not discharge into lakes, streams, rivers, or other surface waters unless in accordance with a NPDES permit. For guidance, contact your Regional Office of the Environmental Protection Agency.

PHYSICAL AND CHEMICAL HAZARDS: Do not use or store near heat or open flame.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. For control of bacterial and fungal slime in pulp and paper mills, add Busan 110 to the stock or white water going to the lamp pump or to the transfer pump. Addition can be made continuously or intermittently through the pump to feed the product directly from the shipping container. Do not use for control of bacterial and fungal slime in pulp and paper mills. Do not use for control of bacterial and fungal slime in pulp and paper mills. Do not use for control of bacterial and fungal slime in pulp and paper mills.

COOLING TOWER SYSTEMS: For control of bacterial and fungal slime in cooling tower water systems, add Busan 110 to the cooling water at 5 to 10 ppm. Repeat initial dosage until control is achieved. For control of bacterial and fungal slime in cooling tower water systems, add Busan 110 to the cooling water at 5 to 10 ppm. Repeat initial dosage until control is achieved. For control of bacterial and fungal slime in cooling tower water systems, add Busan 110 to the cooling water at 5 to 10 ppm. Repeat initial dosage until control is achieved.

PETROLEUM SECONDARY RECOVERY: Busan 110 is used to control bacterial and fungal slime in water disposal systems. Add 10 to 20 ppm of Busan 110 per 1000 gal of water treated. Add through the means of a metering pump at the line water knock-out, hot well headers, or continuous feed method.

CRUDE AND REFINED OILS: Busan 110 is a preservative for the prevention of bacterial and fungal degradation of crude oil and diesel end distillate heating oils. Add 10 to 20 ppm of Busan 110 per 1000 gal of oil. Addition should be made batchwise where the oil is added to the transfer pump.

STORAGE & DISPOSAL

Store in a cool, dry place. Do not use or store near heat or open flame. Do not store in a confined space. Do not use or store near heat or open flame. Do not store in a confined space. Do not use or store near heat or open flame. Do not store in a confined space. Do not use or store near heat or open flame. Do not store in a confined space.

BUCKMAN LABORATORIES, INC.

1000 N. M. LEAN BLVD. MEMPHIS, TENN. 38103
EPA REG. NO. 1448-34