



U.S. ENVIRONMENTAL PROTECTION AGENCY
Office of Pesticide Programs
Antimicrobials Division (7510C)
1200 Pennsylvania Avenue, N.W.
Washington, D.C. 20460

EPA Reg. Number:

1448-34

Date of Issuance:

NOV 24 2004

Term of Issuance:

CONDITIONAL

Name of Pesticide Product:

MTC 10

NOTICE OF PESTICIDE:
Registration
 Re-registration

Name and Address of Registrant (include ZIP code):

Buckman Laboratories, Inc.
1256 North McLean Blvd.
Memphis, TN 38108

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Antimicrobials Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

Based on your response to the Methylene bis(thiocyanate) Reregistration Eligibility Document, EPA has reregistered the product listed below. This action is taken under the authority of section 4(g)(2)(C) of the Federal Insecticide, Fungicide, and Rodenticide Act(FIFRA),as amended. Reregistration under this section does eliminate the need for continuous reassessment of pesticides. EPA may require submission of data at any time to maintain the registration of your product.

Make the following labeling changes before you release the product for shipment:

- a. Revise the EPA Registration Number to read, "EPA Reg. No.1448-34."
- b. Place the appropriate EPA Establishment No. on the product labeling.

Signature of Approving Official:

Marshall Swindell, Product Manager, Team 33,
Regulatory Management Branch I, Antimicrobials Division


Date:

NOV 24 2004

3. Submit two copies of the revised final printed labeling for the record.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the labeling is enclosed for your records.



Marshall Swindell
Product Manager 33
Regulatory Management Branch I
Antimicrobial Division(7510C)

AL MTC 10

ACTIVE INGREDIENT(S)	
Methylene bis(thiocyanate)	10.0%
INERT INGREDIENTS	90.0%
TOTAL	100.0%

Contains 0.85 pounds active ingredient per gallon. Contains Petroleum Distillates.



**KEEP OUT OF REACH OF CHILDREN
DANGER PELIGRO POISON**

FIRST AID	
If in Eyes	- Hold eye open and rinse slowly and gently with water for 15-20 minutes. - Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. - Call a poison control center or doctor for further treatment advice.
If on Skin, Clothes	- Take off contaminated clothing. - Rinse skin immediately with plenty of water for 15-20 minutes. - Call a poison control center or doctor for treatment advice.
If Swallowed	- Call poison control center or doctor immediately for treatment advice. - Have person sip a glass of water, if able to swallow. - Do not induce vomiting unless told to do so by the poison control center or doctor. - Do not give anything by mouth to an unconscious person.
If Inhaled	- Move person to fresh air. - If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth if possible. - Call a poison control center or doctor for further treatment advice.
HOT LINE NUMBER	
Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment. You may also contact 901-278-0330 or 1-800-BUCKMAN for emergency medical treatment information.	
NOTE TO PHYSICIAN	
NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate use of gastric lavage. Measures against circulatory shock, respiratory depression, and convulsion may be needed.	

Precautionary Statements HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes irreversible eye damage or skin burns. Fatal if swallowed or absorbed through skin or inhaled. Do not get in eyes, on skin, or on clothing. Do not breathe spray mist. Prolonged or frequently repeated skin contact may cause allergic reaction in some individuals. Remove contaminated clothing and wash clothing before reuse.

PERSONAL PROTECTIVE EQUIPMENT (PPE): Applicators and all other handlers must wear: Coversalls over long-sleeved shirt and long pants; Socks and chemical resistant footwear; Goggles or face shield; Chemical-resistant gloves (such as barrier laminate, butyl rubber, nitrile rubber, neoprene rubber, polyvinyl chloride, or viton); Chemical-resistant apron, and Respirator with an organic vapor removing cartridge with a prefilter approved for pesticides (MSHA/NIOSH approved number prefix TC-23C), or a canister approved for pesticides (MSHA/NIOSH approval number prefix TC-14G), or a NIOSH approved respirator with an organic vapor (OV) cartridge or canister with any R, P, or HE prefilter. Handlers participating in hand-dip applications, including introduction of material to and removal from the dip and handling materials still wet from the dip must wear: chemical-resistant full-front aprons with attached full-sleeve gloves.

USER SAFETY RECOMMENDATIONS: Users should wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet. Users should remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users should remove personnel protective equipment immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not apply in marine and/or estuarine or fields. Do not discharge effluent containing this product into lakes, streams, ponds, oceans or public waters unless this product is specifically identified and addressed in a National Pollution Discharge Elimination System (NPDES) permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage authority. For guidance, contact your State Water Board or Regional Office of the U.S. Environmental Protection Agency.

PHYSICAL AND CHEMICAL HAZARDS: Do not use or store near heat or open flame.

Directions for Use

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

PULP AND PAPER MILLS: For control of bacterial and fungal slime on pulp, paper, or paperboard machines, add MTC 10 to the stock or water going to the fan pump in amounts of 0.05 to 1.0 lb per ton of pulp or paper produced. Addition can be made continuously or intermittently required to control the slime. Use of a metering pump to feed the product directly from the shipping container is recommended. To inhibit growth of bacteria in papermaking additives (including alum solutions, animal glue solutions, pigment slurries, coating formulations, and slurries and solutions) MTC 10 is added to these materials in concentrations of 50 to 400 ppm (weight/weight). Pulp that may be held in storage 8 hours to 1 week should be treated with 0.25 to 0.75 kg of MTC 10 per tonne (0.5 to 1.5 lb/ton) of moisture-free pulp. MTC 10 may be added to contaminated fresh water at the rate of 5 to 10 ppm for treatment periods of 6 to 12 hours out of each 24 hours. All persons not directly participating in such spray applications in enclosed or indoor areas must be excluded from the treatment site and from area extending at least 25 feet from the perimeter of the treatment site until application is complete and sprays have settled out of the air.

COMMERCIAL AND INDUSTRIAL RECIRCULATING COOLING/PROCESS WATER SYSTEMS: For control of bacterial and fungal slime commercial and industrial recirculating cooling water systems, add MTC 10 to the cooling or industrial process waters at dosages of 5.5 to 6.8 per 1000 gallons of water in the system (40 to 50 ppm MTC 10, based on the weight of water in the system). Repeat initial dosage until control evident. Then treat the system with 0.7 to 3.4 fl oz of MTC 10 per 1000 gallons of water (5 to 25 ppm MTC 10) every 2 to 5 days, or as needed the system is badly fouled, it should be cleaned to remove old deposits before treatment with MTC 10 is begun. For application to cooling water systems of greater than or equal to 4000 gallons: Do not apply by open pouring of liquid to cooling water system a metering pump delivery system is required for this use and application method.

RETORT SYSTEMS AND PASTEURIZERS: For control of bacterial and fungal slime in retort and pasteurizer process water, MTC 10 is added to the first section of the pasteurizer. For best results, a heavily contaminated system should be cleaned to remove old deposits prior to treatment with MTC 10. The initial dose should be 4.0 to 8.0 fl oz of MTC 10 per 1000 gal of water in the system. To maintain control add 2.0 to 4.0 fl oz per 1000 gal of water. Addition of MTC 10 may be made continuously or intermittently, as required to control growth.

DRILLING FLUIDS: To inhibit bacterial and fungal degradation of the fluids or muds used in the drilling of wells, MTC 10 is incorporated in drilling fluid at concentrations of 0.05 to 0.28% based on the total wet weight of the fluid.

PETROLEUM SECONDARY RECOVERY: MTC 10 is used to control bacteria and fungi in oil field water, polymer, or micellar floods, water-displacement systems, and other oil field water systems at dosage rates of 0.2 to 4.0 fl oz of MTC 10 per 1000 gal of water treated. Additions should be made continuously or intermittently by means of a metering pump at the free water knockouts, before or after injection pumps and injection well head. Continuous Feed Method: When system is noticeably fouled, add 0.6 to 4.0 fl oz MTC 10 per 1000 gal of water continuously until desired degree of control is achieved. Then treat with 0.2 to 1.3 fl oz MTC 10 per 1000 gal of water continuously, or as needed to maintain control. Intermittent Slug Method: When system is noticeably fouled, or to maintain control, add 0.6 to 4.0 fl oz MTC 10 per 1000 gal of water for 4 to 8 hr per day at least 4 to 4 times per week, or as needed to maintain control.

CRUDE AND REFINED OILS: MTC 10 is a preservative for the control of bacteria and fungi that cause the degradation of crude oil and distillate heating oils during storage. It should be added to the oil as it is being transferred from the shipping container to the storage tank at a rate of 0.6 to 6.6 fl oz MTC 10 per 1000 gal of oil. Addition should be made batchwise where mixing occurs or continuously to the suction side of the transfer pump.

FOR THE PRESERVATION OF PIGMENT SLURRIES, ADHESIVES COATINGS AND INKS: MTC 10 should be added at a point in the process system where there will be sufficient time and agitation for good mixing and dispersion. The actual amount of material to be added for preservation of any given formulation will depend on the components and storage time and conditions. Dosage rates should be determined by actual test. For pigment slurries, add MTC 10 at use levels of 0.2-0.5% by weight, based on the total formulation of the slurry to inhibit the growth of bacteria that may cause viscosity loss. For water based adhesives, add MTC 10 at use levels of 0.2-0.5% by weight, based on the total formulation of the adhesive to inhibit the growth of bacteria that may cause viscosity loss. For water-based coatings, add MTC 10 at use levels of 0.2-0.5% by weight, based on the total formulation of the coating to inhibit the growth of bacteria that may cause viscosity loss. Add MTC 10 at use levels of 1.0-5.0%, by weight based on the total formulation of the coating to inhibit discoloration and deterioration caused by fungi on the dry film. For solvent based coatings, add MTC 10 at use levels of 0.5-5.0%, by weight, based on the total formulation of the coating to inhibit discoloration and deterioration caused by fungi on the dry film. For inks, add MTC 10 at use levels of 0.2-2.0% by weight, based on the total formulation of ink to inhibit bacterial and fungal growth in the ink. Not registered for fungal preservation of ink in California.

SOLUTIONS AND EMULSIONS: For the preservation of solutions, emulsions, adhesives, photographic emulsions and other aqueous liquid products, the addition of 75 to 200 ppm MTC 10 is effective. Add MTC 10 at a point in the processing system where there will be sufficient time and agitation for good mixing and dispersion. The exact amount of MTC 10 to be added for the preservation of a given formulation will depend on the components as well as local storage time and conditions. Dosage rates should be determined by actual test. This product is not cleared for use in the manufacture of adhesives, coatings, slurries or inks that may come in contact with food.

AIR WASHER SYSTEMS: For control of bacteria and fungi. Pre-clean the system with detergent and allow air washer to run with fan on for 24 hours. Flush and check nozzles, manually cleaning as necessary. Add 10 to 40 ppm MTC 10 (0.01 to 0.04 gallons/1000 gallons of water) or three times per week or as needed to maintain control. Add MTC 10 to a point where uniform mixing and even distribution will occur.

LEATHER: To prevent bacterial degradation during the soaking of pre-fleshed hides and skins, MTC 10 is used at rates of 30 - 200 ppm (0.03 to 0.02%) based on the weight of the hides/skin and soak water. To prevent mold growth on chrome and vegetable tanned hides and skins during tanning or post-tanning operations prior to finishing, MTC 10 is used at treatment rates of 0.5 - 3.0 pounds per 1000 pounds white weight (lin stock).

METALWORKING FLUIDS: For control of bacteria and fungi in metal working fluids that contain water, add 100 to 400 ppm MTC 10 (0.1 to 0.4 gallons per 1000 gallons of fluid) per week, or as needed to maintain control. Slug feeding to the fluid in the collection tank is recommended. Thoroughly mix the fluid after adding MTC 10 to ensure complete dispersion.