

BUSAN® 881M

Patents issued or pending in the U.S.A. and other countries



Active ingredients
Disodium cyanodithioimidocarbonate 14.7 percent
Potassium N-methyldithiocarbamate 20.3 percent
Inert ingredients
Weight per gallon

Busan 881M is employed for microorganism control in pulp and paper mills, cane sugar mills, and petroleum secondary recovery operations.

In pulp and paper mills, Busan 881M is used to control bacterial and fungal slime. Directions for this use are contained in the Product Data bulletin Busan 881M-For Microorganism Control in Pulp and Paper Mills.

In cane sugar mills producing raw sugar, Busan 881M is employed in the grinding of the cane to inhibit the growth of bacteria and fungi that cause the inversion of sucrose, slime, and odors. Directions for this application are given in the Product Data bulletin Busan 881M -For Microorganism Control in Cane Sugar Mills.

In petroleum secondary recovery operations, Busan 881M is used in waterfloods to control sulfate-reducing bacteria, iron bacteria, and bacteria that cause slime. For directions for this use, see the Product Data bulletin Busan 881M-For Microorganism Control in Petroleum Secondary Recovery Waters.

WARNING

KEEP OUT OF REACH OF CHILDREN

Causes eye damage and skin irritation. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling, Harmful or fatal if swallowed. Avoid contamination of food.

FIRST AID: In case of contact, immediately flush eyes or skin with plenty of water for at least 15 minutes. For eyes, call a physician. Remove and wash contaminated clothing before reuse.

If swallowed, give patient doses of powdered charcoal immediately or all he can swallow of raw egg whites, milk, gruel, or flour and water. Then induce vomiting with salt, soap, or mustard in warm water. Call a physician immediately. NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against

circulatory shock, respiratory depression, and convulsion may be needed.

This product is toxic to fish. Treated effluent should not be discharged where it will drain into lakes, streams, ponds, or public water. Do not contaminate water by cleaning of equipment, or disposal of wastes. Apply this product only as specified on this label.

Do not reuse empty drum. Return to drum reconditioner or destroy it by perforating or crushing and burying in a safe place.

MANUFACTURED BY

BUCKMAN LABORATORIES,

MEMPHIS, TENN. 38108, U.S.A.

EPA Reg. No. 1448-53

9/'74