



BUSAN[®] 30

INDUSTRIAL MICROBICIDE

ACTIVE INGREDIENT:
2-(Thiocyanomethylthio)benzothiazole 30%
INERT INGREDIENTS 70%

EPA REG. NO. 1448-55

KEEP OUT OF REACH OF CHILDREN DANGER

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Causes irreversible eye damage. Causes skin irritation. This product may cause allergic skin reactions. Harmful if swallowed. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse.

FIRST AID: *If in eyes,* flush with plenty of water. Get medical attention. *If on skin,* wash with plenty of soap and water. Get medical attention. *If swallowed,* drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

Note to physician: Probable mucosal damage may contraindicate gastric lavage.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not use in offshore or estuarine drilling operations. Do not discharge into lakes, streams, ponds, or public waters unless in accordance with a NPDES Permit. For guidance, contact the regional office of the Environmental Protection Agency.

PHYSICAL AND CHEMICAL HAZARDS: Do not use or store near heat or open flame.

STORAGE & DISPOSAL

PROHIBITIONS: Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited. Do not reuse empty container.

PESTICIDE DISPOSAL: Pesticide, spray mixture, or rinse water that cannot be used according to label instructions must be disposed of according to applicable Federal, state, or local procedures.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other approved state and local procedures.

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING. Technical assistance in applying Busan 30 for microorganism control as described in the following is available upon request when a description of the problem is provided.

LEATHER: Busan 30 is used at treatment rates of 0.25 to 2 lb/1000 lb of white weight stock to prevent the bacterial or fungal degradation of salt-cured hides and skins and to prevent mold growth on chrome- or vegetable-tanned hides and skins. For treating hides cured with dry salt, Busan 30 should be sprinkled on the hides or should be mixed with the salt before it is applied to the hides. For treating tanned hides, Busan 30 should be dispersed in water and added to the pickling solution or to the tanning liquor at the start of the tanning operation. For preservation of leather-finishing galleys and for slayers, Busan 30 is added to the paste at 0.10 to 0.25% by weight of treated paste and mixed to ensure adequate dispersion.

PULP MILLS: To protect wood chips from fungal degradation during storage, Busan 30 is used at 0.5 to 2 lb/ton of oven-dry wood. It can be applied through a water shower or spray located in the pneumatic conveyor carrying chips from the chipper to the storage pile. For preservation of wet lap or sheet pulp, Busan 30 is used at 0.5 to 4 lb/ton of oven-dry fiber. It is applied to the surfaces of the dewatered pulp by means of sprays or applicator rolls.

PAPER MILLS: To control bacterial and fungal growth on paper and paperboard machines, Busan 30 is added to the white water or stock at 0.1 to 0.5 lb/ton of dry paper or paperboard produced. To make mold-resistant paper or paperboard, Busan 30 is used at 0.05 to 0.1 lb/1000 ft² of surface. For coated paper or board, Busan 30 is incorporated in the coating mix prior to application of the coating. For uncoated paper or board, Busan 30 is dispersed in water,

surface-sizing solution, or other solvent and applied to the surface to be protected by means of an applicator roll. For the preservation of agricultural mulch paper, Busan 30 is used at 1.5 to 5 lb/ton air-dry paper. It is applied to the surfaces of the mulch paper by tub-sizing methods or by means of sprays or applicator rolls before the paper is coated.

PARTICLE BOARD: Busan 30 is employed as a preservative for particle board, insulation board, and other wood-base fiber and particle panel materials. In this use, Busan 30 is mixed with the resin or binding agent at 0.1 to 1% based on the dry weight of the wood.

SAP STAIN CONTROL: Busan 30 is used to control sap stain and mold on freshly cut softwood and hardwood lumber, logs, poles, posts, and timbers. It is applied by dipping, spraying, or pressure impregnation of the wood with a dispersion containing 2 to 6 lb (2 to 6 pt) of Busan 30 per 100 gal of water. Treatment should be made within 24 hr of cutting or sawing, particularly in warm weather, and treated wood should not be exposed to heavy rains soon after treatment.

COOLING TOWERS: Busan 30 is used to protect cooling tower wood against soft or surface rot and internal or dry rot. It is applied by spraying or painting a dispersion containing 0.5 to 0.7% Busan 30 in water onto the clean wood surfaces. The amount applied should provide 0.6 to 0.8 lb Busan 30 per 1000 ft² of wood surface. Soft or surface rot can also be inhibited by periodic shock doses of Busan 30 to the recirculating cooling water at the tower basin or cold well. The dosage should provide 1.25 lb of Busan 30 per 1000 gal of water and the bleedoff should be stopped for 4 to 6 hr after treatment. The shock treatment should be repeated every four months.

COOLING WATER: Busan 30 is used to control algae, bacteria, and fungi in industrial recirculating cooling water systems. Before treatment is begun, the system should be cleaned thoroughly to remove old algal growth, microbiological slime, and other deposits. The system should then be drained, flushed, refilled with water, and treated with an initial dose of 0.6 to 3.7 fl oz Busan 30 per 1000 gal water in the system. Subsequent additions of 0.2 to 1.2 fl oz per 1000 gal should be made every 1 to 5 days, depending on amount of bleedoff and severity of microbiological fouling.

PAINT FILMS: Busan 30 is used to protect paint films against discoloration and deterioration by fungi. For oil paints formulated with modified barium metaborate, zinc oxide, or combinations of these products, Busan 30 is added at 0.1 to 0.5% based on the total weight of the paint. In other oil paints, 0.3 to 1.0% Busan 30 is recommended. The Busan 30 can be dissolved in mineral spirits and added in the letdown or added directly to the finished paints. For water-thinned latex emulsion paints, Busan 30 is used at 0.1 to 1% based on the total weight of the paint. The microbicide can be premixed with wetting agent and added to the pigment slurry or premixed with wetting agent and added to the finished paint.

DRILLING FLUIDS: To inhibit bacterial and fungal degradation of the fluids or muds used in the drilling of wells, Busan 30 is incorporated in the drilling fluid at concentrations of 0.05 to 0.25% based on the total wet weight of the fluid.

PETROLEUM SECONDARY RECOVERY: Busan 30 is used to control sulfate-reducing bacteria, slime-forming bacteria and fungi in oil-field water, polymer, or micellar floods, water-disposal systems, and other oil-field water systems at dosage rates of 0.2 to 3.7 fl oz of Busan 30 per 1000 gal of water treated. Additions should be made continuously or intermittently by means of a metering pump at the free water knockouts, before or after injection pumps and injection well headers. **Continuous Feed Method:** When system is noticeably fouled, add 0.6 to 3.7 fl oz Busan 30 per 1000 gal of water continuously until desired degree of control is achieved. Then treat with 0.2 to 1.2 fl oz Busan 30 per 1000 gal of water continuously, or as needed to maintain control. **Intermittent or Slug Method:** When system is noticeably fouled, or to maintain control, add 0.6 to 3.7 fl oz Busan 30 per 1000 gal of water for 4 to 8 hr per day and 1 to 4 times per week, or as needed to maintain control.

CUTTING FLUIDS: Busan 30 is used to inhibit bacterial and fungal degradation of water-based and water-soluble or emulsifiable cutting fluids and coolants used in metalworking operations. It should be added to the cutting fluid at a rate that will provide 2.5 to 250 parts per million Busan 30 (weight/weight) after final dilution with water. Busan 30 can be added after the dilution or can be added to the concentrate before dilution at a rate of 125 to 1250 parts per million in order to provide the required concentration in the diluted fluid.

CAULKING-SEALANTS & WALLCOVERING ADHESIVES: For details on the use of Busan 30 for the protection of these materials, refer to the bulletin *Busan 30—Preservative for Caulking-Sealants and Vinyl Acetate Wallcovering Adhesives*.

TEXTILES: For directions on the use of Busan 30 to protect textiles from fungal degradation, refer to the bulletin *Busan 30 for the Preservation of Textiles*.

ACCEPTED

JUN 22 1982

Under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended for the Microbicide

MANUFACTURED BY
BUCKMAN LABORATORIES, INC.

1256 N. McLEAN BLVD., MEMPHIS, TENN. 38108, U.S.A.

EPA EST. NO. 1448-TN-1

5/82

1448-55

06/22/1982

1448-55