



BUSAN[®] 1005

INDUSTRIAL MICROBICIDE

ACTIVE INGREDIENT:

2-Hydroxypropyl methanesulfonate	10.0%
INERT INGREDIENTS	90.0%

TOTAL 100.0%

This product contains 0.85 lb active ingredient per gallon
EPA REG. NO. 1448-78

ACCEPTED
with COMMENTS
Letter Dated

**KEEP OUT OF REACH OF CHILDREN
DANGER**

AUG 11 1983
If used as a local insecticide, fungicide, and herbicide, use as intended, for the products registered under EPA Reg. No. 1448-78

STATEMENT OF PRACTICAL TREATMENT

If product gets in eyes, flush with plenty of water for at least 15 minutes. Call a physician. In case of skin contact, wash thoroughly with soap and water. Remove and wash contaminated clothing before reuse. If product is swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate use of gastric lavage. Measures against circulatory shock, respiratory depression, and convulsion may be needed.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER Corrosive. Causes eye damage. Causes severe skin irritation. Harmful if swallowed. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling this product. Remove and wash contaminated clothing. Do not take internally.

ENVIRONMENTAL HAZARDS

Do not discharge into lakes, streams, ponds, or public waters unless in accordance with an NPDES permit. For guidance, contact your Regional Office of the EPA.

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

Busan 1005 is used to control bacterial slime in pulp and paper mills. For this purpose, it should be added to the white water or stock at the rate of 4 to 40 ppm of Busan 1005, based on the total weight of fiber and water at maximum dilution, for treatment periods of 4 to 6 hours. When conditions favor very rapid bacterial slime growth, the Busan 1005 treatment should be repeated every 8 hours or every 12 hours, depending on the severity of the slime problem. Under average conditions of slime growth, the Busan 1005 treatment can be made once every 24 hours.

Busan 1005 is used to inhibit the bacterial degradation of coatings, surface sizes, internal sizes, and starch solutions used in the manufacture of paper and paperboard. It is also employed to inhibit bacterial growth in the synthetic latex emulsions used to manufacture paints. For these applications as a preservative, Busan 1005 should be incorporated in the substrate to be protected at concentrations of 0.4 to 4.0% based on the total weight of the solution or emulsion.

Busan 1005 is used to control the growth of bacteria in commercial and industrial recirculating cooling water systems, and industrial, nonpotable water supply systems. It should not be used in water intended for drinking or food preparation. Before treatment with Busan 1005 is begun, cooling water systems should be cleaned thoroughly to remove slime and other deposits. Then they should be drained, refilled with water, and treated with an initial slug dose of 2.5 to 10.0 fluid ounces of Busan 1005 per 1000 gallons of water in the system. Repeat until control is evident. Then treat with 0.5 to 10.0 fluid ounces per 1000 gallons of water every 1 to 5 days, or as needed. To control the growth of bacteria in industrial water supply systems, treat with 0.5 to 5.0 fluid ounces of Busan 1005 per 1000 gallons of water entering the system, continuously or as needed.

STORAGE AND DISPOSAL

PROHIBITIONS Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL Pesticide spray mixture or rinse water that cannot be used according to label instructions must be disposed of in compliance with Federal or state waste management regulations, except where specifically exempted.

CONTAINER DISPOSAL Triple-rinse (or equivalent). Then offer for recycling or reconditioning, or for other disposal, if available, or for sanitary landfill, or by other approved means.

BUCKMAN LABORATORIES, INC.

1766 N. M. LEAN BLVD. MEMPHIS, TENN. 38103 U.S.A.
TELEPHONE: (901) 521-1111

11 AUG 1983

Buckmann Laboratories
1256 N. McLean Blvd.
Memphis, TN 38108

Attention: Grace Bonner
Regulatory Affairs Specialist

Gentlemen:

Subject: Busan 1005
EPA Registration No. 1449-78
Submission Date: July 25, 1983

The amendment referred to above, submitted in connection with registration under FIFRA sec. 3(c)(7)(A), is acceptable provided that you:

1. Submit and/or cite all data required for registration/reregistration of your product under FIFRA sec. 3(c)(5) when the Agency requires all registrants of similar products to submit such data.
2. Submit five (5) copies of your final printed labeling before you release the product for shipment.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely yours,

John H. Lee
Product Manager (31)
Disinfectants Branch
Registration Division (TS-767C)

Enclosure

DTS: John Lee:DCR-11574:WA:--:TS:KIM:Raven:479-2013:8/8/83

CONCURRENCES							
SYMBOL	TS-767						
SURNAME	Lee						
DATE	8-9-83						

EPA Form 1320 1-4-81

OFFICIAL FILE COPY