



U.S. ENVIRONMENTAL PROTECTION AGENCY
Office of Pesticide Programs
Registration Division (H7505C)
401 "M" St., S.W.
Washington, D.C. 20460

NOTICE OF PESTICIDE:

Registration
 Reregistration
(under FIFRA, as amended)

EPA Reg. Number:

1448-81

Date of Issuance:

MAR 26 2004

Term of Issuance: **Conditional**

Name of Pesticide Product:

Busan 1009

Name and Address of Registrant (include ZIP Code)

Buckman Laboratories, Inc.
1256 McLean Blvd
Memphis, TN 38108

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence for this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

Based on your response to the Reregistration Eligibility Document for Methylene bis thiocyanate RED, EPA has reregistered the above name product subject to the comments recorded in the succeeding paragraph. This action is taken under the authority of section 4(g)(2)(c) of the Federal Insecticide, Fungicide, and Rodenticide Act, as amended. Reregistration under this section does not eliminate the need for continual reassessment of pesticides. EPA may require submission of data at any time to maintain the registration of your product.

1. Make the following label changes:
 - a. Revise the EPA Registration Number to read "EPA Reg. No. 1448-81".

Signature of Approving Official:

Marshall Swindell, PM 33
Regulatory Management Branch 1
Antimicrobial Division (7510W)

Date:

MAR 26 2004

2. Please note that the Agency is accepting the two (2) unsupported use patterns (leather and wood preservative) until after a DCI is issued to request additional data.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely,



Marshall Swindell
Product Manager 33
Regulatory Management Branch 1
Antimicrobial Division (7510C)

Enclosure



Directions for Use

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

NOTE TO USER: Do not apply this product in a way that will contact workers or other persons.

BU

ACTIVE INGREDIENT(S)

2-(Thiocyanomethylthio)benzothiazole.....	10.0%
Methylene bis(thiocyanate).....	10.0%
INERT INGREDIENTS.....	80.0%
TOTAL.....	100.0%

KEEP OUT OF REACH OF CHILDREN DANGER

FIRST AID	
If in Eyes	- Hold eye open and rinse slowly and gently with water for 15-20 minutes. - Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. - Call a poison control center or doctor for further treatment advice.
If on Skin, Clothes	- Take off contaminated clothing. - Rinse skin immediately with plenty of water for 15-20 minutes. - Call a poison control center or doctor for treatment advice.
If Swallowed	- Call poison control center or doctor immediately for treatment advice. - Have person sip a glass of water, if able to swallow. - Do not induce vomiting unless told to do so by the poison control center or doctor. - Do not give anything by mouth to an unconscious person.
If Inhaled	- Move person to fresh air. - If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth if possible. - Call a poison control center or doctor for further treatment advice.
HOT LINE NUMBER	
Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment. You may also contact 901-278-0330 or 1-800-BUCKMAN for emergency medical treatment information.	
NOTE TO PHYSICIAN	
Probable mucosal damage may contraindicate the use of gastric lavage.	

Precautionary Statements HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes irreversible eye damage or skin burns. May be fatal if swallowed or inhaled. Do not get in eyes, on skin, or on clothing. Do not breathe vapor. Prolonged or frequently repeated skin contact may cause allergic reaction in some individuals. For handling activities during exposures, wear either a respirator with an organic vapor removing cartridge with a prefilter approved for pesticides (MSHA/NIOSH approval number prefix TC-23C), or a canister approved for pesticides (MSHA/NIOSH approval number prefix TC-14G), or a NIOSH approved respirator with an organic vapor (OV) cartridge or canister with any R, P, or HE prefilter. Wear coveralls with long-sleeved shirt and long pants, socks and chemical resistant footwear, goggles or face shield, and chemical-resistant gloves (such as barrier laminate, butyl rubber, nitrile rubber, neoprene rubber, polyvinyl chloride, viton, selection category C). Handlers participating in hand-dip applications, including introduction of material to and removal from the dip and handling materials still wear from the dip, must wear chemical-resistant full-front aprons with attached full-sleeve gloves. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables, use detergent and hot water. Keep and wash PPE separately from other laundry. Discard clothing or other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them. For cleaning equipment: Add a chemical-resistant apron. User must wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet. If pesticide gets inside clothing, remove clothing immediately; wash thoroughly and put on clean clothing. Users must remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing. Remove contaminated clothing and wash clothing before reuse.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. For terrestrial uses, do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. **PHYSICAL AND CHEMICAL HAZARDS:** Combustible. Do not use or store near heat or open flames.

SAPSTAIN AND MOLD CONTROL: BUSAN 1009 is used to control sapstain and mold on freshly cut hardwood and softwood lumber, logs, poles, posts and timbers. It is applied by dipping the wood until complete surface wetting is accomplished. Use 0.5 to 2.0 gallons of BUSAN 1009/100 gallons water (5 to 18 lbs of BUSAN 1009/100 gallons water) and agitate vigorously until BUSAN 1009 is thoroughly dispersed. Rates to be used will vary according to temperature, humidity, wood moisture, storage conditions, etc. Under conditions suitable for aggressive mold growth, the high rate mentioned above should be used. Treatment should be made as quickly as possible after lumber is cut and always within 24 hours after cutting.

PAPER MILLS: To control bacterial and fungal growth on paper and paperboard machines, BUSAN 1009 is added to the white water or stock at 0.1 to 0.5 lb./ton of dry paper or paperboard produced. To inhibit the growth of bacteria and fungi in papermaking additives (including alum solutions, animal glue solutions, pigment slurries, coating formulations, and starch slurries and solutions) BUSAN 1009 is added to these materials in concentrations of 50-400 ppm (weight/weight). Pulp that may be held in storage for 8 hours to 1 week should be treated with 0.25 to 0.75 kg of BUSAN 1009 per tonne (0.5 to 1.5 lbs per ton) of moisture-free pulp. BUSAN 1009 may be added to contaminated fresh water at the rate of 0.25-1 ppm for treatment periods of 6-12 hours out of each 24 hours.

PULP MILLS: To protect wood chips from fungal degradation during storage, BUSAN 1009 is used at 0.5 to 2 lbs/ton of oven-dry wood. It can be applied through a water shower located in the pneumatic conveyor carrying chips from the chipper to the storage pile. All persons not directly participating in such spray applications in enclosed or indoor areas must be excluded from the treatment site and from an area extending at least 25 feet from the perimeter of the treatment site until application is complete and sprays have settled out of the air. For preservation of wet lap or sheet pulp, BUSAN 1009 is used at 0.5 to 4 lbs/ton of oven-dry fiber. It is applied to the surface of dewatered pulp by means of applicator rolls. Pulp that may be held in storage for 8 hours to 1 week should be treated with 0.25 to 0.75 kg of BUSAN 1009 per tonne (0.5 to 1.5 lbs per ton) of moisture-free pulp.

PARTICLE BOARD: BUSAN 1009 is employed as a preservative against mold and fungi for particle board, insulation board, and other wood-base fiber and particle panel materials. In this use, BUSAN 1009 is mixed with the furnish, resin, or binding agent at 0.1 to 0.3% based on the dry weight of the wood.

BACTERIOSTATIC PAPER: BUSAN 1009 may be used in the production of bacteriostatic paper and paperboard when included in the coating formulation at a dosage of 0.5-9.0% weight/weight of product and added at the size press or similar application. The bacteriostatic paper and paperboard applications are not to be used in the manufacture of food contact paper, paper coatings, or paperboard.

COOLING TOWERS: BUSAN 1009 is used to protect cooling tower wood against soft or surface rot and internal or dry rot. It is applied by painting a dispersion containing 0.5 to 0.7% BUSAN 1009 in water onto the clean wood surfaces. The amount applied should provide 0.8 to 0.8 lb. BUSAN 1009 per 1000 sq. ft. of wood surface. Soft or surface rot can also be inhibited by periodic shock doses of BUSAN 1009 to the recirculating cooling water at the tower basin or cold well. The dosage should provide 1.25 lb. of BUSAN 1009 per 1000 gal of water and the bleedoff should be stopped for 4 to 6 hr after treatment. The shock treatment should be repeated every four months. In systems greater than or equal to 4000 gallons, do not apply BUSAN 1009 by open pouring of liquid to cooling water systems; a metering pump delivery system is required for this use and application method.

COOLING WATER: BUSAN 1009 is used to control algae, bacteria and fungi in industrial recirculating cooling water systems. Before treatment is begun, the system should be cleaned thoroughly to remove old algal growth, microbiological slime, and other deposits. The system should then be drained, flushed, refilled with water, and treated with an initial dose of 0.6 to 3.7 fl oz BUSAN 1009 per 1000 gal of water in the system. Subsequent additions of 0.2 to 1.2 fl oz per 1000 gal should be made every 1 to 5 days, depending on amount of bleedoff and severity of microbiological fouling. In systems greater than or equal to 4,000 gallons, do not apply BUSAN 1009 by open pouring of liquid to cooling water systems; a metering pump delivery system is required for this use and application method.

DRILLING FLUIDS: To inhibit bacterial and fungal degradation of the fluids or muds used in the drilling of wells, BUSAN 1009 is incorporated in the drilling fluid at concentrations of 0.05 to 0.25% based on the total wet weight of the fluid.

PETROLEUM SECONDARY RECOVERY: BUSAN 1009 is used to control sulfate-reducing bacteria, slime-forming bacteria and fungi in oil-field water, polymer, or micellar floods, water-disposal systems, and other oil-field water systems at dosage rates of 3.9 to 13.0 fl oz of BUSAN 1009 per 1000 gal of water treated. Additions should be made continuously or intermittently by means of a metering pump at the free water knockouts, before or after injection pumps and injection well headers. Continuous Feed Method: When system is noticeably fouled, add 3.9 to 13.0 fl oz BUSAN 1009 per 1000 gal of water continuously until desired degree of control is achieved. Then treat with 3.9 to 13.0 fl oz BUSAN 1009 per 1000 gal of water continuously, or as needed to maintain control. Intermittent or Slug Method: When system is noticeably fouled, or to maintain control, add 3.9 to 13.0 fl oz BUSAN 1009 per 1000 gal of water for 4 to 8 hr per day and 1 to 4 times per week, or as needed to maintain control.

CRUDE AND REFINED OILS: BUSAN 1009 is an oil-soluble preservative for the control of bacteria and fungi that cause the degradation of crude oil and refined fuel oils during storage. Crude and refined oils include, but are not limited to, olefinic, aromatic, paraffinic, and naphthenic oils. It should be added to the oil as it is being transferred from the shipping container to the storage tank at the rate of 0.8 to 6.0 fl. oz. per 1000 gal of oil. Addition should be made batchwise where mixing occurs or continuously to the suction side of the transfer pump.

HIDES AND SKINS: BUSAN 1009 is used to prevent bacterial decomposition of brine cured hides and skins. BUSAN 1009 should be used at a level of 0.003-0.02% (30-200 ppm) based upon the weight of green fleshed hides or skins and saturated brine solution. In raceway operations, BUSAN 1009 can be added directly to the raceway during the addition of hides and operation of paddles. In processor/mixer applications, BUSAN 1009 should be added as dispersion in water. A satisfactory dispersion of 1 part BUSAN 1009 plus 4 parts water can be prepared by adding the BUSAN 1009 to the water (as opposed to adding water to BUSAN 1009) with agitation.

LEATHER: BUSAN 1009 can be used to prevent bacterial decomposition of brine cured, wet salted, air-dried or green fleshed hides/skins in the soaking process. For this purpose, treatment levels of 0.02-0.05% (200-500 ppm) based on the total weight of hides/skins and process water (float). BUSAN 1009 is recommended for the prevention of mold in the storage, transport and processing of wet leather stock such as pickled, vegetable-, chrome-, alternative metal or metal free tanned hides/skins. For this purpose, BUSAN 1009 is used at treatment rates of 0.05-0.25% (500-2500 ppm) of white lime stock weight. A dispersion as described above should be prepared and added to the pickling solution or tanning liquor or during the tanning operation or to the rinse water in a post tanning refloat. The product can also be applied during the fatliquoring process to prevent fungal growth at 0.025-0.075% (250-750 ppm) based on the split and shaved weight of leather being processed.

PIGMENT SLURRIES, COATINGS, NON-FOOD ADHESIVES, CAULKS AND SEALANTS: For the preservation of pigment slurries, coatings, non-food adhesives, caulks and sealants, BUSAN 1009 should be added at a point in the processing system where there is sufficient time and agitation for good mixing and dispersion. The actual amount of material to be added for the preservation of any given formulation will depend on the components and storage time and conditions. Dosage rates should be determined by actual testing. For pigment slurries, coatings, non-food adhesives, caulks and sealants which are subject to bacterial and fungal attack in their containers, BUSAN 1009 should be added at use levels of 0.5 to 0.75% by weight to inhibit this attack. To inhibit fungal growth on the dried coating, non-food adhesive, caulk, or sealant, BUSAN 1009 should be incorporated at a use level of 0.75 to 2.5% by weight. To formulate coatings that are mold resistant and that prevent sapstain and decay by fungi, BUSAN 1009 should be added at use levels of 0.5 to 9.0% based on the total weight of the formulation. The exact level to use will depend on the severity of the contamination as well as the nature and amounts of other components of the formulation.

Do not contaminate water, food, or feed. **PESTICIDE STORAGE:** Do not store more than five drums high. Drums should be stored on a pallet. Damaged drums should be removed and absorbed in sawdust or sand. Do not use when not in use. **PESTICIDE DISPOSAL:** Excess pesticide, spray mixture, or empty container cannot be disposed of by pouring into water, soil, or a sewer. Pesticide or Environmental your EPA Regional Office for disposal. **CONTAINER DISPOSAL:** Recycle, if possible. Do not reuse, or puncture, or burn. Containers allowed by state and local authorities.

Under the Fungicide amenders registered 1/4.

Manufactured by

1256 North McLean

EPA Est. No. 1

EPA Reg. No. 1

Product Weight 9

HMS / NI

Health 3 Flamma