UNITED STATES ENVIRONMENTAL PROTECTION AGENCY FM21 1448-85

MAR 2 7 1996

Ms. Kristin G. Counts Buckman Laboratories 1256 North McLean Memphis, TN 38108

Dear Ms. Counts:

)

)

Subject: Busan 1020 - Revised Labeling • . EPA Registration No. 1448-85 Your Submission Dated December 29, 1995

The Agency has reviewed the revised labeling you submitted for the subject pesticide product and found it to be acceptable provided you make the following correction:

The label shows the EPA Registration No. 1448-361. Make the correction to "EPA Reg. No. 1448-85".

A label stamped "Accepted with Comments" is enclosed for your record. If you have any questions regarding this matter, please feel free to contact me or Sidney Jackson of my staff at (703) 305-7610.

Sincerely yours,

Connie B. Welch Product Manager, Team 21 Fungicide-Herbicide Branch Registration Division (7505C)

Enclosure

CONCURRENCES									
SYMBOL +	7505C		•						
SURNAME +	S. Jackson								
DATE >	Mar 27, 1996								
EPA Form 1320-1 (12-70)						-OF	FICIAL FILE CO	φ γ	

BU	SA	N®	1	020	D
----	----	----	---	-----	---

ACTIVE INGREDIENTS Sodiur INER Total

im N-methyldithiocarbamate	33.0%
T INGREDIENTS	<u>67.0%</u>
Ingredients	100.0%

KEEP OUT OF REACH OF CHILDREN

DANGER PELIGRO

Si Usted no entiende la etiqueta, busque a alquien para que se la explique a usted en detaile. (If you do not understand the label, find someone to explain it to you in detail).

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

Corrosive; causes skin damage. May be fatal if absorbed through skin. Do not get on skin or clothing, Prolonged or frequently repealed skin contact may cause allergic reactions in some individuals.

- Harmful if swallowed
- Harmful it inhaled. Irritating to eyes, nose and throat. Avoid breathing vapor or spray mist. Irritating to eyes. Do not get in eyes.

PERSONAL PROTECTION EQUIPMENT (PPE) FOR NON-WPS (non-agricultural) USES: This product should only be applied by Gertified Pesticide Applicators for Non-WPS or non-agricultural uses.

Handlers Performing Direct - Contact Task

Direct-contact task include:

mixing, loading, or furnigant transfer with or without dry-disconnect fittings

- equipment calibration or artiustment
- equipment cleanup and repair
- product sampling
- spiil cleanup
- rinsale disposal
- + cleanup of small spails

Applicators and other handlers performing direct-contact activities must wear:

- Coveralls over long-sleeved shirt and long pants.
- Chemical-r-sistant cloves,
- Chemical-resistant footwear plus socks,
- Chemical-resistant headgear for overhead exposures,
- . Chemical-resistant apron when cleaning equipment, or when mixing, loading, or transferring without drydisconnect fittings.
- Face sealing goggles, unless full face respirator is worn.
- A respirator with either an organic-vapor-removing cartridge with a prefitter approved for pesticides (MSHA/NKOSH approval number prefix TC-23C), or a canister approved for pesticides (MSHA/NIOSH approval number prefix TC-14G).

USER SAFETY REQUIREMENTS

- 1. Respirator Requirements: When a respirator is required for use with this product, the following criteria must be met
- a. Cartridges or canisters must be replaced daily or when odor or irritation from this product, becomes apparent, whichever is sconer
- b. Respirators must be fit-lasted and lit-checked using a program that conforms to the OSHA requirements (described in 29 CFR Part 1910 134).
- 2. Dispose of Contaminated Clothing: Discard clothing and other absorbent material that have been drenched or heavily contaminated with liquid from this product. Do not reuse them.
- 3. Crean and Maintain PPE. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables, use detergent and hot water. Keep and wash PPE separately from other laundry. Wash PPE after each days use.

User Salety Recommendations

- Users should:
- Wash hands before eating, drinking, chewing guin, using tobacco or using the toller.
- Remove clothing immediately it pesticide gets inside. Then wash thoroughly and put on clean c

Remove PPE immediately after handling this product. Wash the outside of gloves before rer
As soon as possible wash thoroughly and change into clean clothing.

ENVIRONMENTAL HAZARDS: This pesticide is loxic to fish. Do not contaminate water when disp equipment washwaters or rinsate. Do not apply directly to water, to areas where surface water is preto intertidal areas below the mean high-water mark. Do not discharge effluent containing this proc lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirement National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority h notified in writing prior to discharge. Do not discharge effluent containing this product to sewer without previously notifying the local sewage treatment plant authority. For guidance contact yo Water Board or Regional Office of the EPA

STATEMENT OF PRACTICAL TREATMENT: immediately start the procedures given below and o Poison Center, a physician or the nearest hospital. Report the type and extent of exposure, desc victim's symptoms and follow the advise given. IF ON SKIN: Immediately flush skin with large am running water for at least 15 minutes while removing contaminated clothing and shoes. Get medical a immediately, IF IN EYES: Immediately flush eyes with large amounts of running water for at least 15 l Hold eyelids apart to ensure rinsing of the entire surface of the eye and lids with water. Get medical immediately. IF INHALED: Remove to fresh air, if not breathing clear the victim's airway and start in mouth artificial respiration. If breathing is difficult, give oxygen, preferably with a physician's adv medical attention immediately. IF SWALLOWED: Immediately give several glasses of water, bu induce vomiting. If vomiting does occur, give fluids again. Have a physician determine if condition of will permit induction of vomiting or evacuation of stomach. Do not give anything by mouth to an unco person.

STORAGE AND DISPOSAL

Do not contaminate water, food or leed by storage or disposal.

STORAGE: Do not expose to extreme temperatures. Do not stack more than 4 drums high, Le damaged drums should be placed in overpack drums for disposal, Spills should be absorbed in sa sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are toxic, improper disposal of excess pesticide, spray minimate is a violation of Federal law, if these wastes cannot be disposed of by use according instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous representative at your EPA Regional Office for guidance.

CONTAINER DISFOSAL: Triple rinse or equivalent. Then offer for recycling or reconditioning, or j and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

DIRECTIONS FOR USE

it is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Do not apply this product in a way that will contact vorkers or other persons, either directly or through Only protected handlers may be in the area during application. For any requirements specific to your Tribe, consult the Agency responsible for pesticide regulation.

NON-AGRICULTURAL USE REQUIREMENTS

The requirements in this box apply to uses of this product that are NOT within the scope of the 1 Protection Standard for agricultural pesticides (40 CFP Part 170). The WPS applies when this pro used to produce agricultural plants on farms, nurseries, or greenhouses. For non-WPS uses product, PPE requirements are listed in the "HAZARDS TO HUMANS AND DOMESTIC ANI section of this label entitled, "PERSONAL PROTECTION EQUIPMENT (PPE) FOR NON-WPS aoricultural) USES*.

WOOD TREATMENT: Busan 1020 is a liquid used to control internal decay in poles, pillings, and simi timber members. Timber known to have internal decay should be scheduled for treatment befor decayed to the point where replacement is necessary. A groundline area of a 40 inch circumference s pole is taken as a guide and example for application of Busan 1020. For interior decay bore 4 or 5 h inch in diameter and a length about 2 1/2 times the radius of the wood at about a 45 degree angle dow The first hole should be at the groundline and succeeding holes about 6 to 12 inches higher and 30 (rotated from the next lower hole. Inject equal amounts of the fumigana into all holes using a total of 1 pole on the average. Plug the holes with treated wood plugs.

AGRICULTURAL USE REQUIREMENTS

Use this product only in accordance with its labeling and with the Worker Protection Standard, 40 CFR 170. This Standard contains requirements for the protection of agricultural workers on farms, forest nurseries and greenhouses and handlers of agricultural pesticides. It contains requirements for training, decontamination, notification and emergency assistance. It also contains specific instructions and exceptions pertaining to the statements in this labeling about personal protective equipment, restricted entry intervals, and notification to workers. The requirements in this box only apply to uses of this product that are covered by the Worker Protection Standard (WPS). Use this product only in accordance with its labeling and with the Worker Protection Standard, 40 CFR 170. Refer to supplemental labeling under "Agriculture Use Requirements" in the Directions for Use section for information about this standard.

ENTRY RESTRICTIONS:

Outdoors: Entry (including early entry that would otherwise be permitted under the WPS) by any personother than a correctly trained and equipped handlo; who is performing a handling task permitted on this labeling—is PROHIBITED from the start of application until 48 hours after application. In addition, if larps are used for the application, non-handler entry is prohibited while tarps are being removed.

NOTIFIC ATION: Notify workers of the application by warning them orally and by posting fumigant warning signs. The signs must bear the skull and crossbones symbols and state: (1) DANGER/PELIGRO, (2) Area under turnigation, DO NOT ENTER/NO ENTRE, (3) the date and time of turnigation, (4) BUSAN 1020 Fumigant in use, and (5) name, address, and telephone number of applicator. Post the fumigant warning signs instead of the WPS sign for this application, but follow all WPS requirements pertaining to location, legibility, size and timin y of posting and removal.

Outrioors: Post the tumigant warning signs at entrances to treated areas.

PPE FOR ENTRY DURING THE RESTRICTED PERIOD: PPE for entry that is permitted by this labeling is listed in the Hazards to Humans and Domestic Animals section of the supplemental labeling.

AGRICULTURAL TREATMENT GUIDELINES: Refer to supplemental labeling entitled "A Multipurpose Soil Furnighant BUSAN 1020" for use directions. Do not apply this product unless the supplemental labeling is tollowed.

THIS PRODUCT IS NOT TO BE SOLD OR USED FOR AGRICULTURAL PURPOSES IN THE FOLLOWING COUNTIES OF TEXAS: ATASCOSA, CAMERON, DUVAL, HIDALGO, MAVERICK, STARR, WILLACY, ZAPATA

LIMITED WARRANTY AND LIMITATION OF LIABILITY AND REMEDIES

Seller warrants that this product conforms to its chemical description and is reasonably fit for the purpose referred to in the directions for use when used in accordance with the directions under normal conditions. Buyer assumes the risk of any use contrary to such directions or resulting from extreme weather conditions. Seller makes no other warranty or representation of any kind, express or implied, concerning the product, Including NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITTNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE. No such warranties shall be impired by law and no agent of seller is authorized to after this warranty in any way except in writing with a spectral provides plate per exclusive remedy against seller shall be a claim for damages not to exceed up provides plate provides plate provides plate provides plate provides plate provides plate plat authorized to atter this warranty in any way except in writing with a specific rate to this warranty. The exclusive remedy against seller shall be a claim for damages not to exceed the purchase part when product, exclusive remedy against seller shall be a claim for damages for the section of warranty of the COMMENTS without regard to whether such a claim is based upon breach of warranty CPA Letter Dated

onded, for the pesticide spiered ande - EPA Reg. No.

HMIS/NPCA RATING Health 3 Flammability 1 Reactivity 1

Product Weight 9.6 lbs/gal, 1.15 kg/L NET CONTENTS MARKED ON CONTAINER EPA Reg. No. 1448-361**

Manufactured by EPA Est. No. 1448-TN-1, 1448-MO-1 Buckman Laboratories, Inc. 1256 N. McLean Blvd., Memphis, Tennessee 38108, U.S.A (901) 278-0330 or 1-800-BUCKMAN

12/19/95

BEST AVAILABLE COPY

This product contains 3.2 lb. of active ingredient per gallon and weighs 9.6 lb. per gallon.

THIS PRODUCT IS NOT TO BE SOLD IN THE FOLLOWING COUNTIES OF TEXAS: ATASCOSA, CAMERON, DUVAL, HIDALGO, MAVERICK, STARR, WILLACY, ZAPATA.

Manufactured by Buckman Laboratories, Inc. Memphis, Tennessee 38108, U.S.A.

J

÷

IT IS THE RESPONSIBILITY OF THE USER TO READ THIS LABEL AND USE THIS PRODUCT ACCORDINGLY.

NET CONTENTS: AS MARKED ON CONTAINER EPA Reg. No. 1448-85 EPA Est. 1448-TN-1 EPA Est. 1448-MO-1

KEEP OUT OF REACH OF CHILDREN

DANGER PELIGRO

Si Usted no entiende la etiqueta, busque a alquien para que se la explique a usted en detalle. (If you do not understand the label, find someone to explain it to you in detail).

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER

- Corrosive; causes skin damage. May be fatal if absorbed through skin. Do not get on skin or clothing. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.
- Harmful if swallowed
- Harmful if inhaled. Irritating to eyes, nose and throat. Avoid breathing vapor or spray mist.
- Irritating to eyes. Do not get in eyes.

Personal Protective Equipment (PPE)

- (1) Handlers Performing Direct Contact Task Direct contact task include:
- Mixing, loading, or furnigant transfer with or without dry-disconnect fittings
- Equipment calibration C adjustment
- Equipment cleanup and repair
- Product sampling
- Application and soil sealing outside an enclosed cab
- Any activity less than 6 feet from an unshielded pressurized hose containing this product

and the second second

.

- Spill cleanup
- Removal of tarp or plastic film
- Rinsate disposal
- Cleanup of small spills
- Preparing containers for aeration
- Any other handling task not otherwise listed in (2) or (3) below

.

Applicators and other handlers performing direct-contact activities must wear.

- Coveralls over long-sleeved shirt and long pants,

- Waterproof gloves,
- Chemical-resistant footwear plus socks,
- Chemical-resistant headgear for overhead exposures,
- Chemical-resistant apron when cleaning equipment, or when mixing, loading, or transfering without dry-disconnect fittings,
- Face sealing goggles, unless full face respirator is worn.

- A respirator with either an organic-vapor-removing cartridge with a prefilter approved for pesticides (MSHA/NIOSH approval number prefix TC-23C), or a canister approved for pesticides (MSHA/NIOSH approval number prefix TC-14G).

59714

(2) Handlers in Enclosed Cabs

Applicators and other handlers in enclosed cabs must wear;

- Coveralis

- Shoes and socks

Plus, if pungent, rotten-egg odor of this product can be detected inside the enclosed cab, the handlers in the cab must wear:

- Face sealing goggles, unless full face respirator is worn

- A respirator with either an organic-vapor-removing cartridge with a prefitter approved for pesticides (MSHA/NIOSH) approval number prefix TC-23C), or a canister approved for pesticides (MSHA/NIOSH approval number prefix TC-14G). In addition, the PPE specified in (1) for direct-contact activities must be immediately available in the enclosed cab and must be worn if the handler leaves the enclosed cab to perform any direct-contact activity. The enclosed cab must meet the requirements listed in the Worker Protection Standard (WPS) for agricultural pesticides – 40 CFR 170.240(d)(5).

(3) Handlers in Treated Areas While Entry Is Restricted

While entry is restricted (see "Entry Restrictions" in the Agricultural Use Requirements box elsewhere in this labeling), only the following handling task may be performed in a treated area outdoors in which a treatment took place:

- Assessing/adjusting the soil seal

- Operating ventilation equipment

- Assessing pest control, application technique, or application efficacy

- Sampling air or soil for this product

All other task are prohibited until the entry restriction is over.

Handlers performing the above task must wear:

- Coveralls over long-sleeved shirts and long pants,

- Waterproof gloves

- Chemical-resistant footwear and socks

Plus: Handlers must wear if pungent, rotten egg odor of this product can be detected outdoors or after ventilation criteria have been met:

- Face-sealing goggles (unless full-face respirator is worn) and

- A respirator with either an organic-vapor-removing cartridge with a prefilter approved for pesticides (MSHA/NIOSH approvat number prefix TC-23C), or a canister approved for pesticides (MSHA/NIOSH approval number prefix TC-14G).

)

USER SAFETY REQUIREMENTS

1. Respirator Requirements: When a respirator is required for use with this product, the following criteria must be met:

a. Cartridges or canisters must be replaced daily or when odor or irritation from this product becomes apparent, whichever is somer.

b. Respirators must be fit-tested and fit-checked using a program that conforms to the OSHA requirements (described in 29 CFR Part 1910.134).

2. Dispose of Contaminated Clothing: Discard clothing and other absorbent material that have been drenched or heavily contaminated with liquid from this product. Do not reuse them.

3. Clean and Maintain PPE: Follow manufacture's instructions for cleaning/maintaining PPE. If no such instructions for washables, use detergent and hot water. Keep and wash PPE seperately from other laundry. Wash PPE after each days use.

User Safety Recommendations

Users should:

* Wash hands before eating, drinking, chewing gum, using tobacco or using the foilet.

*Remove clothing immediately if pesticide get inside. Then wash throughly and put on clean clothing.

*Remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible wash throughly and change into clean clothing.

AN ALMANTAL MART DESIGNATION AND A COMPARED AND A CARD AND A CARD AND A CARD AND A CARD A CARD A CARD A CARD A

STATEMENT OF PRACTICAL TREATMENT

FIRST AID: Immediately start the procedures given below and contact a Poison Center, a physician or the nearest hospital. Report the type and extent of exposure, describe the victim's symptoms and follow the advise given.

IF ON SKIN: Immediately flush skin with large amounts of running water for at least 15 minutes while removing contaminated clothing and shoes. Get medical attention immediately.

IF IN EYES: Immediately flush eyes with large amounts of running water for at least 15 minutes. Hold eyelids apart to ensure rinsing of the entire surface of the eye and lids with water. Get medical attention immediately.

IF INHALED: Remove to fresh air. If not breathing clear the victim's airway and start mouth-to-mouth artificial respiration. If breathing is difficult, give oxygen, preferably with a physician's advise. Get medical attention immediately.

IF SWALLOWED: Immediately give several glasses of water, but do not induce vomiting. If vomiting does occur, give fluids again. Have a physician determine if condition of patient will permit induction of vomiting or evacuation of stomach. Do not give anything by mouth to an unconscious person.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not contaminate water when disposing of equipment washwaters or rinsate. Do not apply directly to water, to areas where surface water is present, or to intertidal areas below the mean high-water mark. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without proviously notifying the local sewage treatment plant authority. For quidance contact your State Water Board or Regional Office of the EPA.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage or disposal.

١

)

STORAGE: Do not expose to extreme temperatures. Do not stack more than 4 drums high. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Improp.e. disposal of excess pesticide, spray mixture or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse or equivalent. Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

USE PRECAUTIONS

Keep children and pets out of treated area. Keep off desirable lawns and plants. Do not apply within 3 feet of the drip line of desirable plants, shrubs or trees. Do not use in confined areas or where fumes may enter nearby houses. Do not use in greenhouses. Keep container tightly closed when not in use.

PRODUCT INFORMATION

CALIFORNIA ONLY

Application Must Be in Compliance With Technical Information Bulletin-California "Guidelines For All Application Methods For Metam Sodium in California". This Information Bulletin May Be Obtained From Your Local Pesticide Dealer Or Metam Sodium Registrant

Busan 1020 is a water-soluble liquid. When applied to property prepared soil, the liquid is converted into a gaseous furnigant. After a sufficient waiting period, the gas dissipates, let the soil ready for planting. Busan 1020 is recommended for the suppression of weeds and the control of plant parasitic nemation and soilborne fungi that cause reductions in the yield and quality of ornamental, food, and fiber crops.

Busan 1020 will control only those pests in the fumigation zone at the time of treatment. Recontamination may occur subsequent to the fumigant's dissipation from the soil.

Weeds and germinating weed seeds that are suppressed include grasses (annual bluegrass, Bermuda grass, water grass, Johnson grass), sedges (nutgrass), composites (dandelion, ragweed), pinks (chickweed), mints (henbit), goosefoots (lambsquarters), amaranths (pigweed, careless weed), convolvulus (wild morning glory), purstanes, and nightshades. The best weed suppression is obtained when Busan 1020 is applied to weeds that are in an active vegetative growth phase.

The plant parasitic nematodes which Busan 1020 controls include root knot, lesion, dagger, lance, needle, pin, reniform, stunt, stubby root, sting, and spiral. Note: In the Northwest, Busan 1020 will only suppress *Meloidogyne chitwoodi*.

The plant pathogenic fungi controlled include species of Verticillium, Rhizoctonia, Pythium, Phytophthora, Sclerotinia, as well as Sclerotium rolfsii, Armillaria mellea (Oak root fungus), and Plasmodiophora brassicae (Club root fungus), Phoma (Pyrenochaeta) terrestris, Cylindrocladium crotalanae (Cylindrocladium Black Rot).

BUSAN 1020 TREATMENT GUIDELINES

For optimum results from soil fumigation with Busan 1020, certain procedures should be observed at designated times in the treatment program. Described in this section are important guidelines for each of the four stages of the treatment process:

- Planning a Busan 1020 application
- Preparing a field for application applying Busan 1020
- Applying Busan 1020

٠,

)

١

Preparing for planting after application of Busan 1020.

Your Buckman Laboratories representative will help you select the best treatment program for your particular needs.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Do not apply this product in a way that will contact workers or other persons, either directly or through drift. Only protected handlers may be in the area during application. For any requirements specific to your State or Tribe, consult the Agency responsible for pesticide regulation.

AGRICULTURAL USE REQUIREMENTS

Use this product only in accordance with its labeling and with the Worker Protection Standard, 40 CFR 170. This Standard contains requirements for the protection of agricultural workers on farms; forest nurseries and greenhouses and handlers of agricultural pesticides. It contains requirements for training, decontamination, notification and emergency assistance. It also contains epecific instructions and exceptions pertaining to the statements in this labeling about personal protective equipment, restricted entry intervals, and notification to workers. The requirements in this box only apply to uses of this product that are covered by the Worker Protection Standard (WPS).

ENTRY RESTRICTIONS:

Outdoors: Entry (including early entry that would otherwise be permitted under the WPS) by any person-- other than a correctly trained and equipped handler who is performing a handling task permitted on this labeling-- is PROHIBITED from the start of application until 48 hours after application. In addition, if tarps are used for the application, non-handler entry is prohibited while tarps are being removed.

NOTIFICATION: Notify workers of the application by warning them orally and by posting fumigant warning signs. The signs must bear the skull and crossbones symbols and state: (1) DANGER/PELIGRO, (2) Area under fumigation, DO NOT ENTER/NO ENTRE, (3) the date and time of fumigation, (4) BUSAN 1020 Fumigant in use, and (5) name, address, and telephone number of applicator. Post the fumigant warning signs instead of the WPS sign for this application, but follow all WPS requirements pertaining to location, legibility, size and timing of posting and removal. Outdoors: Post the fumigant warning signs at entrances to treated areas.

PPE FOR ENTRY DURING THE RESTRICTED PERIOD: PPE for entry that is permitted by this labeling is listed in the Hazards to Humans and Domestic Animals section of this labeling.

è:

General Precautions for Irrigation Systems

Posting of areas to be chemigated is required when 1) any part of a treated area is within 300 feet of sensitive areas such as residential areas, labor camps, businesses, day care centers, hospitals, in-patient clinics, nursing homes or any public area such as schools, parks, playgrounds, or other public facilities not including public roads, or 2) when chemigated area is open to public such as golf courses.

Posting must conform to the following requirements: Treated areas shall be posted with signs at all usual points of entry and along likely routes of approach from the listed sensitive areas. When there are no usual points of entry, signs must be posted in the corners of the treated areas and in any other location affording maximum visibility to sensitive areas. The printed side of the sign should face away from the treated area towards the sensitive area. The signs should be printed in English. Signs must be posted prior to application and must remain posted until foliage has dried and soil surface water has disappeared. Signs may remain in place indefinitely as long as they are composed of materials to prevent detenioriation and maintain legibility for the duration of the posting period. All words shall consist of letters at least 2 1/2 inches tall, and all letters and the symbol shall be a color which sharply contrasts with their immediate background. At the top of the sign shall be the words KEEP OUT, followed by an octagonal stop sign symbol of at least 8 inches in diameter containing the word STOP. Below the symbol shall be the words PESTICIDE IN IRRIGATIO'N WATER. This sign is in addition to any sign posted to comply with the Worker Protection Standard

Planning a Busan 1020 Application

Time of Application

)

Busan 1020 is applied following harvest and not less than 21 days before a new crop is planted. In some area of North America, fall applications are preferred because the fumes dissipate over the winter, allowing planting to begin as soon as favorable springtime conditions arrive.

Application Over Cover Crops

Busan 1020 can be applied through sprinkler irrigation systems over cover crops such as alfalfa, clover, and such grasses as rye, oats, wheat, and sudan grass. When the product is applied over cover crops, no cultivation of the soil is required before the application of Busan 1020.

Application Rate

Apply 20 to 100 gallons of Busan 1020 per treated acre depending on crop, target pest, and soil properties. Soil properties to consider when determining the application rate include the depth of soil to be treated, soil texture, and percent organic matter.

Busan 1020 can be used at 30 to 50 gallons per treated acre before or following the use of Telone II. A minimum of a 14 day interval must be observed between the application of the products.

Target Pest and Depth of Treatment

For control of fungi causing seed or seedling diseases, treatment of only the top 2 to 4 inches of soil may be required. For control of tiematodes and fungi which occur throughout the rhizosphere, treatment to depths greater than 4 inches may be required. For a given soil type, the required application rate will increase proportionately with the depth of treatment required. For example, if 25 gallons of Busan 1020 per acre is required to treat 4 inches, then 50 gallons of Busan 1020 will be required to treat to a depth of 8 inches. Choose the appropriate application method to distribute Busan 1020 evenly throughout the soil to the required depth.

Organic Matter in the Soil

Except in the case of cover crops, plant material under the soil surface should be thoroughly decomposed before Busan 1020 is applied. Because of the absorbing effect of humus, soils with high levels of organic matter under the surface require higher than usual doses of Busan 1020. For example, muck soils require twice the amount of fumigant that would be used in mineral soils.

Soil Texture

Application rates will vary with the soil texture. For instance, heavy clay soils require more Busan 1020 than light sandy soils.

90714

Preparing a Field for Application

Soil Cultivation

Cultivate the soil thoroughly before treatment, breaking up all large clods. If the soil crusts following pretreatment irrigation, lightly cultivate it again before treatment with Busan 1020.

Soil Temperature During Treatment

At the time of funigation, the soil temperature should be in the range of 40° - 90°F (4° - 32°C) at a depth of 3 inches. To prevent rapid evaporation of the product from the soil, avoid treating soil during times of the day when soil temperatures exceed 90° F (2° C). Instead, make the application during the early morning hours when the soil temperature is coolest.

Measuring the Soil Moisture

Application should be made under "good seed bed moisture conditions"; that is, the soil moisture should be about 50 - 80 percent of field capacity. As a simple field test, squeeze a handful of soil into a ball and then gently try to break it apart with your fingers. If it breaks easily, the soil moisture content is sufficient. If it will not break apart or if water can be squeezed out, it is too wet. When necessary, 1-2 weeks prior to treatment sprinkle or flood, irrigate the soil to increase the moisture content. The soil must be moistened to at least the desired treatment depth.

Area To Be Treated

Busan 1020 can be applied either broadcast or in bands, depending on the crop to be planted. For example, in the production of row crops, band applications are most economical.

Phytotoxicity

)

Busan 1020 is phytotoxic. Protect valuable, non-target plants by stopping soil applications of Busan 1020 at least 3 feet short of the drip line of trees, shrubs, and other desirable plants. Crop injury, lack of effectiveness, or illegal pesticide residues in the crop can result from nonuniform distribution of Busan 1020.

Applying Busan 1020

Busan 1020 may be applied by chemigation, soil injection, disc, rotary tiller, power mulcher, and soil covering methods.

Use of Diluted Busan 1020

DO NOT STORE THE DILUTED PRODUCT. Use Busan 1020 promptly after it has been mixed with water. Although Busan 1020 is stable in its concentrated form, in dilute solutions in water Busan 1020 decomposes over a period of weeks.

Odors During Treatment

Strong odors during or after treatment are a signal that the fumigant is escaping and needs to be sealed in the soil.

Sealing Busan 1020 in Soil

To be most effective, Busan 1020 should be sealed in the soil. Sealing methods include applying irrigation water or plastic 'arpaulins and packing soil with a roller or drag. Tarpaulins should be spread loosely over the treated area and secured to prevent removal by wind. They should remain implace for at least 48 hours. Seven days after treatment, the sealed area should be cultivated to a depth of 2 inches to aerate the trial. When tarpaulins are used to seal the soil, wait at least 21 days before planting.

APPLICATION METHODS

10 af 14

1) CHEMIGATION METHODS

PRECAUTIONARY STATEMENTS

When applying by chemigation methods the following precautions must be observed:

GENERAL

)

A. Apply this product only through the following types of systems: sprinkler including center pivot, lateral move, end tow, side (wheel) roll, traveler, big gun, solid set, or hand move; flood (basin); furrow; border; or drip (trickle) irrigation system(s). Do not apply this product through any other type of irrigation system.

B. Crop injury, lack of effectiveness, or illegal pesticide residues in the crop can result from nonuniform distribution of treated water.

C. If you have questions about calibration, you should contact State Extension Service specialists, equipment manufacturers or other experts.

D. Do not connect an irrigation system used for pesticide application to a public water system unless the pesticide label-prescribed safety devices for public water systems are in place.

E. A person knowledgeable of the chemigation system and responsible for its operation or under the supervision of the responsible person, shall shut the system down and make necessary adjustments should the need arise.

Chemigation Systems Connected to Public Water Systems

A "public water system" is one that provides piped water for human consumption to the public, and the system also either has at least 15 service connections or regularly serves an average of at least 25 individuals daily at least 60 days a year.

Chemigation systems connected to public water systems must contain a functional, reduced-pressure zone, backflow preventor (RPZ) or the functional equivalent in the water supply line upstream from the point of pesticide introduction. As an option to the RPZ, the water from the public water system should be discharged into a reservoir tank prior to pesticide, introduction. There should be a complete physical break (air gap) between the outlet end of the fill pipe and the top or overflow rim of the reservoir tank measuring at least twice the inside diameter of the fill pipe.

The pesticide injection pipeline must contain a functional, automatic, quick-closing check valve to prevent the flow of fluid back toward the injection pump.

The pesticide injection pipeline must contain a functional, normally closed solenoid-operated valve located on the intake side of the injection pump and connected to the system interlock. This valve prevents fluid from being withdrawn from the supply tank when the irrigation system is either automatically or manually shut down.

The system must contain functional interlocking controls to shut off the pesticide injection pump automatically when the water pump motor stops. In cases where there is no water pump, controls on the pesticide injection pump are also needed when the water pressure decreases to the point where pesticide distribution is adversely affected.

Systems must use a metering pump, such as a positive displacement injection pump (e.g., diaphragm pump), effectively designed and constructed of materials that are compatible with pesticides and capable of being fitted with a system interlock.

Drift Prevention

Do not apply when wind speed favors drift beyond the area intended for treatment.

Runoff of Treatment Solution

To prevent runoff of treatment solution during sprinkler application, do not exceed the infiltration rate of the solution into the soil. Should runoff occur, isolate it from growing crops and water sources. Once collected, reapply it to the treated area

CALIFORNIA ONLY

Application Must Be in Compliance With Technical Information Bulletin-California "Application Guidelines For California When Applying Metam Sodium Through Sprinkler Irrigation Systems." This Information Bulletin May Be Obtained From Your Local Pesticide Dealer or Metam Sodium Registrant.

BROADCAST CHEMIGATION METHODS

• Sprinkler Chemigation: Use 50 to 100 gallons Busan 1020 per treated acre for control of nematodes and fungi at a depth of 24 inches. For control of fungi and suppression of weeds at a depth of 6 inches or less, use 20 to 100 gallons per treated acre. Inject the Busan 1020 in enough water to reach the desired treatment depth. The product should be continuously metered into the irrigation system throughout the entire application period. Flush the system with only enough water to clear lines. If the soil surface dried quickly, reseal it with 15 minutes of water once a day for the next day or two.

Use sprinkler systems that give uniform coverage. Apply only through central pivot or solid set sprinkler irrigation systems containing antisiphon and check valves which will prevent water source contamination and overflow of the slurry tank. The system must contain a functional check valve, vacuum relief valve and low pressure drain appropriately located on the irrigation pipeline to prevent water source contamination from backflow. The pesticide injection pipeline must contain a functional, automatic, quick-closing check valve in prevent the flow of fluid back toward the injection pump. The pesticide injection pipeline must also contain a functional, normally closed, solenoid-operated valve located on the intake side of the injection pump and connected to the system interlock to prevent fluid from being withdrawn from the supply tank when the irrigation system is either automatically or manually shut down.

The system must also contain interlocking controls between the metering device and the water pump to ensure simultaneous shut-off. The system must contain functional interlocking controls to automatically shut off the pesticide injection pump when the water pump motor stops. The irrigation line or water pump must include a functional pressure switch which will stop the water pump motor when the water pressure decreases to the point where pesticide distribution is adversely affected. Systems must use a metering pump, such as a positive displacement injection pump (e.g., diaphragm pump) effectively designed and constructed of materials that are compatible with pesticides and capable of being fitted with a system interlock.

NOTE: Effect of Air Temperature and Winds on Sprinkler Application

)

When using a sprinkler application method, apply Busan 1020 only when the air temperature is below 90°F (32°C). This precaution is recommended to guard against evaporation of the product. Either low humidity or high winds can also cause the evaporation of Busan 1020 before it can be drenched into the soil. To prevent wind drift of the furnigant, apply only when wind conditions are suitable.

 Check, Flood (Basin), Furrow and Border Chemigation: Meter Busan 1020 at a steady rate into water during irrigation. Depending upon the kind of pest and the treatment depth desired, use 20 to 100 gallons of Busan 1020 per treated acre in 3 to 18 inches of water per treated acre.

Systems using a gravity flow pesticide dispensing system must meter the pesticide into the water at the head of the field and downstream of a hydraulic discontinuity, such as a drop structure or weir box, to decrease the potential for contaminating the water source from backflow should the water flow stop.

Systems utilizing a pressurized water and pesticide injection system must meet the following requirements:

1. The system must contain a functional check valve, vacuum relief valve, and low pressure drain appropriately located on the irrigation pipeline to prevent water source contamination from backflow.

2. The pestroide injection pipeline must contain a functional, automatic, quick closing check valve to prevent the flow of fluid back toward the injection pump.

3. The pesticide injection pipeline must also contain a functional, normally closed, solenoid-operated valve located on the intake side of the injection pump and connected to the system interlock to prevent fluid from being withdrawn from the supply tank when the irrigation system is either automatically or manually shut down.

4. The system must contain functional interlocking controls to automatically shut off the pesticide injection pump when the pump motor stops.

5. The irrigation line or water pump must include a functional pressure switch which will stop the water pump motor when the water pressure decreases to the point where pesticide distribution is adversely affected.

6. Systems must use a metering pump, such as a positive displacement injection pump (e.g., diaphragm pump) effectively designed and constructed of materials that are compatible with pesticides and capable of being fitted with a system interlock.

BAND, BED OR ROW CHEMIGATION METHODS

• "Drip Chemigation": During pre-irrigation, check drip tape for uniform distribution and repair if necessary. Apply 20 to 100 gallons per treated acre. Inject Busan 1020 continuously into drip line as close as possible to treatment area. Use enough water to thoroughly wet entire desired treatment zone. Two or more lines per bed may be needed to ensure full coverage.

The system must contain a functional check valve, vacuum relief valve, and low pressure drain appropriately located on the irrigation pipeline to prevent water source contamination from backflow. The pesticide injection pipeline must contain a functional, automatic, quick closing check valve to prevent the flow of fluid back toward the injection pump. The pesticide injection pipeline must also contain a functional, normally closed, solenoid-operated vive located on the intake side of the injection pump and connected to the system interlock to prevent fluid from being withdrawn from the supply tank when the irrigation system is either automatically or manually shut down.

The system must contain functional interlocking controls to automatically shut off the pesticide injection pump when the water pump motor stops. The irrigation line or water pump must include a functional pressure switch which will stop the water pump motor when the water pressure decreases to the point where pesticide distribution is adversely affected. Systems must use a metering pump, such as a positive displacement injection pump (e.g., diaphragm pump) effectively designed and constructed of materials that are compatible with pesticides and capable of being fitted with a system interlock.

• Drench Method: Busan 1020 may be applied to finished beds in enough water to soak at least 2 inches deep for suppression of shallow seeded weeds. To avoid contamination by untreated soil, do not disturb the treated area. Apply 20 to 100 gallons of Busan 1020 per treated acre.

2) OTHER FIELD APPLICATION METHODS

BROADCAST METHODS

INJECTION METHOD

)

Soil Injection. Use chisel or shank-type injectors to apply 20 to 100 gallons of Busan 1020 per treated acre into well prepared soil. Seal immediately after treatment.

INCORPORATION METHODS

Disc or Plow Applied Method: Spray dilute Busan 1020 immediately under disc or plow. Use 20 to 100 gallons per treated acre. Follow immediately with a roller to smooth and compact the soil surface.

Rotary Tiller or Power Mulcher. Spray dilute Busan 1020 directly in front of tiller or mulcher. Use 20 to 100 gallons per treated acre. Follow immediately with roller or bed shapper to seal soil surface.

BAND, BED OR ROW METHODS

INJECTION METHOD

Soil Injection: Busan 1020 can be injected into pre-formed plant beds using chisel or shank-type injectors. If a wider treated band is desired, space 2 or more shanks to cover the desired treating width. Seal after treatment. Use 20 to 100 gallons per treated acre.

INCORPORATION METHODS

Rotary Tiller or Power Mulcher: Spray dilute Busan 1020 immediately in front of tiller or mulcher. Use 20 to 100 gallons per treated acre. Follow immediately with roller or bed shaper to seal soil surface.

Soil Covering Methods (Bed-over methods). Busan 1020 may be sprayed or dripped onto the soil immediately ahead of bed-shaping equipment. Cover the Busan 1020 with soil to a depth of 3 to 6 inches. The recommended rate of Busan 1020 is 20 to 100 gallons per treated acre.

Busan 1020 may be applied to prepared or unprepared sites as a coarse spray treatment in a band using standard tractor spray application equipment. Use 75 to 100 gallons of product per treated acre. Apply irrigation water while spraying application is taking place and continue until enough water has been applied to drive the Busan 1020 to the minimum depth of two feet. Do not apply more than one inch of irrigation water. The soil should be at 50 - 80% field capacity at the time of application. Because Busan 1020 is harmful to plants, an appropriate interval must be observed between soil furnigation and planting. Planting can only begin 21 days (minimum) after treatment.

• REPLANT METHOD:

Use 24 to 32 fl. oz. of Busan 1020 per 100 gallons of water. Use 16 gallons of this mixture per 4' x 4' treated area. More water and/or product may be necessary to treat different sized areas to insure product movement to desired depth.

Preparing for Planting After Application of Busan 1020

Effect of Rain

)

)

If a Busan 1020 application is rained on less than 24 hours after treatment, lack of control at and near the soil surface may result.

Recontamination

Precautions must be taken to prevent recontamination of treated soil with plant pathogenic fungi and plant parasitic mematodes. Use clean seeds and plants. Before farm equipment is driven into the treated area, it should be rinsed free of the untreated soil from other fields.

Interval Between Treatment and Planting

Because Busan 1020 is harmful to living plants, an appropriate interval must be observed between soil furnigation and planting. On well drained soils which have a light to medium texture and which are not excessively wet or cold following application, planting can begin 14 -21 days after treatment. If soils are heavy or especially high in organic matter, or if they remain wet and/or cold (below 60°F or 15°C) following application, a minimum interval of 30 days should be observed.

Aeration Before Planting

Soils, including soils high in clay or organic matter, should be allowed to aerate and dry thorcughly after treatment with Busan 1020. During cold and/or wet weather, frequent shallow cultivation can aid the escape of Busan 1020 from the soil.

Testing for Dissipation of Busan 1020

After the waiting period has passed, if there is any question about the complete escape of Busan 1020 from the soil, transplant several seedlings into the treated soil. If the plant develops normally without any signs of chemical injury, crop planting can begin. For assistance in testing for dissipation of Busan 1020, contact your Buckman representative.

L MITED WARRANTY AND LIMITATION OF LIABILITY AND REMEDIES

Seller warrants that this product conforms to its chemical description and is reasonably fit for the purpose referred to in the directions for use when used in accordance with the directions under normal conditions. Buyer assumes any risk of any use contrary to such directions or resulting from extreme weather conditions.

Seller makes no other warranty or representation of any kind, express or implied, concerning the product, including NO IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS OF THE GOODS FOR ANY OTHER PARTICULAR PURPOSE. No such warranties shall be implied by law and no agent of seller is authorized to alter this warranty in any way except in writing with a specific reference to this warranty.

The exclusive remedy against seller shall be a claim for damages not to exceed the purchase price of the product, without regard to whether such a claim is based upon breach of warranty or tort. Any controversy or claim arising out of or relating to this contract, or breach thereof shall be settled by arbitration in accordance with the commercial arbitration rules of the American Arbitration Association, and judgement upon the award rendered by the Arbitrator(s) may be entered in any court having jurisdiction thereof.

Rev. 12/20/95

)