



BUSAN® 1029

ACTIVE INGREDIENTS:

Methylene bis(thiocyanate) 0.5%
 2-(Thiocyanomethylthio)benzothiazole 0.5%
INERT INGREDIENTS 99.0%

EPA REG. NO.

This product weighs 7.0 lbs. per gallon

**KEEP OUT OF REACH OF CHILDREN
WARNING****PRECAUTIONARY STATEMENTS
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

WARNING: Causes eye damage and skin irritation. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful if swallowed or absorbed through skin. Avoid breathing vapors or mist. This product may cause skin sensitization.

STATEMENT OF PRACTICAL TREATMENT: *In case of skin contact, wash promptly and thoroughly with soap and water. If product gets in eyes, flush immediately with copious amounts of clean, cool water for 15 to 20 minutes. Get medical attention immediately. If product is swallowed, call a physician or Poison Control Center. Drink 1 or 2 glasses of water and induce vomiting by touching back of throat with finger. Do not induce vomiting or give anything by mouth to an unconscious person.*

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression, and convulsion may be needed.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not apply directly to water. Permits may be required for discharges containing this pesticide into lakes, streams, ponds, or public water. For guidance, contact the regional office of the Environmental Protection Agency.

PHYSICAL AND CHEMICAL HAZARDS: Do not use or store near heat or open flame.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Busan 1029 is a clear, water-repellent, wood preservative, designed to protect wood against decay, stain-causing fungi and surface mold. In addition Busan 1029 has been especially formulated to penetrate into wood and repel water which will reduce swelling and shrinking and increase dimensional stability and protection against the elements.

Examples of typical uses include wood siding, outdoor furniture, patios and decks, and fences. Busan 1029 can be applied by brush, spray, immersion, or vacuum/pressure impregnation.

When applying Busan 1029 by brush or spray for uses that do not call for subsequent finishing with a paint or varnish, two applications of Busan 1029 are recommended for optimum performance.


When applying Busan 1029 by immersion, a 24-48 hour soak is recommended. For certain applications a 3-5 minute dip may provide adequate protection.

Since Busan 1029 penetrates into the wood and does not form a true film, it will not crack, blister, or peel. Exposure to the elements will cause the gradual natural erosion and allows for easy reapplication. Reapplication is recommended each 2 to 3 years to assure optimum results.

STORAGE & DISPOSAL

STORAGE: Keep container closed when not in use. Store in cool place. Leaking or damaged containers should be placed in a plastic bag and discarded in trash. All pesticides should be kept out of reach of children and stored away from food.

DISPOSAL: Do not reuse empty can. Wrap can and place in trash.



MANUFACTURED BY

BUCKMAN LABORATORIES, INC.

1256 N. GLENN BLVD., MEMPHIS, TENN. 38108, U.S.A.

EPA EST. NO. 1448-TN-1