

BUSAN 1059

BUSAN is a registered trademark.

ACCEPTED

KEEP OUT OF REACH OF CHILDREN MAR - 3 2000
DANGER

Under the Federal Insecticide, Fungicide, and
Rodenticide Act as amended, for the
pesticide, registered under
EPA Reg. No. **1448-104**

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes eye damage and severe skin irritation. Harmful or fatal if swallowed or absorbed through skin. Do not get in eyes or on clothing. Avoid contaminating food. Wear goggles or face shield and rubber gloves when handling. May cause skin sensitization.

STATEMENT OF PRACTICAL TREATMENT: If product gets in eyes, flush with plenty of water for at least 15 minutes. Call a physician. In case of skin contact, wash thoroughly with soap and water. Remove and wash contaminated clothing before reuse. If product is swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution, or, if these are not available, a large quantity of water. Avoid alcohol. Call a physician immediately. **PHYSICIAN'S NOTE:** Probable mucosal damage may contraindicate gastric lavage.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination Systems (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewage systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL/CHEMICAL HAZARDS: Solubility in water: 0.2%. Melting Point: 106°C.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

STORAGE: Protect from temperatures in excess of 140 degrees F. Keep container closed when not in use. If contents are spilled or leaked due to container damage, collect and dispose of in accordance with local, state, and federal pesticide disposal regulations.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for Guidance.

CONTAINER DISPOSAL: Fiber Drums with Liners- Completely empty liner by shaking and tapping sides and bottom to loosen clinging particles. Empty residue into application equipment. Then dispose of liner in a sanitary landfill or by incineration if allowed by state and local authorities. If drum is contaminated and cannot be reused, dispose of in the same manner.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

FOR USE AS A PRESERVATIVE OF INDUSTRIALLY PREPARED WATER BASED SUSPENSIONS (PIGMENT SLURRIES, ADHESIVES, POLYMERS, AND STARCHES), AND AS AN ANTIMICROBIAL IN OILFIELD OPERATIONS.

FOR INDUSTRIALLY PREPARED WATER-BASED SUSPENSIONS (PIGMENT SLURRIES, ADHESIVES, POLYMERS, AND STARCHES) USE:

ACTIVE INGREDIENTS:

Tetrahydro-3,5-dimethyl-2H-1,3,5-thiadiazine-2-thione..... 98.0 %

INERT INGREDIENTS 2.0 %

TOTAL:..... 100.0 %

FOR THE PRESERVATION OF CLAY SLURRIES, ADHESIVES, COATINGS AND HIGH VISCOSITY SUSPENSIONS: For preservation of slurries and high viscosity suspensions, Busan 1059 should be added at a point in the processing system where there will be sufficient time and agitation for good mixing and dispersion. Add Busan 1059 at use levels of 0.01-0.11% by weight, based on the total formulation in slurries of starch, clay, calcium carbonate or titanium dioxide; paper coatings; high viscosity suspensions (e.g., polymers; silica-polymers; silica-polymer combinations); polyvinyl alcohol/polyvinyl acetate based adhesives; starch based adhesives; dextrin based adhesives. For Water Soluble Packaging, this may be accomplished by adding from 1 to 3 pounds of Busan 1059 to each 10,000 pounds based on the weight of the total formulation. The exact amount of material to be added for the preservation of any given formulation will depend on the components and local storage time and conditions. Dosage rates should be determined by actual tests.

FOR OILFIELD OPERATIONS USE:

OILFIELD DRILLING MUDS AND WORKOVER OR COMPLETION FLUIDS: FOR CONTROL OF SLIME-FORMING AND/OR SPOILAGE BACTERIA: Determine the total volume of the circulating system. Calculate the number of pounds of Busan 1059 needed to produce a concentration of 520 ppm (0.18 lb/bbl) Busan 1059 in the drilling mud circulating system. For example, 182 pounds of Busan 1059 per 1000 barrels of drilling fluid will produce the proper concentration. For best results, add Busan 1059 in a thin stream to the pit while the drilling fluid is circulating. As the total volume increases, due to greater well depth, add additional Busan 1059 to maintain the proper concentration. Because of the wide variation in drilling mud composition and bacterial contamination, greater or lesser amounts of the antimicrobial agent may be prescribed.

OILFIELD WATER TREATMENT AND WATER FLOODS: FOR CONTROL OF SLIME-FORMING AND/OR SPOILAGE BACTERIA: Calculate the total volume of water to be treated. Using this volume, calculate the number of pounds of Busan 1059 needed to produce a concentration of approximately 625 ppm Busan 1059. For example, 5.22 pounds of Busan 1059 per each 1000 gallons of total volume will produce this dilution. For Water Soluble Packaging, for example, 1 pound of Busan 1059 per each 191 gallons of total volume will produce this solution.

To maintain bacterial control, 88 ppm Busan 1059 added each week is recommended. This may be accomplished by adding 0.73 pounds of Busan 1059 to each 1000 gallons of total volume. For Water Soluble Packaging, this may be accomplished by adding 1 pound of Busan 1059 to each 1363 gallons of total volume.

RECIRCULATING COOLING WATER SYSTEMS: FOR CONTROL OF ALGAE, FUNGI AND SLIME FORMING BACTERIA: Dosages for recirculating cooling water systems will depend on the condition of the system prior to treatment initiation. Systems which are heavily contaminated should be cleaned first. Apply Busan 1059 to the cleaned system when growth is first noticed according to the following schedule.

INITIAL DOSE: Calculate the total volume of water to be treated. Using this volume, calculate the number of pounds of Busan 1059 needed to produce a concentration of 7.5 - 15 ppm of Busan 1059 per each 1000 gallons of water in the system. For Water Soluble Packaging, this may be accomplished by adding 1 pound of Busan 1059 per each 8,000 - 16,000 gallons of water in the system. This dosage may be a continuous treatment or applied once, twice or three times weekly or as required to control the growth of slime forming organisms.

SUBSEQUENT DOSAGE: When microbial control is evident add 1.25 - 7.5 ppm of Busan 1059 per 1000 gallons of water in the system as a continuous treatment daily or every three days as required to maintain control. For Water Soluble Packaging, this may be accomplished by adding 1 pound of Busan 1059 per each 16,000 - 96,000 gallons of water in the system.

EPOXY FLOORING COMPOUND: For epoxy flooring compounds add Busan 1059 at use levels of 0.05 to 0.6%, by weight, based on the total formulation of the compound to inhibit bacterial and fungal growth on the finished compound.

HMIS/NPCA RATING
Health 3 Flammability 1 Reactivity 1

Product Weight: 4.4 lbs./gal. 0.53 kg/l
NET CONTENTS MARKED ON CONTAINER

EPA Reg. No. 1448-104

Manufactured By EPA Est. No. 1448-TN-1, 1448-MO-1
BUCKMAN LABORATORIES, INC.
1256 N. McLEAN BLVD., MEMPHIS, TN 38108 USA
(901) 278-0330 or 1-800-BUCKMAN

Rev. 01/5/00

1448-104
3/3/2000
Page 121