

NOTICE OF PESTICIDE:



(Under the Federal Insecticide, Fungicide,
and Rodenticide Act, as amended)

NAME OF PESTICIDE PRODUCT

T-5-6

NAME AND ADDRESS OF REGISTRANT (Include ZIP code)

Buckman Laboratories, Inc.
2156 North McLean Boulevard
Memphis, TN 38108

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA section 3(c)(7)(A) provided that you:

1. Submit/cite all data required for registration/reregistration of your product under FIFRA section 3(c)(5) when the Agency requires all registrants of similar products to submit such data.
2. Add the phrase "EPA Registration No. 1448-157" to your label before you release the product for shipment.
3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.



John H. Lee
Product Manager (31)
Antimicrobial Program Branch
Registration Division (TS-767C)

Enclosures

ACCEPTED
with COMMENTS
in EPA Letter Dated:

T-5-6

DEC 20 1988

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide
registered under EPA Reg. No.

INDUSTRIAL MICROBICIDE 1448-157

ACTIVE INGREDIENT:

2-(Thiocyanomethylthio)benzothiazole 5%

INERT INGREDIENTS (Contains Petroleum Distillates) 95%

This product weighs 7.84 pounds per gallon.

KEEP OUT OF REACH OF CHILDREN DANGER

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes irreversible eye damage. Causes skin damage. This product may cause allergic skin reactions. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed.

FIRST AID: *If in eyes,* flush with plenty of water. Get medical attention. *If on skin,* wash with plenty of soap and water. Get medical attention. *If swallowed,* drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

Note to physician: Probable mucosal damage may contraindicate gastric lavage.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not use in offshore or estuarine drilling operations. Do not discharge into lakes, streams, ponds, or public waters unless in accordance with a NPDES Permit. For guidance, contact the regional office of the Environmental Protection Agency.

PHYSICAL AND CHEMICAL HAZARDS: Do not use or store near heat or open flame.

STORAGE & DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

STORAGE: Do not expose to extreme temperatures. Do not stack more than five drums high. Drums should be opened in well-ventilated areas. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or waste is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PESTICIDE WITHOUT ITS LABELING. Technical assistance in applying for microorganism control as described in the following is available if a problem is provided.

COOLING TOWERS: T-5-6

wood against soft or surface rot and internal or dry rot. Use on wood surfaces containing 3.0 to 4.2% T-5-6. The amount applied should provide 3.6 to 4.8 lb of T-5-6 per 1000 ft² of wood surface. Soft or surface rot can be controlled by T-5-6 to the recirculating well. The dosage should provide 7.5 lb of T-5-6 per 1000 ft² of water and the bleedoff should be stopped for 4 to 6 hr after repeated every four months.

COOLING WATER: T-5-6 and fungi in industrial recirculating cooling water systems should be cleaned thoroughly to remove old algal growth. The system should then be drained, flushed, refilled with water, and treated with T-5-6 per 1000 gal of 1.2 to 7.2 fl oz per 1000 gal should be made every 1 to 5 days depending on the severity of microbiological fouling.

DRILLING FLUIDS: To inhibit bacterial and fungal degradation of wells, T-5-6 is used in concentrations of 0.3 to 1.5% based on the total wet weight of the drilling fluid. **PETROLEUM SECONDARY RECOVERY:** T-5-6 is used to control sulfate-reducing bacteria, slime-forming bacteria, and micellar floods, water-disposal systems, and other oil-field operations. Use 3.6 to 22.2 fl oz of T-5-6 per 1000 gal of drilling fluid made continuously or intermittently by means of a metering device after injection pumps and injection well headers. Continuous fouling, add 3.6 to 22.2 fl oz of T-5-6 continuously until desired degree of control is achieved. T-5-6 per 1000 gal of control. Intermittent or Slug Method: When system is fouled, add 3.6 to 22.2 fl oz of T-5-6 per 1000 gal of drilling fluid 4 times per week, or as needed to maintain control.

CUTTING FLUIDS: T-5-6 is used to control degradation of water-based and water-soluble or emulsifiable cutting fluids in metalworking operations. It should be added to the cutting fluid at a concentration of T-5-6 parts per million. T-5-6 can be added at a concentration of T-5-6 to the cutting fluid. To prevent fungal growth on the inside walls of the drill pipe, add T-5-6 to the cutting fluid at a concentration of T-5-6. It is recommended that T-5-6 be prepared to provide a concentration of 3000 to 7500 parts per million.

NET CONTENTS

Manufactured

BUCKMAN LABORATORIES

1256 NORTH McLEA

MEMPHIS, TN 3810

EPA REG. NO. _____

NET CONTENTS _____