

Date 1-24-89

B-103-4

NOT REVIEWED
According to FR Notice 02-2.
Based on Draft Labeling Dated

ACTIVE INGREDIENT:

2-(Thiocyanomethylthio)benzothiazole.....30%

INERT INGREDIENTS.....70%

**KEEP OUT OF REACH OF CHILDREN
DANGER**

PRECAUTIONARY STATEMENTS


HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Causes irreversible eye damage. Causes skin irritation. This product may cause allergic skin reactions. Harmful if swallowed. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse.

STATEMENT OF PRACTICAL TREATMENT: // in eyes, flush with plenty of water. Get medical attention. // on skin, wash with plenty of soap and water. Get medical attention. // swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention.

Note to physician: Probable mucosal damage may contraindicate gastric lavage.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not apply in marine and/or estuarine or fields. Do not discharge effluent containing this active ingredient into lakes, streams, ponds, estuaries, oceans, or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.



Manufactured by:

BUCKMAN LABORATORIES, INC.

1256 NORTH McLEAN BOULEVARD

MEMPHIS, TN 38108

EPA REG. NO.

1448-162

EPA EST. NO.

NET CONTENTS

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

B-103-4 is used to inhibit bacterial and fungal degradation of water-based and water-soluble or emulsifiable cutting fluids and coolants used in metalworking operations. It should be added to the diluted cutting fluid at a rate that will provide 150 to 250 parts per million B-103-4 (weight/weight) after final dilution with water. To prevent fungal growth on the inside walls of the diluted metalworking fluid storage tanks, higher concentrations of B-103-4 are needed. For this application, it is recommended that B-103-4 be added to the diluted cutting fluid as prepared to provide a concentration of 1000 to 1250 parts per million.

STORAGE & DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

PESTICIDE STORAGE Do not expose to extreme temperatures. Do not stack more than five drums high. Drums should be opened in well ventilated areas. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill.

PESTICIDE DISPOSAL Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or mixate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

CONTAINER DISPOSAL Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local