

1448-171

3/3/2000

Page 1 of 3

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

MAR - 3 2000

Buckman Laboratories, Inc.
1256 N. McLean Blvd.
Memphis, TN. 38108


Subject: M-5-1
EPA Registration No. 1448-171
Notification Per Pr-Notice 98-10
Your Notification Dated February 9, 2000

Dear Mr. Barbee:

This will acknowledge receipt of your notification to revise your label submitted under the provisions of FIFRA section 3(c)9. Based on a review of the submitted material, the following comments apply.

The application is acceptable and the notification has been made a part of the records for this file.

Sincerely,



Marshall Swindell
Notification Coordinator
Regulatory Management Branch I
Antimicrobials Division (7510C)

CONCURRENCES

SYMBOL	SURNAME	DATE						

273



United States
Environmental Protection Agency
 Washington, DC 20460

<input type="checkbox"/>	Registration
<input type="checkbox"/>	Amendment
<input checked="" type="checkbox"/>	Other

OPP Identifier Number
 259579

Application for Pesticide - Section I

1. Company/Product Number 1448-171	2. EPA Product Manager Marshall Swindell	3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted
4. Company/Product (Name) M-5-1	PM# 33	
5. Name and Address of Applicant (Include ZIP Code) Buckman Laboratories, Inc. 1256 N. McLean Blvd Memphis, TN 38108 <input type="checkbox"/> Check if this is a new address	6. Expedited Review. In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____	

Section - II

<input type="checkbox"/> Amendment - Explain below.	<input checked="" type="checkbox"/> Final printed labels in response to Agency letter dated _____ N/A
<input type="checkbox"/> Resubmission in response to Agency letter dated _____	<input type="checkbox"/> "Me Too" Application.
<input checked="" type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Other - Explain below.

Explanation: Use additional page(s) if necessary. (For section I and Section II.)

Notification of text omission from the label. The following label language was omitted from the Directions for Use: Crude and Refined Oils on the most recent EPA Stamped Approved label dated, May 05, 1999: "...preservative for the control of bacteria [INSERT, and fungi that cause the degradation of crude oil and refined oils during storage. Crude and refined oils include, but are not] limited to, olefinic...". This language was contained on the previously approved label (Stamp dated, Dec. 18, 1997, but was omitted in error on the most recent label. This notification serves to inform the Agency of this mistake. No other changes have been made to the label.

Section - III

1. Material This Product Will Be Packaged In:				2. Type of Container	
Child-Resistant Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input type="checkbox"/> No		<input type="checkbox"/> Metal	<input type="checkbox"/> Plastic
* Certification must be submitted		If "Yes" Unit Packaging wgt. No. per container	If "Yes" Package wgt. No. per container	<input type="checkbox"/> Glass	<input type="checkbox"/> Paper
				<input type="checkbox"/> Other (Specify) _____	
3. Location of Net Contents Information <input type="checkbox"/> Label <input type="checkbox"/> Container		4. Size(s) Retail Container		5. Location of Label Directions <input type="checkbox"/>	
6. Manner in Which Label is Affixed to Product		<input type="checkbox"/> Lithograph <input type="checkbox"/> Paper glued <input type="checkbox"/> Stenciled		<input type="checkbox"/> Other _____	

Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)		
Name Carl Watson	Title Regulatory Toxicologist	Telephone No. (Include Area Code) (901) 272-6228
Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment or both under applicable law.		6. Date Application Received (Stamp)
2. Signature <i>Carl Watson</i> FOR DEB	3. Title Manager, Regulatory Affairs	
4. Typed Name Dennis L. Barbee, M.S., M.P.A.	5. Date February 9, 2000	

M-5-1

**KEEP OUT OF REACH OF CHILDREN
DANGER**

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive, causes irreversible eye damage and causes skin damage. Harmful or fatal if swallowed or absorbed through the skin. This product is a potential skin sensitizer. Workmen handling this product or treated material should wear impervious gloves, goggles or face shield, and protective clothing. All protective clothing, work shoes or boots, and equipment must be left at the work site at the end of the day. Eating, drinking, or smoking during use of this product is prohibited.

STATEMENT OF PRACTICAL TREATMENT (FIRST AID): In case of skin contact, wash promptly and thoroughly with soap and water. Get medical attention. If product gets in the eyes, hold eyelids open and flush with a steady, gentle stream of water for 15 to 30 minutes. Get medical attention immediately. If product is swallowed, call a physician or Poison Control Center. Do not induce vomiting. First, rinse mouth with large amounts of water or milk. Then slowly give one to two glasses of water or milk. Avoid alcohol. Do not give anything by mouth to an unconscious person. Take individual to the nearest medical facility. If inhaled, remove victim to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. Get medical attention.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. For terrestrial uses, do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARDS: Do not expose to extreme temperatures.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

STORAGE: Do not expose to extreme temperatures. Do not stack more than five drums high. Drums should be opened in well-ventilated areas. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

ACTIVE INGREDIENTS:

Methylene bis(thiocyanate) 2.5 %
2-(Thiocyanomethylthio)benzothiazole 2.5 %

INERT INGREDIENTS: 95.0 %

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

COOLING TOWERS: M-5-1 is used to protect cooling tower wood against soft or surface rot and internal or dry rot. It is applied by painting dispersion containing 2.0 to 2.8% M-5-1 in water onto the clean wood surfaces. The amount applied should provide 2.4 to 3.2 lb. M-5-1 per 1000 sq. ft. of wood surface. Soft or surface rot can also be inhibited by periodic shock doses of M-5-1 to the recirculating cooling water at the tower basin or cold well. The dosage should provide 5.0 lb. of M-5-1 per 1000 gal of water and the bleedoff should be stopped for 4 to 6 hours after treatment. The shock treatment should be repeated every four months. **COOLING WATER:** M-5-1 is used to control algae, bacteria, and fungi in industrial recirculating cooling water systems. Before treatment is begun, the system should be cleaned thoroughly to remove old algal growth, microbiological slime, and other deposits. The system should then be drained, flushed, refilled with water, and treated with an initial dose of 2.4 to 14.8 fl oz M-5-1 per 1000 gal water in the system. Subsequent additions of 0.8 to 4.8 fl oz per 1000 gal should be made every 1 to 5 days, depending on amount of bleedoff and severity of microbiological fouling. **DRILLING FLUIDS:** To inhibit bacterial and fungal degradation of the fluids or muds used in the drilling of wells, M-5-1 is incorporated in the drilling fluid at concentrations of 0.2 to 1.0% based on the total wet weight of the fluid.

PETROLEUM SECONDARY RECOVERY: M-5-1 is used to control sulfate-reducing bacteria, slime-forming bacteria and fungi in oil-field water, polymer, or micellar floods, water-disposal systems, and other oil-field water systems at dosage rates of 15.6 to 52.0 fl oz M-5-1 per 1000 gal of water treated. Additions should be made continuously or intermittently by means of a metering pump at the free water knockouts, before or after injection pumps and injection well headers. Continuous Feed Method: When system is noticeably fouled, add 15.6 to 52.0 fl oz M-5-1 per 1000 gal of water continuously, or as needed to maintain control. Intermittent or Slug Method: When system is noticeably fouled, or to maintain control, add 15.6 to 52.0 fl oz M-5-1 per 1000 gal of water for 4 to 8 hours per day and 1 to 4 times per week, or as needed to maintain control. **CRUDE AND REFINED OILS:** M-5-1 is an oil-soluble preservative for the control of bacteria and fungi that cause the degradation of crude oil and refined oils during storage. Crude and refined oils include, but are not limited to, olefinic, aromatic, paraffinic, and naphthenic oils. It should be added to the oil as it is being transferred from the shipping container to the storage tank at the rate of 2.4 to 24.0 fl oz M-5-1 per 1000 gal of oil. Addition should be made batchwise where mixing occurs or continuously to the suction side of the transfer pump. **FUEL:** M-5-1 can be used to eliminate and/or prevent the growth of bacteria and fungi in distillate and residual fuels including Gasoline, Diesel #1, Diesel #2, and Bunker C. M-5-1 is intended for use in applications where residual and distillate fuels are used such as: bulk storage tanks, locomotive fuel tanks, diesel trucks, diesel boats and ships, farm equipment, construction equipment, and diesel generators. M-5-1 should be added to the fuel at a rate of 1.25 to 2.5 fl oz per 100 gal. M-5-1 should be fed by injecting the product into the fill line as the fuel is being added or added batchwise while the fuel is being added to ensure adequate mixing. For contaminated systems M-5-1 should be added at a shock dose of 2.5 ounces per 100 gal (see table below). For clean systems, the maintenance dose is 1.25 to 2.5 fl oz per 100 gal (see table below).

Gallons of Fuel	Shock Treatment	Maintenance Treatment
20	0.5 fluid ounces	0.25 fluid ounces
40	1.0 fluid ounces	0.5 fluid ounces
60	1.5 fluid ounces	0.75 fluid ounces
100	2.5 fluid ounces	1.25 fluid ounces

M-5-1 is NOT for use in Aviation Fuels.

REVERSE OSMOSIS SYSTEMS: M-5-1 may be used to control microbiological fouling in reverse osmosis systems used for process, wastewater, and other non-potable applications. M-5-1 should be fed to the membrane feedwater at a rate of 1 to 20 ppm (0.12 to 2.4 fl oz/1000 gal). The product should be added continuously for a time period of 1 to 3 hours, 3 to 7 days each week depending on the severity of the problem. For off line cleaning, M-5-1 should be added to provide a level of 20 to 200 ppm (2.4 to 24 fl oz/1000 gal) in the soak solution.

HMIS/NPCA RATING
Health 3 Flammability 2 Reactivity 1

Product Weight: 8.6 lbs./gal. 1.03 kg/l
NET CONTENTS MARKED ON CONTAINER
EPA Reg. No. 1448-171

Manufactured By EPA Est. No. 1448-TN-1
BUCKMAN LABORATORIES, INC.
1256 N. McLEAN BLVD., MEMPHIS, TN 38108 USA
(901) 278-0330 or 1-800-BUCKMAN

3
2
3