

NM-175-1

PM31 1448-180

ACTIVE INGREDIENTS:
 Disodium cyanodithioimidocarbonate 7.35%
 Potassium N-methyldithiocarbamate 10.15%
INERT INGREDIENTS: 82.5%

10/1

KEEP OUT OF REACH OF CHILDREN DANGER

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes irreversible eye damage and skin burns. Harmful if absorbed through skin or inhaled. Do not get in eyes, on skin or on clothing. Wear goggles or faceshield and rubber gloves and protective clothing. Harmful or fatal if swallowed. Avoid contamination of food. Wash thoroughly after handling and before eating, drinking or using tobacco. Remove contaminated clothes and wash before reuse.

STATEMENT OF PRACTICAL TREATMENT: In case of skin contact, wash with plenty of soap and water. Remove contaminated clothing and wash before reuse. If product gets in the eyes, flush immediately with copious amounts of clean, cool water for at least 15 minutes. Get medical attention immediately.

Ingestion: DO NOT INDUCE VOMITING. Rinse with copious amounts of water or milk first. Irrigate the esophagus and dilute stomach contents by slowly giving one (1) to two (2) glasses of water or milk. Avoid giving alcohol or alcohol related products. In cases where the individual is semi-comatose, comatose, or convulsing, DO NOT GIVE FLUIDS BY MOUTH. In case of internal ingestion of the product, seek medical assistance immediately; take individual to nearest medical facility. If inhaled, remove the victim to fresh air. If not breathing, give artificial respiration, preferably mouth to mouth. Get medical attention.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

STORAGE: Do not expose to extreme temperatures. Do not stack more than five drums high. Drums should be opened in well-ventilated areas. Leaking or damaged drums should be placed in overpack drum for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste Representative at your EPA Regional Office for guidance.

CONTAINER DISPOSAL:

Metal: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.
Plastic: Triple rinse (or equivalent). Then offer for recycling or reconditioning or puncture and dispose of in a sanitary landfill by incineration, or, if allowed by state and local authorities, by burning. If burned stay out of smoke.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

NM-175-1 is used to control algae and bacteria in recirculating commercial and industrial water cooling towers. Prior to its use systems must be cleaned to remove algal growth, microbiological slime and other deposits. An initial slug addition of 3.3 to 6.6 fluid ounces of NM-175-1 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 1.1 to 6.6 fluid ounces of NM-175-1 per 1000 gallons of water should be employed every 1 to 5 days as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

REC'D EPA/OPP/DPDI
96 OCT 16 P 4:04

ACCEPTED
JAN 17 1997
Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under
EPA Reg. No. 1448-180

HMS/NPCA RATING
Health 3 Flammability 1 Reactivity 1

Product Weight: 9.3 lbs./gal. 1.11 kg/l
NET CONTENTS MARKED ON CONTAINER
EPA Reg. No. 1448-180

Manufactured By:
BUCKMAN LABORATORIES, INC.
1256 N. McLEAN BLVD., MEMPHIS, TN 38108 USA
(901) 278-0330 OR 1-800-BUCKMAN
EPA Est. No. 1448-TN-1