

KEEP OUT OF REACH OF CHILDREN

DANGER

Precautionary Statements

HAZARDS TO HUMANS AND DOMESTIC ANIMALS.

FIRST AID		
if in Ēyes	- Hold eye open and rinse slowly and gently with water for 15-20 minutes Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye Call a poison control center or doctor for further treatment advice.	
If on Skin, Clothes	- Take off contaminated clothing Rinse skin immediately with plenty of water for 15-20 minutes Call a poison control center for treatment advice.	
if Ingested	- Call poison centrol center or doctor immediately for treatment advice Have person sip a glass of water, if able to swallow Do not induce vomiting unless told to do so by the poison control center of doctor Do not give anything by mouth to an unconscious person.	
if Inhaled	- Move person to fresh air. - If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth if possible. - Call a poison control center or doctor for further treatment advice.	
	HOT LINE NUMBER	

or going for treatment. You may also contact 901-278-0330 or 1-300-BUCKMAN for emergency medical treatment information.

NOTE TO PHYSICIAN

Probable mucosal damage may contraindigate the use of gastric lavage.

DANGER: Corrosive. Causes irreversible eye damage and skin burns. Harmful if absorbed through skin or maled. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield, rubber gloves, and protective clothing. Harmful or fatal if swallowed. Avoid contamination of fcod. Wash throughly after handling and before eating, drinking, or using tobacco. Remove contaminated clothes and wash before reuse.

ENVIRONMENTAL HAZARDS: This posticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the rocal sewage treatment plant authority. For guidance contact you State Water Board or Regional Office of the EPA

ACTIVE INGREDIENTS: Disodium cvanodithicimidocarbonate... ..7.35% Potassium N-methyldithiocarbamate... .10.15% INERT INGREDIENTS:.. .82.50% TOTAL. .100.00%

Storage and Disposal

Do not contaminate water, food, or feed by storage or disposal.

PESTICIDE STORAGE: Do not expose to extreme temperatures. Do not stack more than five drums high. Drums should be opened in well-ventilated areas. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray modure, or rinsate is a violation of Federal Law, if these wastes cannot be disposed of by use according to label instructions, contact your. State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

CONTAINER DISPOSAL:

Metal: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

Plastic: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, by incineration, or, if allowed by state and local authorities, by burning. If burned stay out of smoke.

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No 1448-180

Manufactured by	Buckman Laboratories, Inc.
1256 Noah Mo	CLern Blvd., Memphis Tennessee 38108, USA (901) 274-0330 or 1-800-BUCKMAN
EPA Est. No.	*1448-TN-Y
EDA Pen No	1448-180

Reactivity

Product Weight 9.3 lbs/gal 1.11 kg/l

Flammability 1

Net contents are marked on the container.

HMIS / NPCA Ratings

Health 3

Last Revision

9/12/2002

Directions for Use

soner inconsistent with its labeling.

COOLING WATER SYSTEMS: NM-175-1 is used toibit the growth of microorganisms in industrial, commercial, and institutional cooling water systems. In noticeably fouled systems, NM-175-1 should be added at a rate of 3.3 to 6.6 ft. oz. of NM-175-1 per 1000 gallons of system water (30-60 ppm) until control is evident. Subsequent additions of NM-175-1 should be made to the system as needed at a rate of 1.1 to 6.6 ft. oz, of NM-175-1 per 1000 gallons of system water (10-60 ppm) to maintain control. The frequency of treatment depends upon the severity of the microbiological problem. For best results, the system should be cleaned prior to treatment.

It is a violation of Federal law to use this product i

INDUSTRIAL WATER PURIFICATION SYSTEMS: NM-175-1 is used to control microbiological fouling in industrial water purification systems including reverse osmosis systems, filters, clarifiers, and ion exchange equipment. For off-line treatment, NM-175-1 should be fed at a concentration of 11.5 to 23.0 ft. bz. per 1000 gallons of water (100-200 ppm) for 4 to 8 hours. For on-line maintenance treatment, dosing of 2.3 to 4.6 fl. oz. NM-175-1 per 1000 gallons of water (20-40 ppm) for 6 to 12 hours should be made once a week or as needed to maintain control. Not intended for use in potable water systems.