

D-25-2 NOT REVIEWED  
In Accordance with FR Notice 82-2.  
Based on Draft Labeling Dated

**ACTIVE INGREDIENT:**

Potassium dimethyldithiocarbamate ..... 25.0%

**INERT INGREDIENTS** ..... 75.0%

This product contains 2.3 lb. of active ingredient per gallon and weighs 9.25 lb. per gallon.

**KEEP OUT OF REACH OF CHILDREN  
DANGER**

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND DOMESTIC ANIMALS**

**DANGER:** Corrosive. Causes eye and skin damage. Harmful if swallowed. Do not get in eyes, on skin, or on clothing. Avoid contamination of food. Wear goggles or face shield and rubber gloves when handling. Wash thoroughly after handling.

**STATEMENT OF PRACTICAL TREATMENT:** *In case of skin contact*, wash with plenty of soap and water. Remove contaminated clothing and wash before reuse. *If product gets in the eyes*, flush immediately with copious amounts of clean, cool water for at least 15 minutes. Get medical attention immediately. *If product is swallowed*, promptly drink 1 or 2 glasses of water. Contact a physician or Poison Control Center immediately. **DO NOT INDUCE VOMITING.**

*Note to physician:* Probable mucosal damage may contraindicate gastric lavage.

**ENVIRONMENTAL HAZARDS:** This pesticide is toxic to fish. Do not apply in marine and/or estuarine oil fields. Do not discharge effluent containing this active ingredient into lakes, streams, ponds, estuaries, oceans, or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

Manufactured by:  
**BUCKMAN LABORATORIES, INC.**  
1256 NORTH McLEAN BOULEVARD  
MEMPHIS, TN 38108

EPA REG. NO. 1448-199 EPA EST. NO. \_\_\_\_\_

NET CONTENTS \_\_\_\_\_

**DIRECTIONS FOR USE**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

D-25-2 is used in industrial and/or commercial recirculating cooling tower systems and industrial air-washing systems to control microbiological slime. Prior to the use of D-25-2 in industrial and/or commercial recirculating cooling tower systems, systems should be cleaned to remove algal growth, microbiological slime, and other deposits. Then make an initial slug addition of 4.5 to 6.8 fl. oz. of D-25-2 per 1000 gal. of water to provide 40 to 60 ppm of D-25-2, based on total weight of water in the system. Repeat initial dosage until control is evident. Make subsequent slug addition of 2.3 to 6.8 fl. oz. of D-25-2 per 1000 gal. of water (20 to 60 ppm D-25-2) every 2 to 3 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of recirculating cooling tower systems.

D-25-2 is used in industrial air-washing systems to maintain effective mist-eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 10.6 to 13.6 fl. oz. of D-25-2 per 1000 gal. of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 7.9 to 13.6 fl. oz. of D-25-2 per 1000 gallons of water should be employed every 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or the water collection trays of the airwash system.

D-25-2 is used to control sulfate-reducing bacteria in petroleum secondary-recovery waterflooding operations. In systems fouled with microbiological deposits, D-25-2 should be added as a slug dose to provide a concentration of 16 to 32 ppm (1.9 to 3.8 fl. oz. of D-25-2 per 1000 gal. of water treated). This should be followed by a continuous addition of D-25-2 employing a chemical-metering pump to maintain a concentration of 16 ppm, based on total weight of water treated. Both slug additions and continuous addition of D-25-2 should be made at the heater-treater dump, gathering lines, or receiving tanks. Addition should always be made upstream to the filter.

D-25-2 is also used to inhibit the growth of fungi, bacteria in water-based drilling fluids, completion fluids, packer fluids, and other water-based drilling fluids containing starch, gums, sugars, or other organic materials. For these purposes D-25-2 is added at rates of 5.65 to 9.50 gal per 100 barrels of fluid (0.13 to 0.23% by volume).

**STORAGE AND DISPOSAL**

Do not contaminate water, food, or feed by storage or disposal.  
**STORAGE:** Do not expose to extreme temperatures. Do not stack more than four drums high. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

**PESTICIDE DISPOSAL:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or empty container is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative your EPA Regional Office for guidance.

- CONTAINER DISPOSAL:**
- PLASTIC:** Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in sanitary landfill, by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.
  - METAL:** Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in sanitary landfill, or by other means as approved by state and local authorities.

NOTE: Changes in labeling formula differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above U.S. EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby Registered/Reregistered under the Federal Insecticide, Fungicide, and Rodenticide Act.

A copy of the labeling accepted in connection with this Registration/Reregistration is returned herewith.

Registration is in no way to be construed as an indorsement or approval of this product by this Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This document is not valid unless it is stamped with the following conditions:

1. The registrant must verify that you:


1. The registrant must verify that you have provided the information required by section 3(c)(5) with the registration application and that you have provided the information required by section 3(c)(5) with the registration application.

2. Add the name "EPA Registration No. 111-111" to your label before you release the product for shipment.

3. Submit five (5) copies of your final printed labeling before you release the product for shipment. Refer to the 8-79 enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

  
John H. Lee  
Program Manager (111)  
Antimicrobial Program Branch  
Registration Division (70-7070)

Enclosures

ATTACHMENT IS APPLICABLE

SIGNATURE OF APPROVING OFFICIAL

DATE

ACCEPTED  
with COMMENTS  
in EPA Letter Dated:

D-25-2

DEC 20 1988

U.S. Environmental Protection Agency  
Washington, D.C. 20460

ACTIVE INGREDIENT:

Potassium dimethyldithiocarbamate

INERT INGREDIENTS

This product contains 2.3 lb. of active ingredient per gallon and weighs 9.25 lb. per gallon.

KEEP OUT OF REACH OF CHILDREN  
DANGER

PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes eye and skin damage. Harmful if swallowed. Do not get in eyes, on skin, or on clothing. Avoid contamination of food. Wear goggles or face shield and rubber gloves when handling. Wash thoroughly after handling.

STATEMENT OF PRACTICAL TREATMENT: *In case of skin contact*, wash with plenty of soap and water. Remove contaminated clothing and wash before reuse. *If product gets in the eyes*, flush immediately with copious amounts of clean, cool water for at least 15 minutes. Get medical attention immediately. *If product is swallowed*, promptly drink 1 or 2 glasses of water. Contact a physician or Poison Control Center immediately. **DO NOT INDUCE VOMITING.**

Note to physician: Probable mucosal damage may contraindicate gastric lavage.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not apply in marine and/or estuarine oil fields. Do not discharge effluent containing this active ingredient into lakes, streams, ponds, estuaries, oceans, or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

Manufactured by:  
BUCKMAN LABORATORIES, INC.  
1256 NORTH McLEAN BOULEVARD  
MEMPHIS, TN 38108

EPA REG. NO. \_\_\_\_\_ EPA EST. NO. \_\_\_\_\_

NET CONTENTS \_\_\_\_\_

DIRECTIONS FOR

It is a violation of Federal law to use this product in a manner not consistent with its labeling.

D-25-2 is used in industrial cooling tower systems and industrial air-washing systems. Prior to the use of D-25-2 in recirculating cooling tower systems, systems should be cleaned to remove microbiological slime, and other deposits. Then make a 6.8 fl. oz. of D-25-2 solution. Add 40 to 60 ppm of D-25-2 to the water in the system. Repeat initial dosage until control is achieved. Repeat initial dosage until control is evident. Add 2.3 to 6.8 fl. oz. of D-25-2 per 100 gal. of water ( 20 to 60 ppm D-25-2 ) every 1 to 5 days or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Additions may be made to the sump of recirculating cooling tower systems.

D-25-2 is used in industrial water systems to maintain effective mist-eliminating components. Prior to use, clean to remove bacterial slime and other deposits.

Add 13.6 fl. oz. of D-25-2 to the water in the system. Repeat initial dosage until control is evident. Repeat initial dosage until control is evident. Add 7.9 to 13.6 fl. oz. of D-25-2 per 100 gal. of water. Additions may be made to the sump or the water collection tank.

D-25-2 is used to control microbiological deposits in petroleum secondary-recovery waterflooding operations. Add 16 to 32 oz. of D-25-2 per 1000 gal. of water treated. Both slug additions and continuous additions may be made to the dump, gathering lines, or receiving tanks. Addition should be made to the filter.

D-25-2 is also used to control bacteria in water-based drilling fluids, completion fluids, and based drilling fluids containing starch, gums, sugars, etc. Add 0.13 to 0.23 gal per 100 barrels of fluid ( 0.13 to 0.23 % by volume ) to the fluid.

D-25-2 is also used to control bacteria in water-based drilling fluids, completion fluids, and based drilling fluids containing starch, gums, sugars, etc. Add 0.13 to 0.23 gal per 100 barrels of fluid ( 0.13 to 0.23 % by volume ) to the fluid.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal. STORAGE: Do not expose to extreme temperatures. Do not stack drums. Drums should be placed in overpack drums for disposal. Spills should be cleaned up in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Do not reuse containers or reuse or treat as a source of raw materials. If these wastes cannot be disposed of by other means, contact your State Pesticide or Environmental Control Agency or the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL:

PLASTIC: Triple rinse (or equivalent). Then offer for recycling or reuse, or incineration, or, if allowed by state and local authorities, by other means.

METAL: Triple rinse (or equivalent). Then offer for recycling or reuse, or incineration, or, if allowed by state and local authorities, by other means.