W-30-1

1448-232

4/24/2003

...se

with its labeling.

and industrial water cooling towers and systems. Prior to its
d other deposits. An initial slug addition of 1.90 to 4.75 fluid
40 parts per million of W-30-1 based on the total weight of
ent. Subsequent slug additions of 0.47 to 4.75 fluid ounces of
employed every 2 to 5 days, or as needed. The frequency of
crobiological problem. Slug additions should be made in the
air-washing systems that maintain effective mist eliminating
ne and other deposits. An initial slug dose of 7.1 to 11.9 fluid
age until control is evident. Subsequent slug additions of 4.8
each 1 to 5 days, or as needed. The frequency of addition
em. Slug addition may be made to the sump or to the water

do not contain fish. For maximum effectiveness, decorative
just visible algae growth require an initial dose of 2 to 4 fluid
decorative fountain, add initially 1 to 2 fluid ounces of W-30-1
-30-1 should be made every 5 to 7 days after initial treatment
ols, exterior spas, whirlpools, hot tubs, decorative fountains,
irlpools, hot tubs, decorative fountains, and ponds containing
g just visible algae growth add an initial dose of 24 to 36 fluid
y cleaning. For treatment of a freshly cleaned and filled pool
equent additions of 4 to 9 fluid ounces of W-30-1 should be

gae growth require an initial dose of 2 to 4 ounces of W-30-1
-30-1 should be made every 5 to 7 days after initial treatment
n winter months when pools are not in use. For pools, which
e algae, add 13 to 21 fluid ounces of algaecide per 10,000
e growth, add 25 to 37 fluid ounces per 10,000 gallons. It is
he pool be made for maximum effectiveness. If pool is not
ng the season. W-30-1 is compatible with those chemicals
l.

ay reduce the amount of those chemicals normally required.

ACCEPTED

APR 24 2003

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended for the pesticide, registered under EPA Reg. No. 1448-232

Storage and Disposal

Do not contaminate water, food, or feed by storage or disposal.

PESTICIDE STORAGE: Do not stack more than four drums high. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility.

CONTAINER DISPOSAL:

PLASTIC: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

METAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

Manufactured by **Buckman Laboratories, Inc.**

1256 North McLean Blvd., Memphis, Tennessee 38108, USA

(901) 278-0330 or 1-800-BUCKMAN

EPA Est. No.	**1448-TN-1**		
EPA Reg. No.	**1448-232**		Net contents are marked on the container.
Product Weight	**8.9 lbs/gal.**	**1.07 kg/l**	

HMIS / NPCA Ratings					Last Revision
Health	1	Flammability		Reactivity 1	2/19/2003