

ACTIVE INGREDIENT(S)

Poly[oxysthylene(dimethyliminio)sthylene(dimethyliminio)sthylene	
dichloride]	30.0%
INERT INGREDIENTS	70.0%
	100.0%

This product contains 2.67 lb of active ingredient per gallon and weighs 8.9 lb per gallon.

KEEP OUT OF REACH OF CHILDREN CAUTION

FIRST AD	
lf in Eyes	 Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for further treatment advice.
lf on Skin, Ciothes	Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Call a poison control center or doctor for treatment advice.
lf Swallowed	 Call poison control center or doctor immediately for treatment advice. Have person sip a glass of water, if able to swalkow. Do not induce vomiting unless told to do so by the poison control center or doctor. Do not give anything by mouth to an unconscious person.
lf Inhaled	Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth if possible. Call a poison control center or doctor for further treatment advice.
	HOT LINE NUMBER


You may also contact 901-278-0330 or 1-800-BUCKMAN for emergency medical treatment information.

Precautionary Statements

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. Avoid breathing vapors. Avoid contact with skin, eyes, or clothing. Wash thoroughly with soap and water after handling.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish and aquatic organisms. Do not contaminate water by cleaning of equipment or disposal of waste. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sever systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.



waste disposal facility. CONTAINER DISPOSAL:

and local authorities.

discosal

Storage and Disposal

Do not contaminate water, food, or feed by storage or

PESTICIDE STORAGE: Do not stack more than four

drums high. Leaking or damaged drums should be placed

in overpack drums for disposal. Spills should be absorbed

in sawoust or sand and disposed of in a sanitary landfill.

PESTICIDE DISPOSAL: Wastes resulting from the use of

this product may be disposed of on site or at an approved

PLASTIC: Triple rinse (or equivalent). Then offer for

recycling or reconditioning, or puncture and dispose of in a

sanitary landfill, by incineration, or, if allowed by state and local authorities, by burning, if burned, stay out of smoke.

METAL: Triple rinse (or equivalent). Then offer for

recycling or reconditioning, or puncture and dispose of in a

sanitary landfill, or by other procedures approved by state

 \sim

J

 \mathcal{N}

Keep container closed when not in use.

Directions for Use

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

W-30-4 is used to control algae, bacteria, and fungi in recirculating commercial and industrial water cooling towers. Prior to its use, systems must be cleaned to remove algal growth, microbiological slime, and other deposits. An initial slug addition of 1.90 to 4.75 fluid ounces of W-30-4 per 1000 gallons of water to provide a concentration of 16 to 40 parts per million of W-30-4 based on the total weight of water in the system, is recommended. Repeat initial dosage until control is evident.

Subsequent slug additions of 0.47 to 4.75 fluid ounces of W-30-4 per 1000 gallons of water (4 to 40 parts per million of W-30-4) should be employed every 2 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and the severity of the microbiological problem. Slug additions should be made in the sump of water cooling towers.

W-30-4 is used to control bacteria in industrial air-washing systems that maintain effective mist eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug dose of 7.1 to 11.9 fluid ounces of W-30-4 per 1000 gallons of water is recommended. Repeat initial dosage until control is evident. Subsequent slug addition of 4.8 to 11.9 fluid ounces of W-30-4 per 1000 gallons of gallons of water should be employed each 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug addition may be made to the sump or to the water collection trays of the airwash system.

W-30-4 is used to control the growth of algae in swimming pools, exterior spas, whirlpools, hot tubs, decorative fountains, and ponds that do not contain fish. For maximum effectiveness pools, spas, whirlpools, hot tubs, decorative fountains, and ponds containing heavy growth of algae should be cleaned prior to using W-30-4.

For pools having just visible algae growth add an initial dose of 24 to 36 fluid ounces of W-30-4 per 10,000 gallons of water and remove settled algae debris by cleaning. For treatment of a freshly cleaned and filled pool add initially 13 to 24 fluid ounces of W-30-4 per 10,000 gallons of water. Subsequent additions of 4 to 9 fluid ounces of W-30-4 should be made every 5 to 7 days after initial treatment for maintenance.

Spas, whirlpools, hot tubs, decorative fountain, and ponds having just visible algae growth require an initial dose of 2 to 4 ounces of W-30-4 per 1000 gallons of water. For treatment of freshly cleaned spa, whirlpool, hot tub, decorative fountain, and pond, add initially 1 to 2 fluid ounces of W-30-4 per 1000 of water. Subsequent additions of 0.5 to 0.8 fluid ounces of W-30-4 should be made every 5 to 7 days after initial treatment for maintenance.

W-30-4 will prevent growth of most algae during the off-season winter months when pools are not in use. For pools, which have been property treated during the swimming season and are free of visible algae, add 13 to 21 fluid ounces of algaecide per 10,000 gallons of water. If at the end of swimming season pools have some visible algae growth, add 25 to 37 fluid ounces per 10,000 gallons. It is necessary that a uniform distribution of algaecide, throughout the water and the pool be made for maximum effectiveness. If pool is not covered, it may be necessary to repeat the treatment one or more times during the season.

W-30-4 is compatible with those chemicals normally used to treat pools and spas and is effective at both acid and alkaline pH. W-30-4 can be used in pools and spas treated with chlorine chemicals and may reduce the amount of those chemicals normally required. However, do not mix W-30-4 with concentrated dry or liquid chlorine products.

Manufactured by Buckman Laboratories, Inc. 1256 North McLean Blvd. Memphis, Tennessee 38108, USA (901) 278-0330 or 1-800-BUCKMAN EPA Est. No. 1448-TN-1 EPA Reg. No. 1448-235 Product Weight 8.9 lbs/gal. 1.07 kg/l Net contents are marked on the container. HMIS / NPCA Ratings Flammability | Reactivity () Health Last Revision 1/16/2004