



BUSAN 1060

BUSAN is a registered trademark.

ACTIVE INGREDIENT(S)	78.5%
Hexahydro-1,3,5-tris(2-hydroxyethyl)-s-triazine	21.5%
INERT INGREDIENTS	100.0%
TOTAL	

**KEEP OUT OF REACH OF CHILDREN
DANGER**

FIRST AID	
If in Eyes	- Hold eye open and rinse slowly and gently with water for 15-20 minutes. - Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. - Call a poison control center or doctor for further treatment advice.
If on Skin, Clothes	- Take off contaminated clothing. - Rinse skin immediately with plenty of water for 15-20 minutes. - Call a poison control center or doctor for treatment advice.
If Swallowed	- Call poison control center or doctor immediately for treatment advice. - Have person sip a glass of water, if able to swallow. - Do not induce vomiting unless told to do so by the poison control center or doctor. - Do not give anything by mouth to an unconscious person.
If Inhaled	- Move person to fresh air. - If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth if possible. - Call a poison control center or doctor for further treatment advice.
HOT LINE NUMBER	
Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment. You may also contact 901-278-0330 or 1-800-BUCKMAN for emergency medical treatment information.	
NOTE TO PHYSICIAN	
Probable mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression, and convulsion may be needed.	

Precautionary Statements

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes severe eye and skin damage. Do not get in eyes or on skin. Wash contaminated clothing before reuse. Wear goggles or face shield and rubber gloves when handling this product. Wash thoroughly with soap and water after handling. Harmful or fatal if swallowed. Avoid contamination of food.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARDS: Exposure to fire can generate oxides of carbon and nitrogen.

Directions for Use


It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

BUSAN 1060 is used to inhibit the growth of bacteria in metalworking fluids employed as lubricants or coolants in the machining and processing of metals. BUSAN 1060 is also used in oil field applications such as drilling muds, completion fluids, hydraulic fracturing fluids, and enhanced recovery.

METALWORKING FLUIDS: It is recommended that BUSAN 1060 be added to the dilute metalworking fluid at a concentration of 0.1% to 0.2% (1000 to 2000 ppm) based on the total weight of the metalworking fluid. Where added to the undiluted metalworking fluid, Busan 1060 should be added at a concentration which will provide 0.1% to 0.2% (1000 to 2000 ppm) concentration when diluted with the water for use.

Treatment of the diluted metalworking fluid should be repeated every four weeks as long as the metalworking fluid is used. More frequent treatment may be required if excessive contamination occurs.

OIL FIELD APPLICATIONS: Add BUSAN 1060 to provide a concentration of 0.01% to 0.20% of BUSAN 1060 (0.6 ounces/barrel to 12 ounces/barrel) in the final fluid. Not registered for this use in California.



Storage and Disposal

Do not contaminate water, food, or feed by storage or disposal.

PESTICIDE STORAGE: Do not expose to extreme temperatures. If applicable, do not stack more than four drums high. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

GENERAL: Consult federal, state, or local disposal authorities for approved alternative procedures such as limited open burning.

Manufactured by
Buckman Laboratories, Inc.
1256 North McLean Blvd.
Memphis, Tennessee 38108, USA
(901) 278-0330 or 1-800-BUCKMAN

EPA Est. No. 1448-TN-1
EPA Reg. No. 1448-243
Product Weight 9.6 lbs./gal. 1.15 kg/L
Net contents are marked on the container.

HMS / NPCA Ratings

Health 3 Flammability 1 Reactivity 1
Last Revision 9/27/2004

1448-243
11/16/2004