ACTIVE INGREDIENTS:

Potassium dimethyldithiocarbamate	25.0 %
INERT INGREDIENTS:	
TOTAL:	100.0%

5

R

ú)

KEEP OUT OF REACH OF CHILDREN DANGER

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

FIRST AID		
If Illowed	 Call a poison control center or doctor immediately for treatment advice. 	
	 Have person large quantities of water if able to swallow. 	
-	 Do not induce vomiting. 	
	Avoid alcohol.	
	 Do not give anything by mouth to an unconscious person. 	
If in Eyes	 Hold eye open and rinse slowly and gently with water for 15-20 minutes. 	
	 Remove contact lenses, if present, after the first 5 minutes, then continue 	
	rinsing eye.	
	 Call a poison control center or doctor for treatment advice. 	
If on Skin or	Brush off excess chemical	
Clothing	Take off contaminated clothing.	
Į	 Rinse skin immediately with soap and water for at least 15 minutes. 	
	 Call a poison control center or doctor for treatment advice. 	
If inhaled	Move person to fresh air.	
	If person is not breathing, call 911 or an ambulance, then give artificial respiration,	
*	preferably by mouth-to-mouth, if possible.	
Ľ	Call a poison control center or doctor for further treatment advice.	
	ict container or label with you when calling a poison control center or doctor, or going	
for treatment.	You may also contact 1-800-282-5626 for emergency medical treatment information.	
NOTE TO PHYSICIAN		
F able mucosal damage may contraindicate the use of gastric lavage.		
	and the first second state descent of the second state and the second second state and the second second second	

DANGER: Corrosive. Causes eye and skin damage. Harmful if swallowed. Do not get in eyes, on skin, or on clothing. Avoid contamination of food. Wear goggles or face shield and rubber gloves when handling. Wash thoroughly after handling.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal

PESTICIDE STORAGE: Do not expose to extreme temperatures. Do not stack more than four drums high. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

CONTAINER DISPOSAL: PLASTIC: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

METAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.


DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

COOLING WATER SYSTEMS: D-25-5 is used to inhibit the growth of microorganisms in industrial, commercial and institutional cooling water systems. In noticeably fouled systems, D-25-5 should be added daily at a rate of 4.5 to 6.8 fl. oz. of D-25-5 per 1000 gallons of system water (40-60 ppm) until control is evident. Subsequent additions of D-25-5 should be made to the system as needed at a rate of 2.3 to 6.8 fl. oz. of D-25-5 per 1000 gallons of system water (20-60 ppm) to maintain control. The frequency of treatment depends upon the severity of the microbiological problem. For best results the system should be cleaned prior to treatment.

INDUSTRIAL AIR WASHER SYSTEMS: D-25-5 is used inhibit the growth of microorganisms in industrial air washer systems. In noticeably fouled systems, D-25-5 should be added at a rate of 10.6 to 13.6 fl. oz. of D-25-5 per 1000 galions of water (90-120 ppm) until control is evident. Subsequent additions of D-25-5 should be made to the system as needed at a rate of 7.9 to 13.6 fl. oz. of D-25-5 per 1000 galions of water (70-120 ppm) to maintain control. The frequency of treatment depends upon the severity of the microbiological problem. For best results the system should be cleaned prior to treatment.

INDUSTRIAL WATER PURIFICATION SYSTEMS: D-25-5 is used to control microbiological fouling in industrial water purification systems including reverse osmosis, filters, darifiers, and ion exchange equipment. For off-line treatment, D-25-5 should be fed at a concentration of 9.2 to 23.0 fl. oz. per 1,000 gallons of water (80-200 ppm) for 4 to 8 hours. For on-line maintenance treatment, feeding 2.3 to 4.6 fl. oz. D-25-5 per 1,000 gallons of water (20-40 ppm) for 6 to 12 hours should be made once a week or as needed to maintain control. Not intended for use in potable water systems.



HMIS/NPCA RATING

Product Weight: 9.3 lbs./gal. 1.12 kg/l NET CONTENTS MARKED ON CONTAINER

Health 3 Flammability 1 Reactivity 1

EPA Reg. No. 1448-277

Manufactured By: BUCKMAN LABORATORIES, INC. 1256 N. McLean Blvd., Memphis, TN 38108 USA (901) 278-0330 or 1-800-BUCKMAN EPA Est. No. 1448-TN-1