

1448-339

06/20/2011

1/4



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, D.C. 20460

Buckman Laboratories, Inc.
1256 North McLean Blvd.
Memphis, TN 38108-1241 USA

JUN 20 2011

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

Attention: Jeffery M. Thorne
Director, Compliance

Subject: D-33-3
EPA Reg. No.: 1448-339
Amendment Application Dated May 12, 2011

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, is acceptable. The Agency approves the changes made to the label per the Agency letter dated January 7, 2011.

A stamped copy of the accepted labeling is enclosed. Submit three copies of your final printed labeling to the Agency before distributing or selling the product bearing the revised labeling.

If you have any questions concerning this letter, please contact Abigail Downs at (703) 305-5259.

Sincerely,

Marshall Swindell
Product Manager (33)
Regulatory Management Branch I
Antimicrobials Division (7510P)

D-33-3

2/4

Buckman

ACTIVE INGREDIENT(S)

Potassium dimethyldithiocarbamate.....

12.5%

INERT INGREDIENTS.....

87.5%

TOTAL.....

100.0%

KEEP OUT OF REACH OF CHILDREN

DANGER

FIRST AID	
If in Eyes	- Hold eye open and rinse slowly and gently with water for 15-20 minutes. - Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. - Call a poison control center or doctor for further treatment advice.
If on Skin, Clothes	- Take off contaminated clothing. - Rinse skin immediately with plenty of water for 15-20 minutes. - Call a poison control center or doctor for treatment advice.
If Swallowed	- Call poison control center or doctor immediately for treatment advice. - Have person sip a glass of water, if able to swallow. - Do not induce vomiting unless told to do so by the poison control center or doctor. - Do not give anything by mouth to an unconscious person.
If Inhaled	- Move person to fresh air. - If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth if possible. - Call a poison control center or doctor for further treatment advice.
HOT LINE NUMBER	
Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment. You may also contact 901-767-2722 for emergency medical treatment information.	
NOTE TO PHYSICIAN	
Probable mucosal damage may contraindicate the use of gastric lavage.	

Precautionary Statements

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes eye and skin damage. Harmful if swallowed. Do not get in eyes, on skin, or on clothing. Avoid contamination of food. Wear goggles or face shield and rubber gloves when handling. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

JUN 20 2011

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide
registered under EPA Reg. No.
1448-339

D-33-3

3/4

Buckman

Directions for Use

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

COOLING WATER SYSTEMS: D-33-3 is used to inhibit the growth of microorganisms industrial, commercial and institutional cooling water systems. In noticeably fouled systems, D-33-3 should be added daily at a rate of 9.5 to 14.2 fl. oz. of D-33-3 per 1000 gallons of system water (80 - 120 ppm) until control is evident. Subsequent additions of D-33-3 should be made to the system as needed at a rate of 4.7 to 14.2 fl. oz. of D-33-3 per 1000 gallons of system water (40-120 ppm) to maintain control. The frequency of treatment depends upon the severity of the microbiological problem. For best results the system should be cleaned prior to treatment.

INDUSTRIAL AIR WASHER SYSTEMS: D-33-3 is used to inhibit the growth of microorganisms in industrial air washer systems. In noticeably fouled systems, D-33-3 should be added at a rate of 22.2 to 28.4 fl. oz. of D-33-3 per 1000 gallons of water (180-230 ppm) until control is evident. Subsequent additions of D-33-3 should be made to the system as needed at a rate of 16.5 to 28.4 fl. oz. of D-33-3 per 1000 gallons of water (130-230 ppm) to maintain control. The frequency of treatment depends upon the severity of the microbiological problem. For best results the system should be cleaned prior to treatment.

INDUSTRIAL WATER PURIFICATION SYSTEMS: D-33-3 is used to control microbiological fouling in industrial water purification systems including reverse osmosis, filters, clarifiers, and ion exchange equipment. For off-line treatment, D-33-3 should be fed at a concentration of 20 to 50 fl. oz. per 1,000 gallons of water (160-400 ppm) for 4 to 8 hours. For on-line maintenance treatment, feeding 5 to 10 fl. oz. D-33-3 per 1,000 gallons of water (40-80 ppm) for 6 to 12 hours should be made once a week or as needed to maintain control. **Not intended for use in potable water systems. Not registered for this use in California.**

PETROLEUM SECONDARY RECOVERY WATERFLOODING OPERATIONS: D-33-3 is used to control sulfate-reducing bacteria in petroleum secondary waterflooding operations. In systems fouled with microbiological deposits, D-33-3 should be added as a slug dose to provide a concentration of 32 to 64 ppm (3.9 to 7.8 fl. oz. of D-33-3 per 1000 gal. of water treated). This should be followed by a continuous addition of D-33-3 employing a chemical metering pump to maintain a concentration of 32 ppm, based on the total weight of water treated. Both slug additions and continuous addition of D-33-3 should be made at the heater-treater pump, gathering lines, or receiving tanks. Additions should always be made upstream of the filter. D-33-3 is also used to inhibit the growth of fungi and bacteria in water-based drilling muds, completion fluids, packer fluids, and other water-based fluids containing starch, gums, sugars, or other organic materials. For these purposes, D-33-3 is added at rates of 11.82 to 19.85 gal. per 100 barrels of fluid (0.28 to 0.47% by volume).

ACCEPTED
with COMMENTS
in EPA Letter Dated:

JUN 20 2011

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

1448-339

D-33-3

ACCEPTED
with COMMENTS
in EPA Letter Dated:

JUN 20 2011

4/4
Buckman

under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the Pesticide,
registered under EPA Reg. No 1448-339

Storage and Disposal

Do not contaminate water, food, or feed by storage or disposal.

PESTICIDE STORAGE: Do not expose to extreme temperatures. Do not stack more than four drums high. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

CONTAINER DISPOSAL:

(Text for all nonrefillable containers)

Nonrefillable container. Do not reuse or refill this container. Offer for recycling, if available. Triple rinse container (or equivalent) promptly after emptying.

{Liquid residue removal statement for nonrefillable containers with capacity of 5 gals or less}

Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for the later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

{Liquid residue removal statement for nonrefillable containers with capacity of >5 gals}

Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times.

(Text for all nonrefillable containers)

Then offer for recycling if available or reconditioning, if appropriate, or puncture and dispose of in a sanitary landfill, or, if allowed by state and local authorities by burning. If burned, stay out of smoke.

{Text for refillable containers}

Refillable container. Refill this container with pesticide only. Do not reuse this container for any other purpose. Cleaning the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller.

For containers larger than 55 gallons:

To clean the container prior to refilling or disposal, use a pressure wash as follows: Empty the remaining contents into application equipment or a mix tank. Use a pressure wash system that rinses all interior sides with water and that is rated at >40 psi and >120F. Pressure wash the container for a length of time that ensures that a minimum 25% of the container volume of water is used. During the pressure wash, ensure that the container valve is left open for continuous draining. Collect the rinsate and empty into application equipment or a mix tank or store rinsate for later use or disposal. Allow container to drain for 10 minutes after pressure wash is completed.

For containers 55 gallons and smaller:

To clean the container prior to refilling or disposal, use a triple rinse wash as follows: Empty the remaining contents from this container into application equipment or a mix tank. Fill the container about 10 percent full with water. Agitate vigorously. Pour or pump rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this rinsing procedure two more times.

Do not discharge rinsate containing this product unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge rinsate containing this product to sewer systems without prior approval from the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

Batch code: _____

Manufactured by

Buckman Laboratories, Inc.

1256 North McLean Blvd., Memphis, Tennessee 38108, USA
(901) 278-0330 or 1-800-282-5626

EPA Est. No. 1448-TN-1

EPA Reg. No. 1448-339

Product Weight 8.8 lbs/gal 1.05 kg/l

Net contents are marked on the container.

HMIS / NPCA Ratings

Health 3 Flammability 1 Reactivity 1

Last Revision

2/26/2011