

KEEP OUT OF REACH OF CHILDREN

DANGER

Precautionary Statements

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

FIRST AID		
- Hold eye open and rinse slowly and gently with water for 15-20 minutes Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye Call a poison control center or doctor for further treatment advice.		
- Take off contaminated clothing Rinse skin immediately with plenty of water for 15-20 minutes Call a poison control center for treatment advice.		
- Call poison control center or doctor immediately for treatment advice Have person sip a glass of water, if able to swallow Do not induce vomiting unless told to do so by the poison control center or doctor Do not give anything by mouth to an unconscious person.		
- Move person to fresh air If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth if possible Call a poison control center or doctor for further treatment advice.		
HOT LINE NUMBER		

Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment. You may also contact 901-278-0330 or 1-800-BUCKMAN for emergency medical treatment information.

NOTE TO PHYSICIAN

Probable mucosal damage may contraindicate the use of gastric lavage.

DANGER: Corrosive. Causes irreversible eye damage. Causes skin damage. This product may cause allergic skin reactions. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not use in offshore or estuarine drilling operations. For terrestrial uses, do not apply directly to water, or to areas wt. urface water is present or to intertidal areas below the mean high water mark. Do not die, go effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARDS: Do not use or store near heat or open flame.

ACTIVE INGREDIENTS:	
2-(Thiocyanomethyithio)benzothiazole	5.0%
NERT INGREDIENTS:	95.0%
TOTAL	100.00%

Storage and Disposal

Do not contaminate water, food, or feed by storage or disposal. STORAGE: Do not expose to extreme temperatures. Do not stack more than five drums high. Drums should be opened in well-ventilated areas. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfilf. Keep container closed when not in use. PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray moture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.



JAN 2 3 2003

Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 1 4 4 8 3 4 1

	Buckman Laborato	ries, inc.	
1256 North	McLean Blvd., Memphis, Tennessee (901) 278-0330 or 1-800-Bi	•	
EPA Est. No.	1448-TN-1		
EPA Reg. No.	1448-341	Net contents are marked o	
Product Weight	7.6 lbs/gal 0.91 kg/l	the container.	
<u>_</u>	IMIS / NPCA Ratings	Last Revision	
Health 3	Flammability 2 Reactivity 1	11/26/2002	
	 		

Directions for Use

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Technical assistance in applying Busan 1127 for microorganism control as described in the following in available upon request when a description of the problem is provided.

Busan 1127 is a water repellent preservative used to protect wood products (millwork, shingles, structural lumber, logs, and timbers) in above ground service from fungal decay. Before treatment wood should be clean and dry, and operations such as sawing, planing, machining, cutting, and sanding should be completed. Dilute the product by mixing 1 part of 8usan 1127 by volume with 4 parts of mineral spirits and apply to wood products by gurface reatment (rlipping coarse spgaying, or brushing), vacuum treatment, or pressure treatment.

Inline Application System: 1 part Busan 12 can be diluted in 0 - 4 parts of mineral spints for inline applications. Because inline treating systems have variable line species system variatione, treat varied wood species, and type or duration of protection vanes, Busan 1127 application rates may vary from mili to init. Please contact your buckman representative for further information about integrating Busan 1127 into your inline treating system.

