

BUSAN 1078

BUSAN is a registered trademark.

**KEEP OUT OF REACH OF CHILDREN
DANGER**

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes eye damage and skin burns. May cause allergic skin reaction. Harmful if inhaled. Harmful if swallowed. May be fatal if swallowed or absorbed through skin. Do not get in eye, on skin, on clothing. Wear goggles or face shield and rubber gloves when handling. Avoid breathing vapor or mist. Avoid contamination of food. Do not take internally. Wash thoroughly with soap and water after handling.

Statement of Practical Treatment:

If Swallowed: Do not induce vomiting. Drink promptly a large quantity of egg whites, gelatin solution, or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately. Never give anything by mouth to an unconscious person.

If Inhaled: Remove immediately to fresh air. If not breathing apply artificial respiration. If breathing is difficult give oxygen. Call a physician.

If on Skin: Wash thoroughly with soap and water. Remove and wash contaminated clothing before re-use.

If in Eyes: Flush with plenty of water for 15 minutes. Call a physician.

NOTE TO PHYSICIAN: Probable mucosal damage may contraindicate the use of gastric lavage.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on the label.

STORAGE AND DISPOSAL

PROHIBITIONS

This product is corrosive to mild steel. Do not store or transport in unlined metal containers. Do not contaminate food or feed by storage, disposal or cleaning of equipment.

PESTICIDE DISPOSAL

Pesticide waste are acutely hazardous. Improper disposal of excess pesticide or rinsate is a violation of Federal law. If these waste cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative of the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

METAL CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by other procedures approved by state and local authorities.

PLASTIC CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or

reconditioning or puncture and dispose of in a sanitary landfill, or by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

GENERAL

CONSULT FEDERAL, STATE, OR LOCAL DISPOSAL AUTHORITIES FOR APPROVED ALTERNATIVE PROCEDURES.

DIRECTIONS FOR USE

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Papermills: Busan 1078 is recommended for the control of bacteria and fungal slime in the production of paper.

POINT OF ADDITION: Busan 1078 should be added to a point in the system to insure uniform mixing such as the Beater, Hydropulper or Fan and Brake Storage Pumps.

DOSAGE: Apply 0.44 to 1.5 lbs. (7 to 23 fluid ounces) of Busan 1078 per ton (dry basis) of pulp and paper produced as a slug dose. If needed repeat daily. Badly fouled systems should be cleaned before initial treatment.

Paper Coating Preservation: Busan 1078 is recommended as an in-container preservative for the control of bacteria and fungi in water-based coatings such as paper coatings.

Add 0.43 - 1.65 lbs of Busan 1078 (195 - 750 g) to each 1,000 lbs (454 kg) of fluid to provide 425 to 1,675 ppm (6.25 to 25 ppm active isothiazolones).

Industrial Recirculating Water Cooling Towers: For the control of bacteria, algae and fungi add Busan 1078 microbicide to the tower basin, distribution box or some other point to insure uniform mixing.

Initial Dose: When the system is noticeably fouled, apply 148 to 883 ppm Busan 1078 microbicide (1.26 to 7.46 pounds or 19 to 113 fluid ounces of Busan 1078 per 1,000 gallons of water in the system). Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 35 to 219 ppm Busan 1078 microbicide (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of Busan 1078 per 1,000 gallons of water in the system) weekly or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

Air Washer Systems

Add to the air washer sump or chill water sump, to insure uniform mixing. 35 to 883 ppm Busan 1078 microbicide (0.3 to 7.46 pounds or 4.5 to 113 fluid ounces of Busan 1078 per 1,000 gallons of water in the system) depending upon the severity of contamination to control bacteria, fungi and algae which cause fouling in industrial air washer systems.

Intermittent or Slug Method

Initial Dose: When the system is noticeably fouled, apply 148 to 883 ppm Busan 1078 microbicide (1.26 to 7.46 pounds or 19 to 113 fluid ounces of Busan 1078 per 1,000 gallons of water in the system). Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 35 to 219 ppm Busan 1078 microbicide (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of Busan 1078 per 1,000 gallons of water) weekly or as needed to maintain control.

Continuous Feed Method

Initial Dose: When the system is just noticeably fouled, apply 148 to 883 ppm Busan 1078 microbicide (1.26 to 7.46 pounds or 19 to 113 fluid ounces of Busan 1078 per 1,000 gallons of water in the system).

Subsequent Dose: Maintain this treatment level by adding a continuous feed of 35 to 219 ppm Busan 1078 microbicide (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of Busan 1078 per 1,000 gallons of makeup water).

Badly fouled systems must be cleaned before initial treatment.

NOTE: For use only in industrial air washing systems that maintain effective mist eliminating components.

Industrial Recirculating Closed Loop Water Cooling Systems

For the control of bacteria, algae and fungi, add Busan 1078 microbicide to the reservoir, recirculating line or some other point in the system to insure uniform mixing.

Initial Dose: When the system is noticeably fouled, apply 148 to 883 ppm Busan 1078 microbicide (1.26 to 7.46 pounds or 19 to 113 fluid ounces of Busan 1078 per 1,000 gallons of water in the system).

ACTIVE INGREDIENTS:

5-Chloro-2-Methyl-4-isothiazolin-3-one 1.15%

2-Methyl-4-isothiazolin-3-one .35%

INERT INGREDIENTS: 98.5%

Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 35 to 219 ppm Busan 1078 microbicide (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of Busan 1078 per 1,000 gallons of water in the system) weekly or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

Polymer Latex Preservation

Busan 1078 microbicide is recommended for the control of bacteria and fungi in the manufacture and storage of synthetic and natural polymer latexes including: styrene/butadiene; carboxylated styrene/butadiene; ethylene/vinyl acetate, and biopolymers intended for industrial use, such as xanthum gum, gum arabic, guar gum, protein-derived polymers, starches, and casein-derived polymers.

Add 0.43 - 3.3 lbs. of Busan 1078 1.5% microbicide (195 g - 1.5 kg) to each 1,000 lbs. (454 kg) of emulsion to provide 425 to 3,350 ppm product (6.25 to 50 ppm active isothiazolones).

NOTE: To insure uniform mixing add Busan 1078 microbicide to latex or solutions slowly with agitation. The actual concentrations required will depend upon such factors as the specific substance to be treated, frequency of repeated microbial contamination expected and level of protection required.

Adhesive and Tackifier Preservation

Busan 1078 microbicide is recommended as an in-container preservative for the control of bacteria and fungi in water-soluble and water-dispersed adhesives such as animal glues, vegetable glues, natural rubber latexes, polyvinyl acetate, styrene-butadiene, and acrylic latexes. Busan 1078 microbicide is recommended as a preservative for tackifiers derived from resin and hydrocarbon resins. Add 0.43 - 1.65 lbs of Busan 1078 1.5% microbicide (195 - 750 g) to each 1,000 lbs (454 kg) of fluid to provide 425 to 1,675 ppm product (6.25 to 25 ppm active isothiazolones).

Paint and Coatings Preservation

Busan 1078 microbicide is recommended as an in-container preservative for the control of bacteria and fungi in water-based coatings such as paper and wood coatings and paints used for architectural product finishes, and special purpose coatings. Add 0.43 - 1.65 lbs. of Busan 1078 microbicide (195 - 750 g) to each 1000 lbs. (454 kg) of fluid to provide 425 to 1,675 ppm product (6.25 to 25 ppm active isothiazolones).

Building Material Preservation

Busan 1078 microbicide is recommended as an in-container preservative for the control of bacteria and fungi in building material such as mastics, caulks, joint cement, spackling and grouting. Add 0.43 - 1.65 lbs. of Busan 1078 microbicide (195 - 750 g) to each 1000 lbs. (454 kg) of fluid to provide 425 to 1,675 ppm product (6.25 to 25 ppm active isothiazolones).

Dispersed Pigment Preservation

Busan 1078 microbicide is recommended for the control of bacteria and fungi in the manufacture and storage of dispersed pigments such as kaolin clay, montmorillonite clay, titanium dioxide, calcium carbonate, calcium sulfate, barium sulfate, magnesium silicate, and kieselguhr used in paint and paper production. Add 0.43 - 1.65 lbs. of Busan 1078 microbicide (195 - 750 g) to each 1000 lbs. (454 kg) of fluid to provide 425 to 1,675 ppm product (6.25 to 25 ppm active isothiazolones).

ACCEPTED
MAR 04 1992

Under the Federal Insecticide,
Fungicide, and Rodenticide Act,
as amended, for the pesticide
registered under
EPA Reg. No. 1448-348

HMIS/NPCA RATING

Health 3 Flammability 1 Reactivity 1

EPA Reg. No. 1448-348

Product Weight 8.5 lbs/gal 1.02 Kg/L

NET CONTENTS MARKED ON CONTAINER

Manufactured By EPA Est. No 1448 TN-1

BUCKMAN LABORATORIES, INC.

1256 N. McLean Blvd, Memphis, TN 38108

(901) 278-0330 or 1-800-BUCKMAN