

DANGER

-

	Precautionary Statements				EMULSION PAINTS: For in-can preservation of emulsion paints, including acrylic, butadiene-stryene and PVA paints, add 0.025 to 0.4% (250 to
HAZARDS TO HUMANS AND DOMESTIC ANIMALS			ACTIVE INGREDIENTS:		γ 4,000 ppm) Busan 1104 based on the total weight of the formulation. The preservative can be added to the paint or any aqueous raw materials
lf in Eyes	FIRST AID - Hold eye open and rinse slowly and gently with water for 15-20 minutes. - Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.	1H-Pyrazole-1-methanol,			incorporated into the paint. ADHESIVES *: To protect adhesives, including natural gums, natural latex, PVA emulsions, synthetic gums, starched based adhesives (including non-converted tapicca, corn, and potato starches) and animal glues (including those derived from hide, bone, fish, blood or getatin) or other adhesives, add 0.05 to 0.4% Busan 1104 based on the total weight of the formulation. LATEX EMULSIONS: For the preservation of styrene-butadiene, PVA, acrylic and vinyl chloride, or other tatex emulsions, add 0.02 to 0.3%
	- Call a poison control center or doctor for further treatment advice.		Storage and Dis	sposal	Busan 1104 based on the total weight of the emulsion. POLISHES AND WAXES: To preserve water-based polishes and waxes in-can during storage, add 0.02 to 0.3% Busan 1104 based on the total 🥆
lf on Skin, Clothes	Skin, - Rinse skin immediately with plenty of water for 15-20 minutes. Clothes - Call a poison control center for treatment advice. If - Call poison control center or doctor immediately for treatment advice.		Do not contaminate water, food, or feed by storage and disposal. STORAGE: Do not use or store near heat or open flame. Do not stack more than four drums high. Drums should be opened in well-ventilated areas. Leaking or damaged		weight of the product. PAPERMAKING CHEMICALS AND COATINGS *: To control the bacterial degradation of paper coatings, size press solutions, wet-end starch (slurries, wet-end cooked starch, and other formulations used in papermaking, add 0.05 to 0.4% (500 to 4,000 ppm) Busan 1104 based on the lotal weight of the formulation. For pigment slurries (including clay, lifanium dioxide, and calcium carbonate based slurries) add 0.03 to 0.3% (300 to 3,000 ppm) Busan 1104 based on the lotal weight of the formulation.
lf Ingested			ust or sand and disposed of in a sanitary land CIDE DISPOSAL: Pesticide wastes are acu s pesticide, spray mixture, or rinsate is a viola	dfill. Keep container closed when not tely hazardous. improper disposal ol ation of Federal Law. If these wastes	DETERGENTS: To prevent bacterial degradation during storage and to increase shelf life of biodegradable surfactants, add 0.05 to 0.5% (500 to 5,000 ppm) Busan 1104 by weight of the formulation. INKS: To increase the shelf life of water based fountain pen, fabric, or paper printing inks, add 0.05 to 0.3% (500 to 3,000 ppm) Busan 1104 by weight of the formulation. TEXTILES: To prevent spoilage of spinning emulsions for rayon and finishing solutions and to prevent viscosity and pH changes in printing
lf Inhaled	 Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth if possible. Call a poison control center or doctor for further treatment advice. 	Al Pestic Nour E CONT	of be disposed of by use according to lab bide or Environmental Control Agency, or the SPA Regional Office for guidance. AINER DISPOSAL: Completely empty line	Hazardous Waste representative at	CONSTRUCTION MATERIALS: To increase the shelf and use life of caulking, grouting, sealing and spackling compounds and cements, add 0.04 to 0.4% (400 to 4,000 ppm) Busan 1104 by weight of the formulation. * Busan 1104 may NOT be used for the preservation of materials which may contact food.
HOT LINE NUMBER			bottom to loosen clinging particles. Empty residue into application equipment. Dispose of liner in a sanitary tandfill, or by incineration if allowed by State and local authorities. If		
Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment. You may also contact 901-278-0330 or 1-800-BUCKMAN for emergency medical treatment information.		rii bume	d, stay out of smoke.		
NOTE TO PHYSICIAN		-11			
Probable mucosal damage may contraindicate the use of gastric lavage.] [ACCEPTED		, Č
DANGER: Corrosive. Causes eye irritation and skin damage. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield, rubber gloves, and protective clothing when handling. Harmful or fatal if swallowed. Avoid contamination of food. Wash thoroughly with soap and water after handling. ENVIRONMENTAL HAZARDS: Do not discharge effluent containing this product into lakes streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.		en th S, Ne Ne Ne	JAN 2 3 2003 Under the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticide, registered under EPA Reg. No. 1448-357		
			Manufectured by Buckman Laboratories, Inc. 1256 North McLean Bivd., Memphis, Tennessee 38108, USA (901) 278-0330 or 1-800-BUCKMAN		
		EPA F	EPA Est. No. 1448-TN-1 EPA Reg. No. 1448-351 Product Weight 9.8 lbs./gal. 118 kg/L Ihe container.		
			HMIS / NPCA Ratings Last Revision		\sim
		, ,eai	Ith 2 Flammability 1 Reactivity	1 /5/2002	

.

.

Directions for Use

Busan 1104 is a preservative that is effective for the protection of emulsion paints, adhesives, latex emulsions, and liquid polishes and waxes.

The directions given on this label show the range of effective concentrations indicated by laboratory tests on typical substrates, but it is recommended that appropriate preservation tests be conducted to determine the minimum amount of Busan 1104 needed to preserve a particular

formulation. Technical assistance with the application of Busan 1104 as a preservative is available upon request when a description of the

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

problem is provided.