

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, D.C. 20460



United States
Environmental Protection
Agency

Office of Pesticide Programs

Buckman Laboratories, Inc.
256 N. McLean Blvd.
Memphis, TN 38108

MAR 24 2010

Attention: Carl F. Watson, Ph.D.

Subject: BUSAN 1192
EPA Registration No. 1448-363
Amendment Dated February 24, 2010

This will acknowledge receipt of your notification, submitted under the provisions of FIFRA Section 3(c)(9).

Proposed Notification

- To revise Storage and Disposal statement per PR Notice 2007-4

General Comments

Based on a review of the submitted material, the following comments apply:

The Notification is in compliance with PR Notice 98-10 and is acceptable. This information has been added to your file.

If you have any questions concerning this letter, please contact Martha Terry at (703) 308-6217.

Sincerely,

A handwritten signature in black ink that reads "M Swindell".

Marshall Swindell
Product Manager (33)
Regulatory Management Branch 1
Antimicrobials Division (7510P)

2/10



United States
Environmental Protection Agency
 Washington, DC 20460

<input type="checkbox"/>	Registration
<input checked="" type="checkbox"/>	Amendment
<input type="checkbox"/>	Other

OPP Identifier Number

Application for Pesticide - Section I

1. Company/Product Number 1448-363	2. EPA Product Manager Marshall Swindell	3. Proposed Classification <input checked="" type="checkbox"/> None <input type="checkbox"/> Restricted
4. Company/Product (Name) BUSAN 1192	PM# 33	
5. Name and Address of Applicant (Include ZIP Code) Buckman Laboratories, Inc. 1256 N. McLean Blvd Memphis, TN 38108 <input type="checkbox"/> Check if this is a new address	6. Expedited Review. In accordance with FIFRA Section 3(c)(3) (b)(i), my product is similar or identical in composition and labeling to: EPA Reg. No. _____ Product Name _____	

Section - II

<input checked="" type="checkbox"/> Amendment - Explain below.	<input type="checkbox"/> Final printed labels in response to Agency letter dated _____
<input type="checkbox"/> Resubmission in response to Agency letter dated _____	<input type="checkbox"/> "Me Too" Application.
<input type="checkbox"/> Notification - Explain below.	<input type="checkbox"/> Other - Explain below.

Explanation: Use additional page(s) if necessary. (For section I and Section II.)
 Label Amendment: Non-PRIA action.
 ACTION: Revise the Storage & Disposal Section in order to comply with PR Notice 2007-4
 Contact: cfwatson@buckman.com; FAX: (901) 272-6256

Section - III

1. Material This Product Will Be Packaged In:

Child-Resistant Packaging <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Unit Packaging <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	Water Soluble Packaging <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No	2. Type of Container <input checked="" type="checkbox"/> Metal <input checked="" type="checkbox"/> Plastic <input type="checkbox"/> Glass <input type="checkbox"/> Paper <input type="checkbox"/> Other (Specify) _____
* Certification must be submitted		If "Yes" Unit Packaging wgt. No. per container	If "Yes" Package wgt. No. per container

3. Location of Net Contents Information <input type="checkbox"/> Label <input checked="" type="checkbox"/> Container	4. Size(s) Retail Container 5 to 55 gal, 250 gal & bulk	5. Location of Label Directions <input checked="" type="checkbox"/> On Label
6. Manner in Which Label is Affixed to Product <input checked="" type="checkbox"/> Lithograph Paper glued Stenciled		<input type="checkbox"/> Other _____

Section - IV

1. Contact Point (Complete items directly below for identification of individual to be contacted, if necessary, to process this application.)

Name Carl Watson	Title Sr. Regulatory Toxicologist	Telephone No. (Include Area Code) (901) 272-6228
---------------------	--------------------------------------	---

Certification I certify that the statements I have made on this form and all attachments thereto are true, accurate and complete. I acknowledge that any knowingly false or misleading statement may be punishable by fine or imprisonment, or both under applicable law.		6. Date Application Received (Stamped)
2. Signature 	3. Title Sr. Regulatory Toxicologist	
4. Typed Name Carl F. Watson, Ph.D.	5. Date 24 February 2010	

BUSAN 192

BUSAN is a registered trademark.

Buckman

3/5

ACTIVE INGREDIENT(S)

Chlorothalonil (tetrachloroisophthalonitrile).....

98.0%

INERT INGREDIENTS.....

2.0%

TOTAL.....

100.0%

KEEP OUT OF REACH OF CHILDREN DANGER PELIGRO


FIRST AID	
If in Eyes	- Hold eye open and rinse slowly and gently with water for 15-20 minutes. - Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. - Call a poison control center or doctor for further treatment advice.
If on Skin, Clothes	- Take off contaminated clothing. - Rinse skin immediately with plenty of water for 15-20 minutes. - Call a poison control center or doctor for treatment advice.
If Swallowed	- Call poison control center or doctor immediately for treatment advice. - Have person sip a glass of water, if able to swallow. - Do not induce vomiting unless told to do so by the poison control center or doctor. - Do not give anything by mouth to an unconscious person.
If Inhaled	- Move person to fresh air. - If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth if possible. - Call a poison control center or doctor for further treatment advice.
HOT LINE NUMBER	
Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment. You may also contact 901-767-2722 for emergency medical treatment information.	
NOTE TO PHYSICIAN	
Probable mucosal damage may contraindicate the use of gastric lavage. Persons having a temporary allergic reaction respond to treatment with antihistamines or steroid creams and/or systemic steroids.	

Precautionary Statements

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive, causes severe eye damage. May be a potential skin sensitizer. Do not get in eyes, on skin or on clothing. Wear goggles or face shield, rubber gloves, long sleeve shirt and long pants when mixing, loading or applying this product. May be fatal if inhaled. Do not breathe dust. Wear a mask or pesticide respirator jointly approved by the Mine Safety and Health Administration and the National Institute for Occupational Safety and Health. Harmful if swallowed or absorbed through the skin. Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS: Do not discharge effluent containing this product directly into lakes, streams, ponds, estuaries, oceans or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product into sewer systems without previously notifying the sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the Environmental Protection Agency.



BUSAN 1992

BUSAN is a registered trademark.

^u
3
Buckman

Storage and Disposal

Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

STORAGE: Store in a dry place.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Improper disposal of excess pesticide, pesticide formulation or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for Guidance.

CONTAINER DISPOSAL:

(Text for all nonrefillable containers)

Nonrefillable container. Do not reuse or refill this container. Offer for recycling, if available. Triple rinse container (or equivalent) promptly after emptying.

{Solid residue removal statement for containers with capacity of 50 lbs or less}

Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for the later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

{Solid residue removal statement for containers with capacity of >50 lbs}

Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Turn the container over onto its other end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times.

(Text for all nonrefillable containers)

Then offer for recycling if available or reconditioning, if appropriate, or puncture and dispose of in a sanitary landfill, or, if allowed by state and local authorities by burning. If burned, stay out of smoke.

{Text for refillable containers}

Refillable container. Refill this container with pesticide only. Do not reuse this container for any other purpose. Cleaning the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller.

For containers larger than 55 gallons:

To clean the container prior to refilling or disposal, use a pressure wash as follows: Empty the remaining contents into application equipment or a mix tank. Use a pressure wash system that rinses all interior sides with water and that is rated at >40 psi and >120F. Pressure wash the container for a length of time that ensures that a minimum 25% of the container volume of water is used. During the pressure wash, ensure that the container valve is left open for continuous draining. Collect the rinsate and empty into application equipment or a mix tank or store rinsate for later use or disposal. Allow container to drain for 10 minutes after pressure wash is completed.

For containers 55 gallons and smaller:

To clean the container prior to refilling or disposal, use a triple rinse wash as follows: Empty the remaining contents from this container into application equipment or a mix tank. Fill the container about 10 percent full with water. Agitate vigorously. Pour or pump rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this rinsing procedure two more times.

Do not discharge rinsate containing this product unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge rinsate containing this product to sewer systems without prior approval from the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

Batch code: _____

Manufactured by

Buckman Laboratories, Inc.
1256 North McLean Blvd., Memphis, Tennessee 38108, USA
(901) 278-0330 or 1-800-282-5626

EPA Est. No. 37429-GA-2

EPA Reg. No. 1448-363

Product Weight 14.99 lbs/gal

Net contents are marked on the container.

HMIS / NPCA Ratings

Health 2 Flammability 0 Reactivity 0

Last Revision

1/29/2010

BUSAN 1192

BUSAN is a registered trademark.

5/5
Buckman

Directions for Use

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

For Manufacturing Use to Impart Mildew Control on Paint and Stain Films, Adhesives, Caulks and Sealants, and Decay Protection in Wood Composites.

This product is used to protect treated articles from decay, mold or mildew, including paints and stains, adhesives, caulks, grouts, sealants, wood and wood composites. Do not apply this product in a way that will contact workers or other persons. Only protected handlers may be in the area during use.

This product may not be sold as a mildewcidal paint additive designed for direct sale to retail customers, e.g. in a "pillow pack" or other small volume or one-use package.

This product may be added only to paint products that are labeled: A) with product specific instructions for the use of a respirator during application; or B) as follows: 'When applying with a sprayer, wear a NIOSH approved respirator any P, R, or HE filter. (If oil is not present in the paint product or recommended for use as an additive in the paint product, add "N" as an additional filter type.)'

This product must not be used as an in-container preservative.

BUSAN 1192, a micromilled powder, is best dispersed during the pigment grinding operations for paints, stains and coatings. Grinding equipment normally used in the paint industry is recommended.

Latex Emulsion Paints, Stains, and Coatings: Disperse 5 to 10 pounds of BUSAN 1192 per 100 gallons of exterior paint to obtain effective mildew control in the paint film after it is applied. Use the high rate in areas favorable to mildew and mold growth, such as where painted surfaces frequently are warm and moist. BUSAN 1192, when added to stains designed for exterior wood, also protects the wood from surface molds and mildew stains cause by fungi. Use 2.5 to 5 pounds BUSAN 1192 per 100 gallons of interior latex paint. BUSAN 1192 is compatible with zinc oxide in latex paint. BUSAN 1192 can be used with either unmodified or alkyd modified acrylic, or polyvinyl acetate latexes. **Note:** If BUSAN 1192 is used to produce post-manufacturing paint additive products, such products must be distributed to and used by only professional personnel engaged in the mixing or blending of paints. Such post-manufacturing paint additive products may not be sold directly to homeowners or non-professional painters.

If an in-can preservative is used in combination with BUSAN 1192, its compatibility with BUSAN 1192 should be examined first. **DO NOT** use in paints designed for applications on food-contact surfaces, or on the interior of buildings engaged in food processing or food handling. **DO NOT** use in paints designed to be handled by children.

Solvent-Based Exterior Paints, Stains, and Coatings: BUSAN 1192 protects solvent-based paint and stain films from mold growth on the coated surface. Disperse 5 to 12 pounds of BUSAN 1192 per 100 gallons of paint. Use the high rate in areas favorable to mildew and mold growth, such as where painted surfaces frequently are warm and moist. BUSAN 1192, when added to stains designed for exterior wood, also protects the wood from surface molds and mildew stains cause by fungi. Dispersion is readily accomplished during the pigment grinding operation. Zinc oxide can be used with BUSAN 1192.

Adhesives: BUSAN 1192 may be incorporated into adhesives to protect the applied adhesive films from mold growth and decomposition. Fully disperse 5 to 10 pounds of BUSAN 1192 per 1,000 pounds of adhesive while it is being manufactured. Use the high rate in areas favorable to mildew and mold growth, such as where surfaces frequently are warm and moist. **DO NOT** use in adhesives designed for applications on food-contact surfaces, or on the interior of buildings engaged in food processing or food handling.

Grouts: BUSAN 1192 may be incorporated into tile grouts to protect the finished grout joints from mold growth. Add BUSAN 1192 to dry grout at 0.4% to 1.6% by weight to the dry blending process (0.4 to 1.6 pounds of BUSAN 1192 per 100 pounds of dry grout blend). Adequate controls should be employed to prevent dusting during the handling and use of this product.

Caulks and Sealants: To provide mildew and mold control on caulking or sealing deposits after application, fully disperse 0.5 to 5 pounds of BUSAN 1192 per 1,000 pounds of caulk or sealant products while they are being manufactured. The high rate is recommended for exterior caulks. **DO NOT** use in caulks designed for applications on food-contact surfaces, or on the interior of buildings engaged in food processing or food handling.

Composite Wood Products: To provide decay protection for composite wood products, such as flakeboard or particle board that is to be used for building, sheathing, construction timbers, decking or planking, incorporate BUSAN 1192 into the wood composite material while it is being manufactured. Use 0.5 to 5 pounds of BUSAN 1192 per cubic foot volume of final wood composite. The high loading rate should be used in composite wood products that are intended to be installed in contact with soil or concrete, or where the wood is intended to be exposed to conditions with continuously high levels of moisture. Thoroughly incorporate BUSAN 1192 into composite material as it is being ground, mixed or blended with adhesives or binding materials prior to final formation of the wood matrix.