

1448-377

6/20/2011

1 of 4



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, D.C. 20460

JUN 20 2011

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

Buckman Laboratories, Inc.
1256 North McLean Blvd.
Memphis, TN 38108-1241 USA

Attention: Jeffery M. Thorne
Director, Compliance

Subject: Busan 1009 WB
EPA Reg. No.: 1448-377
Amendment Application Dated May 12, 2011

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, is acceptable. The Agency approves the changes made to the label per the Agency letter dated January 7, 2011.

A stamped copy of the accepted labeling is enclosed. Submit three copies of your final printed labeling to the Agency before distributing or selling the product bearing the revised labeling.

If you have any questions concerning this letter, please contact Abigail Downs at (703) 305-5259.

Sincerely,

A handwritten signature in cursive script that reads "M Swindell".

Marshall Swindell
Product Manager (33)
Regulatory Management Branch I
Antimicrobials Division (7510P)

2014

BUSAN 1009WB

BUSAN is a registered trademark.

Buckman

ACCEPTED
with COMMENTS
in EPA Letter Dated:

JUN 20 2011

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No
1448-~~673~~ 377

10.0%
10.0%
80.0%
100.0%

ACTIVE INGREDIENT(S)
2-(Thiocyanomethylthio)benzothiazole.....
Methylene bis(thiocyanate).....
INERT INGREDIENTS.....
TOTAL.....

The product contains methylene bis(thiocyanate) and 2-(thiocyanomethylthio)benzothiazole each at 0.90 pounds active ingredient per gallon.

KEEP OUT OF REACH OF CHILDREN DANGER PELIGRO

FIRST AID	
If in Eyes	- Hold eye open and rinse slowly and gently with water for 15-20 minutes. - Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. - Call a poison control center or doctor for further treatment advice.
If on Skin, Clothes	- Take off contaminated clothing. - Rinse skin immediately with plenty of water for 15-20 minutes. - Call a poison control center or doctor for treatment advice.
If Swallowed	- Call poison control center or doctor immediately for treatment advice. - Have person sip a glass of water, if able to swallow. - Do not induce vomiting unless told to do so by the poison control center or doctor. - Do not give anything by mouth to an unconscious person.
If Inhaled	- Move person to fresh air. - If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth if possible. - Call a poison control center or doctor for further treatment advice.
HOT LINE NUMBER	
Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment. You may also contact 901-767-2722 for emergency medical treatment information.	
NOTE TO PHYSICIAN	
Probable mucosal damage may contraindicate the use of gastric lavage.	

Precautionary Statements HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER.: Corrosive. Causes irreversible eye damage or skin burns. May be fatal if swallowed or absorbed through skin or inhaled. Do not get in eyes, on skin, or on clothing. Do not breathe spray mist. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse.

Personal Protective Equipment (PPE): Applicators and all other handlers must wear: Coveralls over long-sleeved shirt and long pants; Socks and chemical resistant footwear; Goggles or face shield; Chemical-resistant gloves such as barrier laminate, butyl rubber, nitrile rubber, neoprene rubber, polyvinyl chloride, or viton; and Respirator with an organic vapor removing cartridge with a prefilter approved for pesticides (MSHA/NIOSH approval number prefix TC-23C), or a canister approved for pesticides (MSHA/NIOSH approval number prefix TC-14G), or a NIOSH approved respirator with an organic vapor (OV) cartridge or canister with any R, P, or HE prefilter. Handlers participating in hand-dip applications, including introduction of material to and removal from the dip and handling materials still wet from the dip must wear: chemical-resistant full-front aprons with attached full-sleeve gloves.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish and aquatic organisms. For terrestrial uses, do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA

PHYSICAL AND CHEMICAL HAZARDS: Do not expose to extreme temperatures. Do not mix with an oxidant. Combustible. Do not use or store near heat or open flame.

BUSAN 1009WB

BUSAN is a registered trademark.

ACCEPTED
with COMMENTS
in EPA Letter dated:

JUN 20 2017

3084
Buckman

Directions for Use

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No. 144P-377

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

SAPSTAIN AND MOLD CONTROL: BUSAN 1009 WB is used to control sapstain and mold on freshly cut hardwood and softwood lumber, logs, poles, posts and timbers. It is applied by dipping the wood until complete surface wetting is accomplished. Use 0.5 to 2.0 gallons of BUSAN 1009 WB/100 gallons water (5 to 18 lbs of BUSAN 1009 WB/100 gallons water) and agitate vigorously until BUSAN 1009 WB is thoroughly dispersed. Rates to be used will vary according to temperature, humidity, wood moisture, storage conditions, etc. Under conditions suitable for aggressive mold growth, the high rate mentioned above should be used. Treatment should be made as quickly as possible after lumber is cut and always within 24 hours after cutting.

PAPER MILLS: To control bacterial and fungal growth on paper and paperboard machines, BUSAN 1009 WB is added to the white water or stock at 0.1 to 0.5 lb/ton of dry paper or paperboard produced. To inhibit the growth of bacteria and fungi in papermaking additives (including alum solutions, animal glue solutions, pigment slurries, coating formulations, and starch slurries and solutions) BUSAN 1009 WB is added to these materials in concentrations of 50-400 ppm (weight/weight). Pulp that may be held in storage for 8 hours to 1 week should be treated with 0.25 to 0.75 kg of BUSAN 1009 WB per tonne (0.5 to 1.5 lb per ton) of moisture free pulp. BUSAN 1009 WB may be added to contaminated fresh water at the rate of 0.25-1 ppm for treatment periods of 6-12 hours out of each 24 hours.

PARTICLE BOARD: BUSAN 1009WB is employed as a preservative against mold and fungi for particle board, insulation board, and other wood-base fiber and particle panel materials. In this use, BUSAN 1009WB is mixed with the furnish, resin, or binding agent at 0.1 to 0.3% based on the dry weight of the wood. **Not Registered for this use in California**

BACTERIOSTATIC PAPER: BUSAN 1009WB may be used in the production of bacteriostatic paper and paperboard when included in the coating formulation at a dosage of 0.5 - 9.0% (weight/weight) of product and added at the size press or similar application. The bacteriostatic paper and paperboard applications are not to be used in the manufacture of food contact paper, paper coatings, or paperboard. **Not Registered for this use in California**

COOLING TOWERS: BUSAN 1009WB is used to protect cooling tower wood against soft or surface rot and internal or dry rot. It is applied by painting a dispersion containing 0.5 to 0.7% BUSAN 1009WB in water onto the clean wood surfaces. The amount applied should provide 0.6 to 0.8 lb BUSAN 1009WB per 1000 sq. ft of wood surface. Soft or surface rot can also be inhibited by periodic shock doses of BUSAN 1009WB to the recirculating cooling water at the tower basin or cold well. The dosage should provide 1.25 lb. of BUSAN 1009WB per 1000 gal of water and the bleedoff should be stopped for 4 to 6 hr after treatment. The shock treatment should be repeated every four months. **Not Registered for this use in California**

COOLING WATER: BUSAN 1009WB is used to control algae, bacteria and fungi in industrial recirculating cooling water systems. Before treatment is begun, the system should be cleaned thoroughly to remove old algal growth, microbiological slime, and other deposits. The system should then be drained, flushed, refilled with water, and treated with an initial dose of 0.6 to 3.7 fl oz BUSAN 1009WB per 1000 gal water in the system. Subsequent additions of 0.2 to 1.2 fl oz per 1000 gal should be made every 1 to 5 days, depending on amount of bleedoff and severity of microbiological fouling. In systems greater than or equal to 4000 gallons, do not apply BUSAN 1009WB by open pouring of liquid to cooling water systems; a metering pump delivery system is required for this use and application method.

DRILLING FLUIDS: To inhibit bacterial and fungal degradation of the fluids or muds used in the drilling of wells, BUSAN 1009WB is incorporated in the drilling fluid at concentrations of 0.05 to 0.25% based on the total wet weight of the fluid.

PETROLEUM SECONDARY RECOVERY: BUSAN 1009WB is used to control sulfate-reducing bacteria, slime-forming bacteria and fungi in oil-field water, polymer, or micellar floods, water-disposal systems, and other oil-field water systems at dosage rates of 3.9 to 13.0 fl oz of BUSAN 1009WB per 1000 gal of water treated. Additions should be made continuously or intermittently by means of a metering pump at the free water knockouts, before or after injection pumps and injection well headers. Continuous Feed Method: When system is noticeably fouled, add 3.9 to 13.0 fl oz BUSAN 1009WB per 1000 gal of water continuously until desired degree of control is achieved. Then treat with 3.9 to 13.0 fl oz BUSAN 1009WB per 1000 gal of water continuously, or as needed to maintain control. Intermittent or Slug Method: When system is noticeably fouled, or to maintain control, add 3.9 to 13.0 fl oz BUSAN 1009WB per 1000 gal of water for 4 to 8 hr per day and 1 to 4 times per week, or as needed to maintain control.

CRUDE AND REFINED OILS: BUSAN 1009WB is an oil-soluble preservative for the control of bacteria and fungi that cause the degradation of crude oil and refined fuel oils during storage. Crude and refined oils include, but are not limited to, olefinic, aromatic, paraffinic, and naphthenic oils. It should be added to the oil as it is being transferred from the shipping container to the storage tank at the rate of 0.6 to 6.0 fl. oz. per 1000 gal of oil. Addition should be made batchwise where mixing occurs or continuously to the suction side of the transfer pump.

HIDES AND SKINS: BUSAN 1009WB is used to prevent bacterial decomposition of brine cured hides and skins. BUSAN 1009WB should be used at a level of 0.003 - 0.02% (30-200 ppm) based upon the weight of green fleshed hides or skins and saturated brine solution. In raceway operations, BUSAN 1009WB can be added directly to the raceway during the addition of hides and operation of paddles. In processor/mixer applications, BUSAN 1009WB should be added as dispersion in water. A satisfactory dispersion of 1 part BUSAN 1009WB plus 4 parts water can be prepared by adding the BUSAN 1009WB to the water (as opposed to adding water to BUSAN 1009WB) with agitation. **Not Registered for this use in California**

LEATHER: BUSAN 1009WB can be used to prevent bacterial decomposition of brine cured, wet salted, air-dried or green fleshed hides/skins in the soaking process. For this purpose, treatment levels of 0.02-0.05% (200-500ppm) based on the total weight of hides/skins and process water (float). BUSAN 1009WB is recommended for the prevention of mold in the storage, transport and processing of wet leather stock such as pickled, vegetable-, chrome-, alternative metal or metal free tanned hides/skins. For this purpose, BUSAN 1009WB is used at treatment rates of 0.05-0.25% (500-2500ppm) of white lime stock weight. A dispersion as described above should be prepared and added to the pickling solution or tanning liquor during the tanning operation or to the rinse water in a post tanning refloat. The product can also be applied during the fatliquoring process to prevent fungal growth at (0.025-0.075% (250-750)ppm) based on the split and shaved weight of leather being processed. **Not Registered for this use in California**

PIGMENT SLURRIES, COATINGS, NON-FOOD ADHESIVES, CAULKS AND SEALANTS: For the preservation of pigment slurries, coatings, non-food adhesives, caulks and sealants, BUSAN 1009WB should be added at a point in the processing system where there is sufficient time and agitation for good mixing and dispersion. The actual amount of material to be added for the preservation of any given formulation will depend on the components and storage time and conditions. Dosage rates should be determined by actual testing. For pigment slurries, coatings, non-food adhesives, caulks and sealants which are subject to bacterial and fungal attack in their containers, BUSAN 1009WB should be added at use levels of 0.5 to 0.75% by weight to inhibit this attack. To inhibit fungal growth on the dried coating, non-food adhesive, caulk, or sealant, BUSAN 1009WB should be incorporated at a use level of 0.75 to 2.5% by weight. To formulate coatings that are mold resistant and that prevent sapstain and decay by fungi, BUSAN 1009WB should be added at use levels of 0.5 to 9.0% based on the total weight of the formulation. The exact level to use will depend on the severity of the contamination as well as the nature and amounts of other components of the formulation.

40f4

BUSAN 1009WB

BUSAN is a registered trademark.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

Buckman

JUN 23 2011

Under the Federal Insecticide,
Fungicide, and Rodenticide Act a.
amended, for the pesticide,
registered under EPA Reg. No

Storage and Disposal

1448-377

Do not contaminate water, food, or feed by storage or disposal.

PESTICIDE STORAGE: Do not expose to extreme temperatures. Do not stack more than four drums high. Drums should be opened in well-ventilated areas. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

Nonrefillable

5 gals or less

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Offer for recycling, if available. Triple rinse container (or equivalent) promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container 1/4 full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for the later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times. Then offer for recycling if available or reconditioning, if appropriate, or puncture and dispose of in a sanitary landfill, or, if allowed by state and local authorities by burning. If burned, stay out of smoke.

Capacity of >5 gals

CONTAINER DISPOSAL: Nonrefillable container. Do not reuse or refill this container. Offer for recycling, if available. Triple rinse container (or equivalent) promptly after emptying. Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container 1/4 full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times. Then offer for recycling if available or reconditioning, if appropriate, or puncture and dispose of in a sanitary landfill, or, if allowed by state and local authorities by burning. If burned, stay out of smoke.

Refillable

Larger than 55 gallons

CONTAINER DISPOSAL: Refillable container. Refill this container with pesticide only. Do not reuse this container for any other purpose. Cleaning the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller.

To clean the container prior to refilling or disposal, use a pressure wash as follows: Empty the remaining contents into application equipment or a mix tank. Use a pressure wash system that rinses all interior sides with water and that is rated at >40 psi and >120F. Pressure wash the container for a length of time that ensures that a minimum 25% of the container volume of water is used. During the pressure wash, ensure that the container valve is left open for continuous draining. Collect the rinsate and empty into application equipment or a mix tank or store rinsate for later use or disposal. Allow container to drain for 10 minutes after pressure wash is completed.

Do not discharge rinsate containing this product unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge rinsate containing this product to sewer systems without prior approval from the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

55 gallons and smaller

CONTAINER DISPOSAL: Refillable container. Refill this container with pesticide only. Do not reuse this container for any other purpose. Cleaning the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller.

To clean the container prior to refilling or disposal, use a triple rinse wash as follows: Empty the remaining contents from this container into application equipment or a mix tank. Fill the container about 10 percent full with water. Agitate vigorously. Pour or pump rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this rinsing procedure two more times.

Do not discharge rinsate containing this product unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge rinsate containing this product to sewer systems without prior approval from the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

Manufactured by

Buckman Laboratories, Inc.

1256 North McLean Blvd., Memphis, Tennessee 38108, USA

(901) 278-0330 or 1-800-282-5626

EPA Est. No. 1448-TN-1

EPA Reg. No. 1448-377

Product Weight 9.2 lbs/gal 1.1 kg/l

Net contents are marked on the container.

HMIS / NPCA Ratings

Health 3 Flammability 1 Reactivity 1

Last Revision

3/14/2011