

KEEP OUT OF REACH OF CHILDREN DANGER

| lf in Eyes | - Hold eyes open and rinse slowly and gently with water for 15-20 minutes Remove contact tenses, if present, after the first 5 minutes, than continue rinsing eye Call a poison control center or doctor for further treatment advice. |
|---------------|---|
| | · |
| | - Take off contaminated clothing Rinse skin immediately with plenty of water for 15-20 minutes Call a poison control center for treatment advice. |
| - 1 | - Call poison control center or doctor immediately for treatment advice Have person sip a glass of water, if able to swallow Do not induce vomiting unless told to do so by the poison control center or doctor Do not give anything by mouth to an unconscious person. |
| Inhaled | - Move person to fresh air. - If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth if possible. - Call a poison control center or doctor for further treatment advice. |
| | HOT LINE NUMBER |
| or going fo | product container or label with you when calling a Poison Control Center or doctor or treatment. You may also contact 901-278-0330 or 1-800-BUCKMAN for y medical treatment information. |
| | NOTE TO PHYSICIAN |

Precautionary Statements

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes eye and skin damage. Harmful if swallowed. Do not get in eyes, on skin, or on clothing. Avoid Contamination of food. Wear goggles of face shield and rubber gloves when handling. Wash thoroughly after handling.


ENVIRONMENTAL HAZARDS: This posticide is toxic to fish. Do not discharge effluent containing this product into takes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

Directions for Use

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

D-33-8 is used in industrial and/or commercial recirculating cooling tower systems and industrial air-washing systems to control microbiological slime. Prior to the use of D-33-8, in industrial and/or commercial recirculating cooling tower systems, systems should be cleaned to remove algal growth, microbiological slime, and other deposits. Then make an initial slug addition of 9,5 to 14.2 fl oz of D-33-8 per 1000 gal of water to provide 80 to 120 ppm of D-33-8, based on the total weight of water in the system. Repeat initial dosage until control is evident. Make subsequent slug addition of 4.7 to 14.2 fl oz of D-33-8 per 1000 gal of water (40 to 120 ppm D-33-8) every 2 to 5 days or as needed. The frequency of addition depends upon the relative amount of blaedoff and the severity of the microbiological problem. Slug additions should be made in the sump of recirculating cooling tower systems.

D-33-8 is used in industrial air-washing systems which maintain effective mist-eliminating components. Prior to its use, systems should be cleaned to remove bacterial slime and other deposits. An initial slug doesof 22.2 to 28.4 fl oz of D-33-8 per 1000 gal of water is recommended. Repeat initial dosage until control is evident. Subsequent slug additions of 16.5 to 28.4 fl oz of D-33-8 per 1000 gal of water should be employed every 1 to 5 days, or as needed. The frequency of addition depends upon the relative amount of bleedoff and severity of the bacterial problem. Slug additions may be made to the sump or the water collection rays of the airwash system.



D-33-8

Storage and Disposal

Do not contaminate water, food or feed by storage or disposal.

PESTICIDE STORAGE: Do not expose to exreme temperatures. Do not stack more than four drums high. Leaking or damaged drums should be placed in overpack drums for disposal. Spill should be absorbed in sawdust or sand and disposed of in a sanitary landfill, Keep container closed when not in use.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to tabel instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

CONTAINER DISPOSAL:

PLASTIC: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, by incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

METAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

Manufactured by

Buckman Laboratories, Inc.

Reactivity 1

1256 North McLean Blvd., Memphis, Tennessee 38108, USA (901) 278-0330 or 1-800-BUCKMAN

EPA Est. No. EPA Reg. No. 1448-TN-1 1448-392

Net contents are marked on the container.

 \mathcal{Q}

ىز)

00

W

Product Weight

8.8 lbs/gai 1.05 kg/L

HMIS/NPCA Ratings

Health 3 Flammability 1

Last Revision 4/16/2003