ACTIVE INGREDIENTS:	
2-(Thiocyanomethylthio)benzothiazole	1.0 %
(Contains petroleum distillates)	
INERT INGREDIENTS:	99.0 %

# KEEP OUT OF REACH OF CHILDREN DANGER

BUSAN is a registered trademark

**BUSAN 1127 RTU** 

### PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes irreversible eye damage. Causes skin damage. This product may cause allergic skin reactions. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful or fatal if swallowed. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse.

FIRST AID: If in eyes, flush with plenty of water. Get medical attention. If on skin, wash with plenty of soap and water. Get medical attention. If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Get medical attention. Note to physician: Probable mucosal damage may contraindicate gastric lavage.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish. Do not use in offshore or estuarine drilling operations. For terrestrial uses, do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean high water mark. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

PHYSICAL AND CHEMICAL HAZARDS: Do not use or store near heat or open flame.

# STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

STORAGE: Do not expose to extreme temperatures. Do not stack more than five drums high. Drums should be opened in well-ventilated areas, Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

**PESTICIDE DISPOSAL:** Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

CONTAINER DISPOSAL: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

#### **DIRECTIONS FOR USE**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

Technical assistance in applying Busan 1127 RTU for microorganism control, as described in the following, is available upon request when a description of the problem is provided,

Busan 1127 RTU is a water repellent preservative used to protect wood products (millwork, shingles, structural lumber, logs, and timbers) in above ground service from fungal decay. Before treatment wood should be clean and day, and oporations such as sawing, planing, machining, cutting, and sanding should be completed. Apply Busan 1127 RTU to wood products by surface treatment (dipping, coarse spraying, or brushing), vacuum treatment, or pressure treatment.

ACCEPTED

with-COMMENTS

In EPA Letter Dated

NOV 27 1996

Under the Federal Insecticide

Fundicide, and Rodenticide Ac

as amended, for the pesticid

registered under EPA Reg. No.

Inline Application System: Busan 1127 RTU can be applied through inline treating systems. Because inline treating systems have variable line speeds, system variations, treat varied wood species, and type or duration of protection varies, Busan 1127 RTU application rates may vary from mill to mill. Please contact your Buckman representative for further information about integrating Busan 1127 RTU into your inline treating system.

## HMIS/NPCA RATING Health 2 Flammability 2 Reactivity I

Product Weight: 7.18 lbs./gal. .86 kg/l NET CONTENTS MARKED ON CONTAINER

EPA Reg. No. 1448 - Gro-G

RECU CITA

COdd/d:

ģ

NOV 12

212 215

:24

Manufactured By EPA Est. No. 1448-TN-1 BUCKMAN LABORATORIES, INC. 1256 N. McLEAN BLVD., MEMPHIS, TN 38108 USA (901) 278-0330 or 1-800-BUCKMAN

Rev. 11/8/96