6102011



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY WASHINGTON, D.C. 20460

JUN 10 2011

OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

Buckman Laboratories, Inc. 1256 North McLean Blvd. Memphis, TN 38108-1241 USA

Attention: Jeffery M. Thorne Director, Compliance

Subject: Busan 1366 EPA Reg. No.: 1448-394 Amendment Application Dated May 12, 2011

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, is acceptable. The Agency approves the changes made to the label per the Agency letter dated January 7, 2011.

The label must be revised so the routes of exposure are listed in the same order in both the First Aid and Hazards to Humans and Domestic Animals Sections, organized so that the routes of exposure of most concern (severe routes of exposure) as supported by the toxicity category classification are listed first.

A stamped copy of the accepted labeling is enclosed. Submit three copies of your final printed labeling to the Agency before distributing or selling the product bearing the revised labeling.

If you have any questions concerning this letter, please contact Abigail Downs at (703) 305-5259.

Sincerely. Marshall Swindell

Marshall Swindell Product Manager (33) Regulatory Management Branch I Antimicrobials Division (7510P)

BUSAN is a registered trademark.

ACTIVE INGRI	EDIENT
--------------	--------

Propiconazole:1-[[2-(2,4-dichlorophenyl)-4-propyl-1,3-dioxolan-2-yl]methyl]-1H-1,2,4-triazole...... INERT INGREDIENTS......

TOTAL



Buckman

KEEP OUT OF REACH OF CHILDREN

CAUTION


FIRST AID If in - Hold eye open and rinse slowly and gently with water for 15-20 minutes. - Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eve. Eyes - Call a poison control center or doctor for further treatment advice. If on - Take off contaminated clothing, - Rinse skin immediately with plenty of water for 15-20 minutes. Skin. - Call a poison control center or doctor for treatment advice. Clothes lf - Call poison control center or doctor immediately for treatment advice. Swallowed - Have person sip a glass of water, if able to swallow. - Do not induce vomiting unless told to do so by the poison control center or doctor. - Do not give anything by mouth to an unconscious person. - Move person to fresh air. If - If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth if possible. Inhaled - Call a poison control center or doctor for further treatment advice. HOT LINE NUMBER

Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment. You may also contact 901-767-2722 for emergency medical treatment information.

Precautionary Statements HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed, inhaled or absorbed through the skin. Avoid breathing spray mist. Avoid contact with skin, eyes or clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove contaminated and wash clothing before reuse.

ENVIRONMENTAL HAZARDS: Do not apply directly to water. Do not contaminate water when disposing of equipment washwaters. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.





Directions for Use

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

SAPSTAIN AND MOLD CONTROL:

BUSAN 1366 is used to control sapstain and mold in freshly cut hardwood and softwood lumber, logs, poles, posts and timbers. BUSAN 1366 is applied by dipping or spraying the wood until complete surface wetting is achieved. For bulk dip tanks BUSAN 1366 is diluted by using 0.5 gallons to 2.0 gallons BUSAN 1366 per 100 gallons of water. Agitate vigorously until completely dispersed. For conventional spray systems a 0.25% to 10% BUSAN 1366 spray solution is used. For example, in a 100 gallon day tank, 0.25 to 10 gallons of BUSAN 1366 are added to the day tank and then enough water is added to bring the total volume up to 100 gallons of solution. In electrostatic spray applications, BUSAN 1366 dilution is not required, treatment strength is varied by number of application nozzles used and line speed. Rates, for all applications used, will vary according to temperature, humidity, wood moisture, storage conditions, etc. Contact your local Buckman Laboratories representative for application advice.

Remove sawdust and other debris from treating solution on a regular basis to maintain correct concentration of BUSAN 1366 in application solution. To prevent fungal attack below the surface of the wood, freshly sawn lumber should be treated within 24 hours. Treated lumber should be protected from rain and removed from direct soil/ground contact.

COATINGS, CAULKS, SEALANTS, ADHESIVES, AND INKS

Sufficient mixing to ensure adequate dispersion of the biocide is required. BUSAN 1366 should be used at levels between 0.6 and 10.0%, based on the total weight of the formulation, to inhibit fungal disfigurement and deterioration. For solvent based formulations, BUSAN 1366 can be dissolved in aromatic solvents or combination of aromatic and aliphatic solvents and added to the letdown or added directly to the finished product. For water-thinned latex emulsion formulations, BUSAN 1366 can be premixed with the wetting agent and added to the pigment slurry or simply added to the letdown or the finished product.

Not for use in coatings and adhesives which will come in contact with paper or paperboard.

* Active ingredient developed by Janssen Pharmaceutica, Beerse, Belgium.

and Contractor 1975 - Contractor III 1975 - Santar Canadi

JUN 1 0 2011 "Inder the Roderel Insecticide, Pungleide, and Rodenticide Act a. Emanded, for the pesticide, registered under EPA Reg. No

1448-394

	í - · ·	401
BUSAN is a registered trademark.	66 ACCEPTED With COLAINER'S in EPA Letter Date 1: JUN 1 0 2011	Buckman
·	Maler the Federal Insecticide, Margineide, and Rodenticide June. Estimated, for the pesticide, Marginersci under EPA Reg. No. 1448-384	
	Storage and Disposal	
Do not contaminate water, food or feed by storage or dispo	osal.	
PESTICIDE STORAGE Store in original container in a cool, dry place.		
Liquid residue removal statement for nonrefillable containe riple rinse as follows: Empty the remaining contents into	application equipment or a mix tank and drain for 10 seconds aft onds. Pour rinsate into application equipment or a mix tank or	ter the flow begins to drip. Fill th
Hosures. Tip container on its side and roll it back and forth back and forth several times. Empty the rinsate into app wo more times. Text for all nonrefillable containers) Then offer for recycling if available or reconditioning, if juthorities by burning. If burned, stay out of smoke. Text for refillable containers}	o application equipment or a mix tank. Fill the container ¼ full n, ensuring at least one complete revolution, for 30 seconds. Star olication equipment or a mix tank or store rinsate for later use of appropriate, or puncture and dispose of in a sanitary landfill,	nd the container on its end and ti disposal. Repeat this procedur or, if allowed by state and loca
s the responsibility of the person disposing of the containe or containers larger than 55 gallons: o clean the container prior to refilling or disposal, use a p Jse a pressure wash system that rinses all interior sides w hat ensures that a minimum 25% of the container volum continuous draining. Collect the rinsate and empty into ap or 10 minutes after pressure wash is completed. For containers 55 gallons and smaller:	y. Do not reuse this container for any other purpose. Cleaning the reliant of the residuent of the refiller. The ressure wash as follows: Empty the remaining contents into apprith water and that is rated at >40 psi and >120F. Pressure wash are of water is used. During the pressure wash, ensure that the plication equipment or a mix tank or store rinsate for later use or	plication equipment or a mix tank the container for a length of tim e container valve is left open fo disposal. Allow container to drai
equipment or a mix tank. Fill the container about 10 perc ank or store rinsate for later use or disposal. Repeat this r Do not discharge rinsate containing this product unless in permit and the permitting authority has been notified in wri	triple rinse wash as follows: Empty the remaining contents fro ent full with water. Agitate vigorously. Pour or pump rinsate int insing procedure two more times. accordance with the requirements of a National Pollutant Discha ting prior to discharge. Do not discharge rinsate containing this prior ity. For guidance contact your State Water Board or Regional Of	to application equipment or a mi arge Elimination System (NPDES product to sewer systems withou
Batch code:		
Manufactured by Buckman Laborat	•	
1256 North McLean E (901) 278-0330 or 1-	Blvd., Memphis, Tennessee 38108, USA 800-282-5626	

EPA Est. No. 1448-TN-1

EPA Reg. No. 1448-394

Product Weight 8.5 lbs/gal 1.02 kg/l

Net contents are marked on the container.

HMIS / NPCA Ratings

Health 1 Flammability 1 Reactivity 1

Last Revision 3/9/2011