

1448-395

6/10/2011

1 of 4



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, D.C. 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

Buckman Laboratories, Inc.
1256 North McLean Blvd.
Memphis, TN 38108-1241 USA

JUN 10 2011

Attention: Jeffery M. Thorne
Director, Compliance

Subject: Busan 1370
EPA Reg. No.: 1448-395
Amendment Application Dated May 12, 2011

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, is acceptable. The Agency approves the changes made to the label per the Agency letter dated January 7, 2011.

The label must be revised so the routes of exposure are listed in the same order in both the First Aid and Hazards to Humans and Domestic Animals Sections, organized so that the routes of exposure of most concern (severe routes of exposure) as supported by the toxicity category classification are listed first.

A stamped copy of the accepted labeling is enclosed. Submit three copies of your final printed labeling to the Agency before distributing or selling the product bearing the revised labeling.

If you have any questions concerning this letter, please contact Abigail Downs at (703) 305-5259.

Sincerely,

A handwritten signature in black ink that reads "M. Swindell".

Marshall Swindell
Product Manager (33)
Regulatory Management Branch I
Antimicrobials Division (7510P)

BUSAN 1370

BUSAN is a registered trademark.

ACCEPTED
with COMMENTS
in EPA Letter Dated:
JUN 10 2011

Buckman

ACTIVE INGREDIENT(S)
Tetrahydro-3,5-dimethyl-2H-1,3,5-thiadiazine-2-thione.....
INERT INGREDIENTS.....
TOTAL.....

Under the Federal Insecticide,
Fungicide, and Rodenticide Act a.
amended, for the pesticide,
registered under EPA Reg. No
1448-395

.....
.....24.0%
.....76.0%
.....100.0%
.....
.....
.....
.....
.....
.....
.....
.....

KEEP OUT OF REACH OF CHILDREN DANGER

FIRST AID	
If in Eyes	- Hold eye open and rinse slowly and gently with water for 15-20 minutes. - Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. - Call a poison control center or doctor for further treatment advice.
If on Skin, Clothes	- Take off contaminated clothing. - Rinse skin immediately with plenty of water for 15-20 minutes. - Call a poison control center or doctor for treatment advice.
If Swallowed	- Call poison control center or doctor immediately for treatment advice. - Have person sip a glass of water, if able to swallow. - Do not induce vomiting unless told to do so by the poison control center or doctor. - Do not give anything by mouth to an unconscious person.
If Inhaled	- Move person to fresh air. - If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth if possible. - Call a poison control center or doctor for further treatment advice.
HOT LINE NUMBER	
Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment. You may also contact 901-767-2722 for emergency medical treatment information.	
NOTE TO PHYSICIAN	
Probable mucosal damage may contraindicate the use of gastric lavage.	

Precautionary Statements HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER. KEEP OUT OF REACH OF CHILDREN. Corrosive. Causes severe eye damage and skin irritation. Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Harmful if swallowed. Avoid contamination of food. May cause skin sensitization. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. remove and wash contaminated clothing before reuse.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination Systems (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewage systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

BUSAN 1370

BUSAN is a registered trademark.

with COMMENTS
in EPA Letter dated:

JUN 10 2011

Under the Federal Insecticide,
Fungicide, and Rodenticide Act a-
amended, for the pesticide,
registered under EPA Reg. No
1448-395

3044

Buckman

Directions for Use

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

PAPER MILL SLIME CONTROL: FOR THE CONTROL OF SLIME-FORMING AND/OR SPOILAGE BACTERIA: BUSAN 1370 is added at a point in the system (raw stock chest, beater and/or refiner chest, or machine chest-wirepit) where it will be uniformly mixed. Application may be continuous or intermittent for a certain number of hours/day or per shift, depending upon system characteristics. Add 5 to 20 fluid ounces of BUSAN 1370 per ton of paper produced.

INTERMITTENT FEED METHOD: Apply 12 to 20 fluid ounces of BUSAN 1370 per ton (dry basis) of pulp or paper for 2 hours every 8 hours. Badly fouled process systems must be cleaned before initial treatment.

CONTINUOUS FEED METHOD: Apply 5 to 15 fluid ounces of BUSAN 1370 per ton (dry basis) of pulp or paper produced on a continuous basis. Badly fouled process systems must be cleaned before initial treatment.

OILFIELD DRILLING MUDS AND WORKOVER OR COMPLETION FLUIDS: FOR CONTROL OF SLIME-FOAMING AND/OR SPOILAGE BACTERIA: Determine the total volume of the circulating system. Calculate the number of gallons of BUSAN 1370 needed to produce a concentration of 2,080 ppm (0.73 lb/bbl) of BUSAN 1370 in the drilling mud circulating system. For example, 75 gallons of BUSAN 1370 per 1000 barrels of drilling fluid is circulating. As the total volume increases, due to greater well depth, add additional BUSAN 1370 to maintain the proper concentration. Because of the wide variation in drilling mud composition and bacterial contamination, greater or lesser amounts of the BUSAN 1370 may be prescribed.

OILFIELD WATER TREATMENT AND WATER FLOODS: FOR CONTROL OF SLIME-FORMING AND/OR SPOILAGE BACTERIA: Calculate the total volume of water to be treated. Using this volume, calculate the number of gallons of BUSAN 1370 needed to produce concentration of approximately 2500 ppm BUSAN 1370. For example, 2.1 gallons of BUSAN 1370 per each 1000 gallons of total volume will produce this dilution. 350 ppm BUSAN 1370, added each week, is recommended to maintain bacterial control. This may be accomplished by adding 0.30 gallons of BUSAN 1370 to each 1000 gallons of total volume. Because of the wide variation in waters found in the oil field, greater or lesser amounts of BUSAN 1370 may be required in a particular location.

FOR THE PRESERVATION OF CLAY SLURRIES, ADHESIVES, COATINGS, AND HIGH VISCOSITY SUSPENSIONS: For preservation of slurries and high viscosity suspensions, BUSAN 1370 should be added at a point in the processing system where there will be sufficient time and agitation for good mixing and dispersion. Add BUSAN 1370 at use processing system where there will be sufficient time and agitation for good mixing and dispersion. Add BUSAN 1370 at use levels of 0.04% - 0.11%, by weight, based on the total formulation in slurries of starch, clay, calcium carbonate, or titanium dioxide; paper coatings; high viscosity suspensions (e.g., polymers, silica-polymer combinations); polyvinyl alcohol/polyvinyl acetate-based adhesives; starch-based adhesives; dextrin-based adhesives. The exact amount of material to be added for the preservation of any given formulation will depend on the components and local storage time and conditions. Dosage rates should be determined by actual tests.

RECIRCULATING COOLING WATER SYSTEMS: FOR CONTROL OF ALGAE, FUNGI AND SLIME FORMING BACTERIA: Dosages for recirculating cooling water systems will depend on the condition of the system prior to treatment initiation. Systems which are heavily contaminated should be cleaned first. Apply BUSAN 1370 to the cleaned system when growth is first noticed according to the following schedule.

INITIAL DOSE: Apply 3.25 - 6.5 fluid ounces (30 - 60 ppm) of BUSAN 1370 per each 1000 gallons of water in the system. This dose may be a continuous treatment or applied once, twice or three times weekly or as required to control the growth of slime forming organisms.

SUBSEQUENT DOSAGE: When microbial control is evident, add 0.5 - 3.25 fluid ounces (5 - 30 ppm) of BUSAN 1370 per 1000 gallons of water in the system as a continuous treatment daily or every three days or as required to maintain control.

4044

BUSAN 1370

BUSAN is a registered trademark.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

Buckman

JUN 10 2011
Under the Federal Insecticide,
Fungicide, and Rodenticide Act a.
amended, for the pesticide,
registered under EPA Reg. No
1448-395

Storage and Disposal

Do not contaminate water, food, or feed by storage or disposal.

PESTICIDE STORAGE: Protect from freezing and temperatures in excess of 140°F. Keep container closed when not in use. If contents are spilled or leaked due to container damage, collect liquid with absorbent material and dispose of in accordance with local, state, and federal pesticide disposal regulations.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these waste cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL:

(Text for all nonrefillable containers)

Nonrefillable container. Do not reuse or refill this container. Offer for recycling, if available. Triple rinse container (or equivalent) promptly after emptying.

{Liquid residue removal statement for nonrefillable containers with capacity of 5 gals or less}

Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for the later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

{Liquid residue removal statement for nonrefillable containers with capacity of >5 gals}

Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use of disposal. Repeat this procedure two more times.

(Text for all nonrefillable containers)

Then offer for recycling if available or reconditioning, if appropriate, or puncture and dispose of in a sanitary landfill, or, if allowed by state and local authorities by burning. If burned, stay out of smoke.

{Text for refillable containers}

Refillable container. Refill this container with pesticide only. Do not reuse this container for any other purpose. Cleaning the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller.

For containers larger than 55 gallons:

To clean the container prior to refilling or disposal, use a pressure wash as follows: Empty the remaining contents into application equipment or a mix tank. Use a pressure wash system that rinses all interior sides with water and that is rated at >40 psi and >120F. Pressure wash the container for a length of time that ensures that a minimum 25% of the container volume of water is used. During the pressure wash, ensure that the container valve is left open for continuous draining. Collect the rinsate and empty into application equipment or a mix tank or store rinsate for later use or disposal. Allow container to drain for 10 minutes after pressure wash is completed.

For containers 55 gallons and smaller:

To clean the container prior to refilling or disposal, use a triple rinse wash as follows: Empty the remaining contents from this container into application equipment or a mix tank. Fill the container about 10 percent full with water. Agitate vigorously. Pour or pump rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this rinsing procedure two more times.

Do not discharge rinsate containing this product unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge rinsate containing this product to sewer systems without prior approval from the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

Batch code: _____

Manufactured by **Buckman Laboratories, Inc.**
1256 North McLean Blvd., Memphis, Tennessee 38108, USA
(901) 278-0330 or 1-800-282-5626

EPA Est. No. 1448-TN-1

EPA Reg. No. 1448-395

Product Weight **8.5 lbs/gal 1.02 kg/l**

Net contents are marked on the container.

HMIS / NPCA Ratings

Health 3 Flammability 1 Reactivity 1

Last Revision

3/9/2011