January 21, 2003

Dennis L. Barbee, Ph.D. Director, Regulatory Affairs Buckman Laboratories, Inc. 1256 North McLean Blvd. Memphis, TN 38108

Subject:

WSKT 10

EPA Registration No. 1448-398

Application Date: November 25, 2002 EPA Received Date: November 29, 2002

Dear Dr. Barbee:

The following amendment, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act (FIFRA), as amended, is acceptable with the conditions listed below.

Proposed Amendment

Update First Aid Statement per PR Notice 2001-1

Conditions

Revise the label as follows:

Separate the Precautionary Statement heading from the First Aid Statements. In addition, the precautionary heading and its statement must be grouped together 1. to read as follows:

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes irreversible eye damage. Do not get in eyes or on clothing. Wear goggles, face shield, or safety glasses. Harmful if swallowed or absorbed through skin. Avoid contact with skin. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse. Prolonged or frequently repeated skin contact may cause allergic reactions in

Prolonged or frequently repositer skin contact thay sales							
SYMBOL 15/00 SOME	e individuals.						
SURNAME DE SALL						,	
DATE (-) 103							
EPA Form 1320-14 (1/90)		Printed on Remailed Day		OFFICIAL FILE COPY			

2. The child signal word "Danger" and the "Keep Out of Reach of Children" statement must be placed under the ingredient statement.

General Comments

A stamped copy of the labeling accepted with conditions is enclosed. Submit one(1) copy of your final printed labeling before distributing or selling the product bearing the revised labeling.

Should you have any questions or comments concerning this letter, please contact me at 703-308-6422.

Sincerely,

Adam Heyward

Product Manager 34

Regulatory Management Branch II Antimicrobials Division (7510 C)

KEEP OUT OF REACH OF CHILDREN

DANGER

Precautionary Statements

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

	FIRST AID
lfin Eyes	- Hold eye open and rinse slowly and gently with water for 15-20 minutes Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye Call a poison control center or doctor for further treatment advice.
lf on Skin, Ciothes	- Take off contaminated clothing Rinse skin immediately with plenty of water for 15-20 minutes Call a poison control center for treatment advice.
if ingested	- Call poison control center or doctor immediately for treatment advice Have person sip a glass of water, if able to swallow Do not induce vomiting unless told to do so by the poison control center or doctor Do not give anything by mouth to an unconscious person.
lf Inha ie d	- Move person to fresh air If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth if possible Call a poison control center or doctor for further treatment advice.
	KOT LINE NUMBER
or going	product container or label with you when calling a Poison Control Center or doctor for treatment. You may also contact 901-278-0330 or 1-800-BUCKMAN for by medical treatment information.
	NOTE TO PHYSICIAN
_	

DANGER: Corresive. Causes inversible eye damage. Do not get in eyes, on skin, or on clothing. Harmful if swallowed or absorbed through skin or inhaled. Avoid contact with skin. Prolonged or frequently repeated skin contact may cause allergic reaction in some individuals.

Personal Protective Equipment: Applicators and other handlers must wear: coveralls over long-sleeved shirt and long pants, socks and chemical resistant footwear, goggles or face shield, chemical-resistant gloves (such as waterproof or rubber gloves). Respirator with an organic vapor removing cartridge with a prefilter approved for pesticides (MSHA/NIOSH approval number prefix TC-23C), or a canister approved for pesticides (MSHA/NIOSH approval number prefix TC-14G), or NIOSH approval number prefix organic vapor (OV) cartridge or canister with any N,R,P, or HE prefilter. For Cleaning Equipment: chemical-resistant apron. Remove contaminated clothing and wash clothing before reuse.

User Safety Recommendations User should wash hands before eating, drinking, chewing gum, using lobacco, or using the toilet. User should remove clothing immediately if pesticide gets inside. Then wash thoroughly and put or clean clothing. User should remove Personal Protective Equipment immediately after handling this product. Wash the outside of gloves pefore removing. As soon as possible wash thoroughly.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes streams, ponds, estuaries, oceans, or public waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing part to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on the label.

ACTIVE INGREDIENTS: Poly[oxyethylene(dimethyliminio)ethylene	5				
(dimethyliminio)ethylene dichloride] 5-Chioro-2-Methyl-4-isothiszolin-3-one	1;				
5-Chloro-2-Methyl-4-isothiazolin-3-one					
NERT INGREDIENTS: 93.29% TOTAL 100.00%	} !				
Storage and Disposal					
PROHIBITIONS: This product is corrosive to mild steel.	Do not store or transport in				
untined metal containers. Do not contaminate food or f cleaning of equipment.	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \				
PESTICIDE DISPOSAL: Pesticide wastes are acutely haz	rardous, improper disposal of				
excess pecticide or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative of the nearest					
EPA Regional Office for guidance.	1:				
CONTAINER DISPOSAL: METAL CONTAINERS: Triple	rinse (or equivalent). Then				
offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill or by other procedures approved by state and local authorities. PLASTIC CONTAINERS: Triple rinse (or equivalent). Then offer for recycling or reconditioning or puncture and dispose of in a sanitary landfill, or by incineration, or, if allowed by state and local					
authorities, by burning. If burned, stay out of smoke.	allowed by state and local v				
GENERAL: CONSULT FEDERAL, STATE, OR LOCAL DISPOSAL AUTHORITIES					
FOR APPROVED ALTERNATIVE PROCEDURES.					
•					
	•				
	-				
	i				
	i				
	1				
	·].				
1 2 4 4					
, , , , , , , , , , , , , , , , , , , ,					
Buckman Laboratories, Inc.					
1255 North McLean Blvc., Memphis, Tennessee 38108, USA (904) 278-€330 or 1-800-BUCKMAN					
EPA Est. No. 1448-TN-1					
EPA Reg. No. 1448-398	N				
	Net contents are marked on the container.				
Product Weight 8.7 lbs/gal 1.04 kg/l	ino containor.				

Reactivity 1

Last Revision

9/26/2002

HMRS / NPCA Ratings

Flammability 1

Health 3

Directions fo

It is a violation of Federal law to use this product in a manner inconsist

Do not apply this product in a way that will contact workers or other persons. COOLING WATER SYSTEMS: WSKT 10 may be used to control the grecirculating cooling water systems. In noticeably fouled systems, WSKT 10 1000 gallons of system water (100 to 600 ppm WSKT 10). Extremely fouled s biofilm, and other deposits prior to program initiation. Subsequent additions of water (10 to 300 ppm WSKT 10) should be made to maintain control.

AIR WASHER SYSTEMS: WSKT 10 may be used to control microbiologic should be cleaned prior to addition of WSKT 10. When systems are noticeat to 92.8 fluid ounces per 1000 gallons of system water (100 to 800 ppm WSK58.0 fluid ounces per 1000 gallons of system water (100 to 500 ppm WSKT 1000 ppm WSK

METALWORKING FLUID SYSTEMS: WSKT 10 may be used to prevent mix 10 should be added tank-side to the system at 23.2 to 232 fluid ounces per maintain control. Systems with excessive fouling should be cleaned prior to in

FIRE WATER PROTECTION SYSTEMS: WSKT 10 can be added to help water protection systems. WSKT 10 should be added to the system at a p WSKT 10 should be fed to maintain 200 to 800 ppm of product in the system. gallons of water. Subsequent doses should be evaluated based on microbiologic

PETROLEUM SECONDARY RECOVERY: WSKT 10 is used to control sulvater, polymer or micellar floods, water disposal systems, and other oil field ppm (weight/weight) or 11.6 to 92.8 fluid ounces per 1000 gallons of treated means of a chemical-metering pump at the free water knockouts, before or: Method: When system is noticeably fouled, add WSKT 10 at a rate of 100 gallons of treated water until desired degree of control is achieved. Then treper 1000 gallons of treated water continuously, or as needed to maintain colled directly by a timed chemical-metering pump. The dosage rate and feed to ppm (weight/weight) or 23.2 to 92.8 fluid ounces per 1000 gallons of water is week, or as needed to maintain control.

ACCEPTED with COMMENTS
• EPA Letter Dated:

JAN 2 | 2003

Under the Federal Insecticide, Fungicide, and Rodenticide Ac amended, for the pesticide, registered under EPA Reg. No