

1448-423

7-19-2002

1/3



U.S. ENVIRONMENTAL PROTECTION AGENCY
Office of Pesticide Programs
Registration Division (H7505C)
401 "M" St., S.W.
Washington, D.C. 20460

EPA Reg. Number:

1448-423

Date of Issuance:

JUL 19 2002

NOTICE OF PESTICIDE:

- Registration
- Reregistration

(under FIFRA, as amended)

Term of Issuance:

Conditional

Name of Pesticide Product:

DIALD 15

Name and Address of Registrant (include ZIP Code):

Buckman Laboratories, Inc.
1256 North McLean, Boulevard
Memphis, TN 38108

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Registration Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered/reregistration under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA sec. 3(c) (7) (A) provided that you:

1. Submit and/or cite all data or other material required for registration/reregistration of your product under FIFRA sec. 3(c) (5) or FIFRA sec. 4 when the Agency requires all registrants of similar products to submit such data.

2. Add the phrase, "EPA Registration No.1448-423" to your label before you release your product for shipment.

Signature of Approving Official:

Marshall Swindell, Product Manager (33)
Regulatory Management Branch I
Antimicrobials Division (7510C)

Date:

JUL 19 2002

page 2
EPA Reg. No.1448-423


2/3

3. Submit five (2) copies of your final printed labeling before you release the product for shipment. Refer to the A-79 enclosure for a further description of final printed labeling.

If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA sec. 6(e). Your release for shipment of the product constitutes acceptance of these conditions.

A stamped copy of the label is enclosed for your records.

Sincerely,



Marshall Swindell
Product Manager 33
Regulatory Management Branch I
Antimicrobials Division (7501C)

Enclosure

STORAGE AND DISPOSAL
Feed by storage or disposal.

PESTICIDE STORAGE

To many commonly used materials of construction such as steel, galvanized iron, fusions can be stored and handled in baked phenolic lined steel, stainless steel or product freezes at approximately -20°C (-4°F). Therefore, unless the storage tank and insulation may be required. If heating is needed, exposure to high temperatures age (1 month) temperatures up to 100°F can be tolerated; however, the preferred is approximately 80°F. Keep away from fire and open flames. A stainless steel transfer service.

PESTICIDE DISPOSAL

ous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of it be disposed of by use according to label instructions, contact your State Pesticide or Hazardous Waste Representative at the nearest EPA regional office for guidance.

CONTAINER DISPOSAL

or for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by e and local authorities.

GENERAL

thorities for approved alternative procedures RCRA Hazardous Waste Code D002.

DIRECTIONS FOR USE

ERIAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELLING

AND RECIRCULATING COOLING WATER SYSTEMS

Industrial air washer systems which have mist-eliminating components. DIALD 15 on rates described below, to a water treatment system at a convenient point of area. Addition may be made intermittently (SLUG DOSE) or continuously. Badly fed with DIALD 15. Under these conditions, blowdown should be discounted for up

METHOD: Initial Dose: When the system is noticeably fouled, add 40-80 fluid 15 per 1,000 gallons of water in the system. Repeat until control is achieved.

al control is evident, add 16-40 fluid ounces (130-325 ppm) of DIALD 15 per 1,000 or day, or as needed to maintain control. Badly-fouled systems must be cleaned

Initial Dose: When the system is noticeably fouled, apply 40-80 fluid (325-650 ppm) water in the system.

treatments by starting a continuous feed of 16-40 fluid ounces (130-325 ppm) of ter in the system per day. Badly-fouled systems must be cleaned before treatment

HEAT TRANSFER SYSTEMS

static Sterilizers and Retorts, and Pasteurizers and Warmers)

noticeably fouled, add 40-80 fluid ounces (325-650 ppm) of DIALD 15 per 1,000

treatments by starting a continuous feed of 16-40 fluid ounces (130-325 ppm) of ter in the system per day. Badly fouled systems must be cleaned before treatment system at a point of uniform mixing such as the basin area, pump area, or other which the treated water will be circulated uniformly throughout the system.

ILLING AND OIL FIELD PROCESS APPLICATIONS

r flood system and, using this volume, calculate the number of gallons of DIALD 15

control is achieved. For example, 0.3-0.6 gal DIALD 15 per 1000 gal flood-water

ntently.

week is recommended to maintain bacterial control. This may be accomplished by ch 1,000 gals of total volume.

illing mud system and using this volume, calculate the number of gallons of DIALD levels are for total product.

depending on the severity of the bacterial contamination. For example, 12.7 gal (ilions) of fluid will provide this dilution.

ld the DIALD 15 in a thin stream.

tain the proper concentration as the total volume of the system increases with the

WORKOVER FLUIDS

Calculate the total vol e workover fluid system and, using this volume, calculate the number of gallons of DIALD 15 needed.

Use up to 3333 ppm of DIALD 15, depending on the severity of the bacterial contamination. For example, 12.7 gal DIALD 15 per 100 barrels (4200 gallons) of fluid will provide this dilution.

Add DIALD 15 into the system.

Circulate the workover fluid system until the fluid returns clear. Shut the system down and idle for several hours.

Remove the workover fluid. This well should be ready for productive use.

PAPER MILLS AND PAPER MILL PROCESS WATER SYSTEMS

DIALD 15 should be added to papermaking systems at a point of uniform mixing, such as the beaters, broke chest pump, save-all tank, or white water tank.

Initial Treatment: When the water is noticeably contaminated, add 1.67-10.0 lbs per ton of pulp or paper (dry basis) as a slug dose. Repeat until control is achieved. Heavily-fouled systems should be cleaned prior to initial treatment. Subsequent Dose: When microbial control is evident add 1.0-6.57 lbs per ton to pulp or paper (dry basis) as a slug dose as necessary to maintain control.

PIGMENTS AND FILLER SLURRIES FOR FOOD-CONTACT PAPER AND PAPERBOARD

To inhibit the growth of spoilage microorganisms during manufacture, storage and distribution of pigments and filler slurries such as kaolin, calcium carbonate and titanium dioxide.

Add sufficient quantities of DIALD 15 to produce a concentration of 333-2000 ppm by weight of the formulation slurry (3.3-20.0 lbs of product per 10,000 lbs of slurry).

WATER-BASED COATINGS FOR NON-FOOD-CONTACT PAPER AND PAPERBOARD

To inhibit the growth of spoilage microorganisms during manufacture, storage and distribution of water-based coatings for use on non-food-contact paper and paperboard.

Add sufficient quantities of DIALD 15 to produce a concentration of 333-2000 ppm by weight of the formulation slurry (1-6 Lbs of product per 10,000 lbs of slurry).

CONDITIONS OF SALE

The Directions for Use of this product reflect the opinion of experts based on field use and tests. The directions are believed to be reliable and should be followed carefully. However, it is impossible to eliminate all risk inherently associated with use of this product. Ineffectiveness or other unintended consequences may result because of such factors as weather conditions, presence of other materials, or use of the product in a manner inconsistent with its labeling, all of which are beyond the control of the Seller. All such risks shall be assumed by the Buyer. The manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes referred to above.

THE MANUFACTURER MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY OF FITNESS OR MERCHANTABILITY OR ANY OTHER EXPRESS OR IMPLIED WARRANTY. IN NO CASE SHALL THE MANUFACTURER BE LIABLE FOR CONSEQUENTIAL, SPECIAL OR INDIRECT DAMAGES RESULTING FROM THE USE OR HANDLING OF THIS PRODUCT.

The manufacturer offers this product, and the Buyer and User accept it, subject to the foregoing Conditions of Sale and Warranty which may be varied only by agreement in writing signed by a duly authorized representative.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

JUL 19 2002

Under the Federal Insecticide,
Fungicide, and Rodenticide Act as
amended, for the pesticide,
registered under EPA Reg. No.

Manufactured By:

Buckman Laboratories, Inc.

1448-423
1256 N. McLean Blvd., Memphis, Tennessee 38108, U.S.A.

(901) 278-0330 or 1-800-BUCKMAN

EPA Est. No. 1448-TN-1

EPA Reg. No. 1448-

Product Weight: 8.7 lbs/gal 1.04 kg/L

NET CONTENTS MARKED ON CONTAINER

HMS/NPCA RATING

Health 3 Flammability 1 Reactivity 0

W/C