

UNITED STATES ENVIRONMENTAL PROTECTION AGENCY

WASHINGTON, D.C. 20460

JUN 20 2011

OFFICE OF CHEMICAL SAFETY AND POLLUTION PREVENTION

Buckman Laboratories, Inc. 1256 North McLean Blvd. Memphis, TN 38108-1241 USA

Attention: Jeffery M. Thorne Director, Compliance

Subject:

DIALD 50

EPA Reg. No.: 1448-427

Amendment Application Dated May 12, 2011

The amendment referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide, and Rodenticide Act, as amended, is acceptable. The Agency approves the changes made to the label per the Agency letter dated January 7, 2011.

The label must be revised so the routes of exposure are listed in the same order in both the First Aid and Hazards to Humans and Domestic Animals Sections, organized so that the routes of exposure of most concern (severe routes of exposure) as supported by the toxicity category classification are listed first.

A stamped copy of the accepted labeling is enclosed. Submit three copies of your final printed labeling to the Agency before distributing or selling the product bearing the revised labeling.

If you have any questions concerning this letter, please contact Abigail Downs at (703) 305-5259.

Sincerely,

Marshall Swindell

Product Manager (33)

Regulatory Management Branch I Antimicrobials Division (7510P)



JUN 20 2011

Buckman

Glutaraldehyde **INERT INGREDIENTS:** TOTAL

ACTIVE INGREDIENT(S): "Index the Federal Insecticide." Funcicide, and Rodenticide Act a. amended, for the pesticide, 50.0% registered under EPA Reg. No 50.0% 1448-427 100.00%

KEEP OUT OF REACH OF CHILDREN DANGER

	FIRST AID و المحادث ا			
If swallowed	 Call a poison control center immediately for treatment advice. DO NOT INDUCE VOMITING Do not give anything to drink. 			
If in eyes	 Wash immediately and continuously with flowing water for at least 30 minutes. Remove contact lenses, if present, after the first 5 minutes and continue washing. Obtain prompt medical consultation, preferably from an ophthalmologist. Call a poison control center or doctor for further treatment advice. 			
lf on skin or clothing	 Take off contaminated clothing. Rinse skin immediately with plenty of water for 15–20 minutes. Call a poison control center or doctor for treatment advice. 			
If inhaled	 Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth if possible. Call a poison control center or doctor for further treatment advice. 			

HOT LINE NUMBER

Have the product container or label with you when calling a Poison Control Center or doctor, or going for treatment. You may also contact 901-767-2722 for emergency medical treatment information.

NOTE TO PHYSICIAN

Aspiration may cause lung damage. Probable mucosal damage may contraindicate the use of gastric lavage.

PRECAUTIONARY STATEMENTS HAZARDS TO HUMANS AND DOMESTIC ANIMALS

Corrosive. Causes irreversible eye damage. Causes skin irritation. Harmful if inhaled. Harmful if swallowed. Harmful if absorbed through skin. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Causes asthmatic signs and symptoms in hyper-reactive individuals. Do not get in eyes, on skin, on clothing. Avoid breathing vapor. Do not swallow. Wear goggles, protective clothing, and butyl or nitrile gloves. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

Buckman

STORAGE AND HANDLING

DIALD 50 is incompatible with many commonly used materials of construction such as steel, galvanized iron, aluminum, tin, and zinc. DIALD 50 can be stored and handled in baked phenolic-lined steel, polyethylene, stainless steel, or reinforced epoxy-plastic equipment. This product freezes at about 6°F (–21°C). Therefore, unless the storage tank is inside or underground, heating and insulation may be required. If heating is needed, exposure to high temperatures should be avoided. For short storage times (up to about 1 month), temperatures of up to 100°F (37.8°C) can be tolerated but the preferred maximum storage temperature is about 80°F (26.7°C).

A stainless steel centrifugal pump is suggested for transfer service. Spiral-wound stainless steel with TEFLON® Polymer is suitable for gaskets and packing.

Handle in a well-ventilated area. If vapors are irritating to the nose or eyes, special ventilation or respiratory protection (MSHA/NIOSH approved air purifying respirator equipped with an organic vapor cartridge) may be required.

STORAGE AND DISPOSAL

PESTICIDE DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or your Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL

(TEXT FOR ALL NONREFILLABLE CONTAINERS)

<u>NONREFILLABLE CONTAINERS</u>: Do not reuse or refill this container. Offer for recycling, if available. Triple rinse container (or equivalent) promptly after emptying. **Plastic Containers**: May be incinerated, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke. **Metal Containers**: Must not be incinerated. Do not cut or weld on or near metal containers.

Liquid residue removal statement for nonrefillable containers with capacity of 5 gals or less: Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container half full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for the later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

Liquid residue removal statement for nonrefillable containers with capacity of >5 gals: Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container half full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use of disposal. Repeat this procedure two more times.

(TEXT FOR ALL NONREFILLABLE CONTAINERS)

Then offer for recycling if available or reconditioning, if appropriate, or puncture and dispose of in a sanitary landfill, or, if allowed by state and local authorities by burning. If burned, stay out of smoke.

(TEXT FOR ALL REFILLABLE CONTAINERS)

REFILLABLE CONTAINERS. Refill this container with pesticide only. Do not reuse this container for any other purpose. Cleaning the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller.

ACCEPTED

with COMMENTS in EPA Letter Dated:

JUN 2 0 2011

Buckman

For containers larger than 55 gallons: To clean the container prior to refilling or disposal, use a pressure wash as follows: Empty the remaining contents into application equipment or a mix tank. Use a pressure wash system that rinses all interior sides with water and that is rated at >40 ps and >120°F. Pressure wash the container for a length of time that ensures that a minimum 50% of the container volume of water is used. During the pressure wash, ensure that the container valve is left open for continuous draining. Collect the rinsate and empty into application equipment or a mix tank or store rinsate for later use or disposal. Allow container to drain for 10 minutes after pressure wash is completed. For containers 55 gallons and smaller: To clean the container prior to refilling or disposal, use a triple rinse wash as follows: Empty the remaining contents from this container into application equipment or a mix tank. Fill the container about 10 percent full with water. Agitate vigorously. Pour or pump rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this rinsing procedure two more times.

Do not discharge rinsate containing this product unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge rinsate containing this product to sewer systems without prior approval from the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

Batch code:		
Dalon ocac.	 	

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

For formulation of industrial bactericides and preservatives for use in:

- Air washers and industrial scrubbing systems, recirculating cooling and process water systems including those that contain reverse osmosis membranes, service water and auxiliary systems, heat transfer systems, wastewater systems including wastewater sludge and holding tanks,
- Beet sugar mills and beet sugar mill process water systems
- Paper mills and paper mill process water systems, pigments and filler slurries for paper and paperboard, water based coatings for paper and paperboard
- Functional fluids and lubricants and aqueous metalworking fluids and in industrial, institutional and consumer processes and products in aqueous-based solutions, slurries and emulsions
- Oil well drilling, oil field processing applications, oil field water systems, gas production and transmission
 pipelines and systems and gas storage fields and equipment such as steam-injection water holding
 tanks, flood water, injection water, holding pond water, disposal-well water, water holding tanks, fuel
 storage tanks and related refinery and oil field closed, industrial recirculating water handling systems
- Animal production facilities and farm equipment such as: poultry & turkey houses, swine housing and farrowing areas, barns and large animal buildings, hatchers, setters and chick processing facilities, cages and transport vehicles, and hatching eggs and for sanitizing industrial or non-food contact surfaces such as equipment for mixing, packing, or packaging products, product transfer lines, storage tanks, floors, and walls.

ACCEPTED
with COMMENTS
in EPA Letter Dated:

JUN 2 0 2011

Buckman

ACCEPTED with COMMENTS in EPA Letter Dated:
JUN 2 0 2011

'nder the Federal Insecticide, Fungicide, and Rodenticide Act as amended, for the pesticidis, registered under EPAReac. No

1448-427

Manufactured by:

Buckman Laboratories, Inc.

1506 N. McLean Blvd., Memphis, Tennessee 38108, U.S.A. (901) 278-0330 or 1-800-282-5626

EPA Est. No. 10352-WV-2^(A); 464-WV-1^(B)

EPA Reg. No. 1448-427

(A) 5-gallon pails in pallets; all drums; bulk.(B) Single 5-gallon pails only.

Product Weight: 9.5 lbs/gal 1.13 kg/L NET CONTENTS MARKED ON CONTAINER

HMIS/NPCA RATING

Health 3

Flammability 1

Reactivity 0

Revised: 03/10/11