IDDIALD 25P

1	ACTIVE INGREDIENT:		
	Glutaraldehyde		
Ì	INERT INGREDIENTS:	75.0%	
١	TOTAL	100.00%	

KEEP OUT OF REACH OF CHILDREN DANGER

FIRST AID		
If swallowed	Call poison control center of doctor immediately for treatment advice. DO NOT INDUCE VOMITING. Bo not give anything to drink.	
lf in eyes	Wash immediately and continuously with flowing water for at least 30 minutes. Remove contact lenses after the first 5 minutes and continue washing. Obtain prompt medical consultation, preferably from an opthalmologist. Call a poison control center or doctor immediately for treatment advice.	
tf on skin or clothing	Take off contaminated clothing. Hinse skin immediately with plenty of water for 15–20 minutes. Call appoison control center for treatment advice.	
If inhaled	Wore person to fresh air. Hiperson is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth if possible. Galla poison control center or doctor for further treatment advice.	

HOT LINE NUMBER

Have the product container or label with you when calling a Poison Control Center or doctor, or going for treatment. You may also contact 901-276-0330 or 1 800 BUCKMAN for emergency medical treatment informations

NOTE TO PHYSICIAN

Aspiration may cause lung damage. Probable mucosal damage may contraindicate the use of

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

Corrosive. Causes irreversible eye damage. Causes skin irritation. Harmful if inhaled. Harmful if swatlowed. Barmful if also bed through skin. Prolonged or frequently repeated slon contact may cause altergic reactions in some individuals. Causes asthmatic signs and symptoms in hyper-reactive individuals, Do not get in eyes, on skin on clothing, Avoid breathing vapor, Do not swallow. Wear googles, protective clothing, and butyl or ratific gloves. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish. Do not discharge effluent containing this product into lakes, streams, ponds estuaries, occaps, ocother waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit, and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

STORAGE AND HANDLING

DIALD 25P is incompatible with many commonly used materials of construction such as steel, galvanized iron, aluminum, tin, and zinc. DIALD 25P can be stored and handled in baked phenolic-lined steet, polyethylene, stainless steel, or reinforced epoxy-plastic equipment. This product freezes at about 14°F (-10°C). Therefore, unless the storage tank is inside or underground, heating and insulation may be required. It heating is needed, exposure to high temperatures should be avoided. For short storage times (up to about 1 month), temperatures of up to 100°F (37.8°C) can be tolerated but the preferred maximum storage temperature is about 80°F (26.7°C).

A stainless steel centrifugal pump is suggested for transfer service. Spiral-wound stainless steel with TEFLON® Polymer is suitable for gaskets and packing.

Handle in a well-ventilated area. If vapors are irritating to the nose or eyes, special ventilation or respiratory protection (MSHA/NIOSH approved air purifying respirator equipped with an organic vapor cartridge) may be required.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

PAPER MILLS AND PAPER MILL PROCESS WATER SYSTEMS: DIALD 25P should be added to paper making system at a point of uniform mixing such as the beaters, broke chest pump, save-all tank, or white-water tank. Initial Dose: When the system is noticeably contaminated, add 1,0-6.0 lbs of DIALD 25P per ton of pulp or paper (dry basis) as a stug dose. Repeat until control is achieved. Heavilyfouled systems should be boiled out prior to initial treatment. Subsequent Dose: When microbial control is evident add 0.6-4.0 lbs of DIALD 25 per ton of pulp or paper (dry basis) as a stud dose as necessary to maintain control.

PIGMENTS AND FILLER SLURRIES FOR PAPER AND PAPERBOARD: (For use in food and nonfood contact pigments and filter sturries). Use from 0.2 to 1.2 lbs of DIALD 25P per 1,000 lbs dry powder to produce a concentration of 200 to 1,200 ppm as product (based on sturry solids) in the mixed

WATER-BASED COATINGS FOR PAPER AND PAPERBOARD; (For use in non-food contact coatlings only). Use from 0.2 to 1:2 lbs of DIALD 25 per 1,000 lbs dry powder to produce a concentration from 200 to 1,200 pom as product (based on sturry solids) in the mixed sturry.

STORAGE AND DISPOSAL

PESTICIDE DISPOSAL: Do not contaminate water, food or feed by storage or disposal. Open dumping is prohibited. Pesticide wastes are toxic, Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal law, if these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or your Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL: Metal Containers or Plastic Containers: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or other procedures approved by state and local authorities. Plastic Containers: May be incinerated, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke. Metal Containers: Must not be incinerated. Do not cut or weld on or near metal containers.

Manufactured By:

Buckman Laboratories, Inc.

NOV 2 3 2005

EPA Reg. No. 1448-429

pesticide, registered under

1256 N. McLean Blvd., Memphis, Tennessee 38108, U.S.A.

(901) 278-0330 or 1-800-BUCKMAN

Under the Federal Insecticide, Funcicide, and Rodenticide, Act as amended, for the Est. No. 10352-WV-2^(A); 464-WV-1^(B) EPA Reg. No. 1448-429 (A) 5-gallen pails in pallets; all drums; bulk. (B) Single 5-gallon pails only.

> Product Weight: 8.7 lbs/gal 1.04 kg/L **NET CONTENTS MARKED ON CONTAINER**

HMIS/NPCA RATING

Health 3 Flammability 1 Reactivity 0

Revised: 8/05