



UNITED STATES ENVIRONMENTAL PROTECTION AGENCY
WASHINGTON, DC 20460

OFFICE OF CHEMICAL SAFETY
AND POLLUTION PREVENTION

October 3, 2016

Carl F. Watson
Sr. Regulatory Toxicologist
Buckman Laboratories, Inc.
1256 N. McLean Blvd
Memphis, TN 38108

Subject: Label Amendment – revision of directions for use
Product Name: BUSAN 1215
EPA Registration Number: 1448-433
Application Date: September 15, 2016
Decision Number: 521777

Dear Mr. Watson:

The amended label referred to above, submitted in connection with registration under the Federal Insecticide, Fungicide and Rodenticide Act, as amended, is acceptable. This approval does not affect any conditions that were previously imposed on this registration. You continue to be subject to existing conditions on your registration and any deadlines connected with them.

A stamped copy of your labeling is enclosed for your records. This labeling supersedes all previously accepted labeling. You must submit one copy of the final printed labeling before you release the product for shipment with the new labeling. In accordance with 40 CFR 152.130(c), you may distribute or sell this product under the previously approved labeling for 18 months from the date of this letter. After 18 months, you may only distribute or sell this product if it bears this new revised labeling or subsequently approved labeling. "To distribute or sell" is defined under FIFRA section 2(gg) and its implementing regulation at 40 CFR 152.3.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

Your release for shipment of the product constitutes acceptance of these conditions. If these conditions are not complied with, the registration will be subject to cancellation in accordance with FIFRA section 6.

Page 2 of 2
EPA Reg. No. 1448-433
Decision No. 521777

If you have any questions, please contact Tara Flint at flint.tara@epa.gov or Eric Miederhoff at Miederhoff.Eric@epa.gov

Sincerely,

A handwritten signature in blue ink that reads "E. Miederhoff".

Eric Miederhoff
Product Manager 31
Regulatory Management Branch I
Antimicrobials Division (7510P)
Office of Pesticide Programs

Enclosure

BUSAN[®] 1215

Buckman

A microbiocide for controlling algal, bacterial and fungal deposits in influent water systems, and all process water systems used for the manufacture of paper and paperboard products and in industrial cooling towers, recirculating cooling water systems, evaporative condensers, influent water systems, brewery and food pasteurizers including industrial microbial and biofuel fermentation processes, industrial fresh water systems, airwashers, seawater desalination and reverse osmosis systems, paint spray booth sumps, non-fish containing decorative fountains and ponds used for cooling purposes, sewage and wastewater systems. This product is also used for the control of algae, bacteria, fungi and mollusks in both seawater and freshwater influent systems. **(Not registered for mollusk and fungi control in California.)**

ACCEPTED

10/03/2016

Under the Federal Insecticide, Fungicide and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No.

1448-433

ACTIVE INGREDIENT(S):

Ammonia (total)

7.59%

INERT INGREDIENTS:

92.41%

TOTAL

100.00%

KEEP OUT OF REACH OF CHILDREN

CAUTION

FIRST AID

If Swallowed	<ul style="list-style-type: none">• Call a poison control center or doctor immediately for treatment advice.• Have person sip a glass of water if able to swallow.• Do not induce vomiting unless told to do so by a poison control center or doctor.• Do not give anything by mouth to an unconscious person.
If Inhaled	<ul style="list-style-type: none">• Move person to fresh air.• If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible.• Call a poison control center or doctor for further treatment advice.
If in Eyes	<ul style="list-style-type: none">• Hold eye open and rinse slowly and gently with water for 15–20 min.• Remove contact lenses, if present, after first 5 min. then continue rinsing eye.• Call a poison control center or doctor for further treatment advice.
If on Skin, Clothes	<ul style="list-style-type: none">• Take off contaminated clothing.• Rinse skin immediately with plenty of water for 15–20 minutes.• Call a poison control center or doctor for treatment advice.
Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment. You may also contact 901-767-2722 for emergency medical treatment information.	

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if swallowed. Avoid breathing vapor. Avoid contact with skin, eyes, or clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse.

ENVIRONMENTAL HAZARDS: The pesticide is toxic to fish and aquatic organisms. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. PULP AND PAPER MILLS: BUSAN 1215 is used as a microbiocide in the manufacture of paper and paperboard that contacts food.

This product is applied in conjunction with sodium hypochlorite to form monochloramine, a slower acting less aggressive oxidizing microbiocide. The products are added to dilution water to achieve a minimum molar ratio of 1.0 to 1.0, BUSAN 1215 to sodium hypochlorite. This ratio may be obtained by combining 0.5 fluid ounces of BUSAN 1215 to 1.0 fluid ounces of sodium hypochlorite (less than or equal to 15.0% wt/wt). To insure both handling safety and effectiveness, the monochloramine solution must be generated and fed into the treatment water systems through a proper chemical feed skid only by a trained Buckman representative. Use of this product for any other purposes or contrary to the use directions specified below is prohibited.

Dosage Rates: When noticeably fouled, apply sufficient product and sodium hypochlorite to achieve a total chlorine residual of at least 1 ppm in excess of the system oxidant demand. Once control is achieved, treatment rates can be reduced to sub-demand rates from 50% to 80% of system demand. The product may be added to the system continuously or intermittently as needed to any area of the system where uniform mixing can be obtained.

For intermittent treatment, mix 0.5 fluid ounces of BUSAN 1215 to 1.0 fluid ounce of sodium hypochlorite (less than or equal to 15.0% wt/wt). Apply the solution at a rate to obtain 1 to 2 ppm in excess of the system oxidant demand (maximum of 5 ppm measured) as total chlorine in the water being treated for 5 to 60 minutes every 1 to 6 hours. The frequency of feeding and the duration of treatment will depend on the severity of the problem. Badly fouled systems must be cleaned before initial treatment.

For continuous treatment, mix 0.5 fluid ounces of BUSAN 1215 to 1.0 fluid ounce of sodium hypochlorite (less than or equal to 15.0% wt/wt). Apply the solution at a rate to obtain 0.5 to 1 ppm in excess of system oxidant demand (maximum of 5 ppm measured) as total chlorine in the water being treated on a continuous basis. The frequency of feeding and the duration of treatment will depend on the severity of the problem. Badly fouled systems should be cleaned before initial treatment.

If chloramine is detected in the effluent, it can be neutralized by the addition of sodium metabisulfite until the chloramine is no longer detected.

INDUSTRIAL WATER SYSTEMS: BUSAN 1215 is used for the control of algal, bacterial and fungal deposits in industrial cooling towers, recirculating cooling water systems, evaporative condensers, influent water systems, brewery and food pasteurizers including industrial microbial and biofuel fermentation processes, industrial fresh water systems, airwashers, seawater desalination and reverse osmosis systems, paint spray booth sumps, non-fish containing decorative fountains and ponds used for cooling purposes, sewage and wastewater systems. This product is also used for the control of algae, bacteria, fungi and mollusks in both seawater and freshwater influent systems. **(Not registered for mollusk and fungi control in California.)**

When this product is used to treat sewage and wastewater systems, seawater, and freshwater influent systems for once-through industrial water systems, and seawater desalination and reverse osmosis systems, and the system water is not sent to a POTW; residual levels of chloramine in the effluent must be monitored and neutralized using on-line monitoring and control equipment.

When this product is used to treat recirculating cooling water systems, evaporative condensers, influent water systems (not part of once-through industrial water systems), brewery and food pasteurizers including industrial microbial and biofuel fermentation processes, airwashers, paint spray booth sumps,

and non-fish containing decorative fountains and ponds used for cooling purposes; effluent detection of chloramine should be conducted at least once per shift. If chloramine is detected in the effluent, it can be neutralized by the addition of sodium metabisulfite until the chloramine is no longer detected.

This product is applied in conjunction with sodium hypochlorite to form monochloramine, a slower acting less aggressive oxidizing microbiocide. The products are added to dilution water to achieve a minimum molar ratio of 1.0 to 1.0, BUSAN 1215 to sodium hypochlorite. This ratio may be obtained by combining 0.5 fluid ounces of BUSAN 1215 to 1.0 fluid ounces of sodium hypochlorite (less than or equal to 15.0% wt/wt). To insure both handling safety and effectiveness, the monochloramine solution must be generated and fed into the treatment water process through a closed metered chemical feed system. The system operator must be trained by a Buckman representative in the use of the chemical feed system. Use of this product for any other purposes or contrary to the use directions specified below is prohibited.

Dosage Rates: When noticeably fouled, apply sufficient product and sodium hypochlorite to achieve a total chlorine residual of at least 1 ppm in excess of the system oxidant demand. Once control is achieved, treatment rates can be reduced to sub-demand rates from 50% to 80% of system demand. The product may be added to the system continuously or intermittently as needed to any area of the system where uniform mixing can be obtained.

For intermittent treatment, mix 0.5 fluid ounces of BUSAN 1215 to 1.0 fluid ounce of sodium hypochlorite (less than or equal to 15.0% wt/wt). Apply the solution at a rate to obtain 1 to 2 ppm in excess of the system oxidant demand (maximum of 5 ppm measured) as total chlorine in the water being treated for 5 to 60 minutes every 1 to 6 hours. The frequency of feeding and the duration of treatment will depend on the severity of the problem. Badly fouled systems must be cleaned before initial treatment.

For continuous treatment, mix 0.5 fluid ounces of BUSAN 1215 to 1.0 fluid ounce of sodium hypochlorite (less than or equal to 15.0% wt/wt). Apply the solution at a rate to obtain 0.5 to 1 ppm in excess of the system oxidant demand (maximum of 5 ppm measured) as total chlorine in the water being treated on a continuous basis. The frequency of feeding and the duration of treatment will depend on the severity of the problem. Badly fouled systems must be cleaned before initial treatment.

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

PESTICIDE STORAGE: Keep container tightly closed. Store in a dry place. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or Hazardous Waste representative at the nearest EPA Regional office for guidance. Clean equipment and/or dispose of equipment wash water in a manner to avoid contamination of water resources.

CONTAINER HANDLING: NONREFILLABLE CONTAINER. Do not reuse or refill this container. Offer for recycling, if available. Triple rinse container (or equivalent) promptly after emptying.

(Capacity of 5 gallons or less) Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for the later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this

procedure two more times.

(Capacity of greater than 5 gallons) Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times.

(All) Then offer for recycling if available or reconditioning, if appropriate, or puncture and dispose of in a sanitary landfill, or, if allowed by state and local authorities by burning. If burned, stay out of smoke. If metal container, do not puncture or burn.

CONTAINER HANDLING: REFILLABLE CONTAINER. Refill this container with pesticide only. Do not reuse this container for any other purpose. Cleaning the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller.

(Capacity of greater than 55 gallons) To clean the container prior to refilling or disposal, use a pressure wash as follows: Empty the remaining contents into application equipment or a mix tank. Use a pressure wash system that rinses all interior sides with water and that is rated at >40 psi and >120°F. Pressure wash the container for a length of time that ensures that a minimum 25% of the container volume of water is used. During the pressure wash, ensure that the container valve is left open for continuous draining. Collect the rinsate and empty into application equipment or a mix tank or store rinsate for later use or disposal. Allow container to drain for 10 minutes after pressure wash is completed.

(Capacity of 55 gallons or less) To clean the container prior to refilling or disposal, use a triple rinse wash as follows: Empty the remaining contents from this container into application equipment or a mix tank. Fill the container about 10 percent full with water. Agitate vigorously. Pour or pump rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this rinsing procedure two more times.

Manufactured by:

Buckman Laboratories, Inc.

1256 N. McLean Blvd., Memphis, Tennessee 38108, U.S.A.

(901) 278-0330 or 1-800-282-5626

EPA Reg. No. 1448-433

o **EPA Est. No. 11448-TN-1** o **EPA Est. No. 1448-MO-1**

Product Weight: 9.59 lbs/gal 1.15 kg/l

NET CONTENTS MARKED ON CONTAINER

HMIS/NPCA RATING

Health 1 Flammability 1 Reactivity 0

Revised: 07/20/16