



U.S. ENVIRONMENTAL PROTECTION AGENCY
 Office of Pesticide Programs
 Antimicrobials Division (7510P)
 1200 Pennsylvania Ave., N.W.
 Washington, D.C. 20460

EPA Reg. Number:

1448-444

Date of Issuance:

9/4/18

NOTICE OF PESTICIDE:

Registration
 Reregistration
 (under FIFRA, as amended)

Term of Issuance:

Conditional

Name of Pesticide Product:

Busan 30WB NA

Name and Address of Registrant (include ZIP Code):

Buckman Laboratories, Inc.
 1256 N. McLean Blvd
 Memphis, TN 38108

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Antimicrobials Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA section 3(c)(7)(A). You must comply with the following conditions:

1. Submit and/or cite all data required for registration/reregistration/registration review of your product under FIFRA when the Agency requires all registrants of similar products to submit such data.

Signature of Approving Official:

Demson Fuller, Product Manager 32
 (for Zeno Bain – Product Manager 33)
 Regulatory Management Branch I
 Antimicrobials Division (7510P)
 Office of Pesticide Programs

Date:

9/4/18

2. You are required to comply with the data requirements described in the DCI identified below:

a. 2-(Thiocyanomethylthio)benzothiazole GDCI-035603-1485

You must comply with all of the data requirements within the established deadlines. If you have questions about the Generic DCI listed above, you may contact the Reevaluation Team Leader (Team 36):
<http://www2.epa.gov/pesticide-contacts/contacts-office-pesticide-programs-antimicrobial-division>

3. The data requirements for storage stability and corrosion characteristics (Guidelines 830.6317 and 830.6320) are not satisfied. A one year study is required to satisfy these data requirements. You have 18 months from the date of registration to provide these data.
4. Make the following label changes before you release the product for shipment:
- Revise the EPA Registration Number to read, "EPA Reg. No. 1448-444."
5. Submit one copy of the final printed label for the record before you release the product for shipment.

Should you wish to add/retain a reference to the company's website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product's label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA's Office of Enforcement and Compliance.

If you fail to satisfy these data requirements, EPA will consider appropriate regulatory action including, among other things, cancellation under FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions. A stamped copy of the label is enclosed for your records. Please also note that the record for this product currently contains the following CSFs:

- Basic CSF dated 08/15/2018

If you have any questions, you may contact Aline Heffernan at 703-347-8602 or via email at heffernan.aline@epa.gov.

Sincerely,



Demson Fuller, Product Manager 32 (for Zeno Bain – Product Manager 33)
Regulatory Management Branch I
Antimicrobials Division (7510P)
Office of Pesticide Programs
Enclosure: Stamped Label

Buckman

BUSAN[®] 30WB NA

ACTIVE INGREDIENT(S)

2-(Thiocyanomethylthio)benzothiazole 30.0%

OTHER INGREDIENTS

70.0%

TOTAL

100.0%

DANGER

KEEP OUT OF REACH OF CHILDREN

ACCEPTED
1448-444
Under the Federal Insecticide, Fungicide and Rodenticide Act as amended, for the pesticide registered under EPA Reg. No. 09/04/2018

FIRST AID	
If in Eyes	<ul style="list-style-type: none">- Hold eye open and rinse slowly and gently with water for 15–20 minutes.- Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.- Call a poison control center or doctor for further treatment advice.
If on Skin, Clothes	<ul style="list-style-type: none">- Take off contaminated clothing.- Rinse skin immediately with plenty of water for 15–20 minutes.- Call a poison control center or doctor for treatment advice.
If Swallowed	<ul style="list-style-type: none">- Call poison control center or doctor immediately for treatment advice.- Have person sip a glass of water, if able to swallow.- Do not induce vomiting unless told to do so by the poison control center or doctor.- Do not give anything by mouth to an unconscious person.
If Inhaled	<ul style="list-style-type: none">- Move person to fresh air.- If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth if possible.- Call a poison control center or doctor for further treatment advice.
HOT LINE NUMBER	
Have the product container or label with you when calling a Poison Control Center or doctor or going for treatment. You may contact CHEMTREC at 1-703-741-5970 for emergency medical treatment information.	
NOTE TO PHYSICIAN	
Probable mucosal damage may contraindicate the use of gastric lavage.	

Precautionary Statements

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes irreversible eye damage and skin burns. May be fatal if inhaled or swallowed. May be harmful if absorbed through skin. Do not breathe vapor or spray mist. This product may cause allergic skin reactions. Do not get in eyes, on skin, or on clothing. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Wear goggles or face shield and chemical-resistant gloves when handling and a NIOSH approved particulate respirator, with any R or P filter with NIOSH approval number prefix TC-84A, or a NIOSH-approved powered air purifying respirator with an HE filter with NIOSH approval number prefix TC-21C). Handlers participating in hand-dip applications, including introduction of materials to and removal from the dip and handling materials still wet from the dip, must wear chemical-resistant full front aprons with attached full-sleeve gloves. User should remove clothing/PPE immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users should remove PPE immediately after handling this product. As soon as possible, wash thoroughly and change into clean clothing. Wash thoroughly with soap and water after handling and before eating, drinking, chewing gum, using tobacco, or using the toilet. Remove and wash contaminated clothing before reuse.

ENVIRONMENTAL HAZARDS: This pesticide is toxic to fish, aquatic invertebrates, oysters and shrimp. Do not use in offshore or estuarine drilling operations. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Treated lumber must be stored under cover, indoors, or at least 100 feet from any pond, lake, stream, wetland, or river to prevent possible runoff of the product into the waterway. Treated lumber stored within 100 feet of a pond, lake, stream, or river must be either covered with plastic or surrounded by a berm to prevent surface water runoff into the nearby waterway. If a berm or curb is used around the site, it should consist of impermeable material (clay, asphalt, concrete) and be of sufficient height to prevent runoff during heavy rainfall events.

Storage and Disposal

Do not contaminate water, food, or feed by storage or disposal.

STORAGE: Do not expose to extreme temperatures. Do not stack more than five drums high. Drums should be opened in well-ventilated areas. Leaking or damaged drums should be placed in overpack drums for disposal. Spills should be absorbed in sawdust or sand and disposed of in a sanitary landfill. Keep container closed when not in use.

PESTICIDE DISPOSAL: Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. Pesticide wastes are acutely hazardous. Wastes resulting from the use of the product, excess pesticide, spray mixture, or rinsate must be collected and disposed of at an approved disposal facility. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at your EPA Regional Office for guidance.

CONTAINER HANDLING:

{Text for all nonrefillable containers}

Nonrefillable container. Do not reuse or refill this container. Offer for recycling, if available. Triple rinse container (or equivalent) promptly after emptying.

{Liquid residue removal statement for nonrefillable containers with capacity of 5 gals or less}

Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for the later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

{Liquid residue removal statement for nonrefillable containers with capacity of >5 gals}

Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times.

{Text for all nonrefillable containers}

Then offer for recycling if available or reconditioning, if appropriate, or puncture and dispose of in a sanitary landfill, or, if allowed by state and local authorities by burning. If burned, stay out of smoke.

{Text for refillable containers}

Refillable container. Refill this container with pesticide only. Do not reuse this container for any other purpose. Cleaning the container before final disposal is the responsibility of the person disposing of the container. Cleaning before refilling is the responsibility of the refiller.

{For containers larger than 55 gallons}

To clean the container prior to refilling or disposal, use a pressure wash as follows: Empty the remaining contents into application equipment or a mix tank. Use a pressure wash system that rinses all interior sides with water and that is rated at >40 psi and >120°F. Pressure wash the container for a length of time that ensures that a minimum 25% of the container volume of water is used. During the pressure wash, ensure that the container valve is left open for continuous draining. Collect the rinsate and empty into application equipment or a mix tank or store rinsate for later use or disposal. Allow container to drain for 10 minutes after pressure wash is completed.

{For containers 55 gallons and smaller}

To clean the container prior to refilling or disposal, use a triple rinse wash as follows: Empty the remaining contents from this container into application equipment or a mix tank. Fill the container about 10 percent full with water. Agitate vigorously. Pour or pump rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this rinsing procedure two more times.

Do not discharge rinsate containing this product unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge rinsate containing this product to sewer systems without prior approval from the local sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA.

Buckman Laboratories, Inc.

Manufactured by:

1256 North McLean Blvd., Memphis, TN 38108, USA
(901) 278-0330 or 1-800-282-5626

EPA Est. No. 1448-TN-1

EPA Reg. No. 1448-_____

Product Weight 9.25 lbs/gal 1.11 kg/L

Net contents marked on container

HMIS/NPCA Ratings

Health 3 Flammability 1 Reactivity 1

Last Revision

08/31/2018

Directions for Use

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

NOTE TO USER: Do not apply this product in a way that will contact workers or other persons.

LEATHER: This product is recommended for the prevention of mold, bacteria and fungi in the storage, transport and processing of wet leather stock such as pickled, vegetable-, chrome-, alternative metal or metal free tanned hides and skins. Dosage rates of 0.025 - 0.2% (250 - 2,000 ppm) of this product can be used on the white lime stock weight basis to prevent microbial growth on processed hides and skins. The dosage level used will depend on storage conditions and the length of protection required. A satisfactory dilution of 1 part of this product plus 5 parts water can be prepared by adding the product to water (as opposed to adding water to the product) with agitation. The diluted product can then be added to the pickling liquor, or to the tanning liquor at the start of the tanning process or to the rinse water in a post tanning refloat. The product can also be applied during the fatliquoring process to prevent fungal growth at 0.025 - 0.2% (250 - 2,000 ppm) based on the split and shaved weight of leather being processed. This product can be used at the dosage rates suggested above in the processing of U.S. military specification shoe upper leathers. For preservation of leather finishing pastes and fatliquors, the product can be added at a dosage rate of 0.1 - 0.25% (1000 - 2500 ppm) based on the weight of the treated paste or fatliquor and mixed thoroughly to insure adequate dispersion.

PULP MILLS: To protect wood chips from fungal degradation during storage, this product is used at 0.5 to 2 lb/ton of oven-dry wood. It can be applied through a water shower located in the pneumatic conveyor carrying chips from the chipper to the storage pile. For preservation of wet lap or sheet pulp, this product is used at 0.5 to 4 lb/ton of oven-dry fiber. It is applied to the surfaces of the dewatered pulp by means of applicator rolls.

PAPER MILLS: To control bacterial and fungal growth on paper and paperboard machines, this product is added to the white water or stock at 0.1 to 0.5 lb/ton of dry paper or paperboard produced. To make mold-resistant paper or paperboard, this product is used at 0.05 to 0.1 lb/1000 sq ft (0.15 to 0.3 lb/3000 sq ft) of surface. For coated paper or board, this product is incorporated in the coating mix prior to application of the coating. For uncoated paper or board, this product is dispersed in water, surface-sizing solution, or other solvent and applied to the surface to be protected by means of an applicator roll. For the preservation of agricultural mulch paper, this product is used at 1.5 to 5 lb/ton air-dry paper. It is applied to the surfaces of the mulch paper by tub-sizing methods or by means of applicator rolls before the paper is coated.

PARTICLE BOARD: This product is employed as a preservative for particle board, insulation board, and other wood-base fiber and particle panel materials. In this use, the product is mixed with the resin or binding agent at 0.1 to 1% based on the dry weight of the wood.

SAPSTAIN CONTROL: This product is used to control sap stain and mold on freshly cut softwood and hardwood lumber, logs, poles, posts, and timbers. It is applied by dipping or pressure impregnation of the wood with a dispersion containing 0.5 to 8 gal of this product per 100 gal of water. Treatment should be made within 24 hr of cutting or sawing, particularly in warm weather, and treated wood should not be exposed to heavy rains soon after treatment.

COOLING TOWERS: This product is used to protect cooling tower wood against soft or surface rot and internal or dry rot. It is applied by painting a dispersion containing 0.5 to 0.7% of product in water onto the clean wood surfaces. The amount applied should provide 0.6 to 0.8 lbs of product per 1000 sq. ft. of wood surface. Soft or surface rot can also be inhibited by periodic shock doses of this product to the recirculating cooling water at the tower basin or cold well. The dosage should provide 1.25 lbs of this product per 1000 gal. of water and the bleedoff should be stopped for 4 to 6 hr. after treatment. The shock treatment should be repeated every four months.

COOLING WATER: This product is used to control algae, bacteria, and fungi in industrial recirculating cooling water systems. Before treatment is begun, the system should be cleaned thoroughly to remove old algal growth, microbiological slime, and other deposits. The system should then be drained, flushed, refilled with water, and treated with an initial dose of 0.6 to 3.7 fl oz of this product per 1000 gal water in the system. Subsequent additions of 0.2 to 1.2 fl oz per 1000 gal should be made every 1 to 5 days, depending on amount of bleedoff and severity of microbiological fouling.

COATINGS (non-paint), CAULKING-SEALANTS & WALLCOVER ADHESIVES: This product is added with sufficient mixing ensuring dispersion at levels of 0.5 to 5.0% based on the total formulation weight. It will inhibit the growth of fungi (mold, "mildew") that often cause discoloration and degradation of these compounds. This product is added at 0.5 to 5.0% based on the total weight of the formulation to prevent fungal disfigurement and deterioration. For solvent-based formulations, this product can be dissolved in aromatic solvents or combinations of aromatic and aliphatic solvents and added in the let down or added directly to the finished products. For water-thinned latex emulsion formulations, this product can be premixed with the wetting agent and added to the pigment slurry or simply added to the let down or finished product

DRILLING FLUIDS: To inhibit bacterial and fungal degradation of the fluids or muds used in the drilling of wells, this product is incorporated in the drilling fluid at concentrations of 0.05 to 0.25% based on the total wet weight of the fluid.

PETROLEUM SECONDARY RECOVERY: This product is used to control sulfate-reducing bacteria, slime-forming bacteria and fungi in oil-field water, polymer, or micellar floods, water-disposal systems, and other oil-field water systems at dosage rates of 0.2 to 3.7 fl oz of the product per 1000 gal of water treated. Additions should be made continuously or intermittently by means of a metering pump at the free water knockouts, before or after injection pumps and injection well headers. *Continuous Feed Method:* When system is noticeably fouled, add 0.6 to 3.7 fl oz of product per 1000 gal of water continuously until desired degree of control is achieved. Then treat with 0.2 to 1.2 fl oz of the product per 1000 gal of water continuously, or as needed to maintain control. *Intermittent or Slug Method:* When system is noticeably fouled, or to maintain control, add 0.6 to 3.7 fl oz of the product per 1000 gal of water for 4 to 8 hr. per day and 1 to 4 times per week, or as needed to maintain control.

WASTE WATER TREATMENT SYSTEMS: When used as directed, this product controls bacterial and fungal slime in waste water systems and effluents. The quantity of product required varies with the degree of fouling. It should be added at a rate that will provide 10 to 30 ppm (parts per million) of the product (weight/weight) in the waste water. This addition can be made at various points in the system including the influent to the clarifier and or the holding basins or ponds. (*Not registered for this use in California*)