



U.S. ENVIRONMENTAL PROTECTION AGENCY
Office of Pesticide Programs
Antimicrobials Division (7510P)
1200 Pennsylvania Ave., N.W.
Washington, D.C. 20460

EPA Reg. Number:

1448-446

Date of Issuance:

6/30/2020

NOTICE OF PESTICIDE:

Registration
 Reregistration
(under FIFRA, as amended)

Term of Issuance:

Conditional

Name of Pesticide Product:

BUSAN 94_{NA}

Name and Address of Registrant (include ZIP Code):

Carl F. Watson
Buckman Laboratories
1256 N. McLean Blvd.
Memphis, TN 38108

Note: Changes in labeling differing in substance from that accepted in connection with this registration must be submitted to and accepted by the Antimicrobials Division prior to use of the label in commerce. In any correspondence on this product always refer to the above EPA registration number.

On the basis of information furnished by the registrant, the above named pesticide is hereby registered under the Federal Insecticide, Fungicide and Rodenticide Act.

Registration is in no way to be construed as an endorsement or recommendation of this product by the Agency. In order to protect health and the environment, the Administrator, on his motion, may at any time suspend or cancel the registration of a pesticide in accordance with the Act. The acceptance of any name in connection with the registration of a product under this Act is not to be construed as giving the registrant a right to exclusive use of the name or to its use if it has been covered by others.

This product is conditionally registered in accordance with FIFRA section 3(c)(7)(A). You must comply with the following conditions:

1. Submit and/or cite all data required for registration/reregistration/registration review of your product under FIFRA when the Agency requires all registrants of similar products to submit such data.

Signature of Approving Official:

Demson Fuller, Product Manager 32
Regulatory Management Branch I,
Antimicrobials Division (7510P)

Date:

6/30/2020

2. You are required to comply with the data requirements described in the DCI identified below:
 - a. DBNPA GDCI-101801-1171

You must comply with all of the data requirements within the established deadlines. If you have questions about the Generic DCI listed above, you may contact the Reevaluation Team Leader (Team 36): <http://www2.epa.gov/pesticide-contacts/contacts-office-pesticide-programs-antimicrobial-division>

3. Be aware that proposed data requirements for DBNPA have been identified in a Work Plan. For more information on these proposed data requirements, you may obtain copies in the docket at EPA-HQ-OPP-2009-0724 or contact the Reevaluation Team Leader (Team 36): <http://www2.epa.gov/pesticide-contacts/contacts-office-pesticide-programs-antimicrobial-division>
4. Make the following label changes before you release the product for shipment:
 - Revise the EPA Registration Number to read, “EPA Reg. No. 1448-446.”
5. The following alternate brand names are acceptable and have been made a part of the file for this product: BULAB 6042_{NA}, BULAB 8861_{NA}, BULAB 3854_{NA}, and BRONAM 20_{NA}
6. Submit one copy of the final printed label for the record before you release the product for shipment.

Should you wish to add/retain a reference to the company’s website on your label, then please be aware that the website becomes labeling under the Federal Insecticide Fungicide and Rodenticide Act and is subject to review by the Agency. If the website is false or misleading, the product would be misbranded and unlawful to sell or distribute under FIFRA section 12(a)(1)(E). 40 CFR 156.10(a)(5) list examples of statements EPA may consider false or misleading. In addition, regardless of whether a website is referenced on your product’s label, claims made on the website may not substantially differ from those claims approved through the registration process. Therefore, should the Agency find or if it is brought to our attention that a website contains false or misleading statements or claims substantially differing from the EPA approved registration, the website will be referred to the EPA’s Office of Enforcement and Compliance.

If you fail to satisfy these data requirements, EPA will consider appropriate regulatory action including, among other things, cancellation under FIFRA section 6(e). Your release for shipment of the product constitutes acceptance of these conditions. A stamped copy of the label is enclosed for your records. Please also note that the record for this product currently contains the following CSFs:

- Basic CSF dated 10/29/2019

Page 3 of 3
EPA Reg. No. 1448-446
Decision No. 560164

If you have any questions, please contact Wanda Henson by phone at (703) 308-6345, or via email at henson.wanda@epa.gov

Sincerely,

A handwritten signature in blue ink that reads "Wanda G. Henson". The signature is written in a cursive style with a large initial "W" and "H".

Demson Fuller, Product Manager 32
Regulatory Management Branch I
Antimicrobials Division (7510P)
Office of Pesticide Programs

Enclosure



ACCEPTED
 06/30/2020
 Under the Federal Insecticide, Fungicide
 and Rodenticide Act as amended, for the
 pesticide registered under
 EPA Reg. No. 1448-446

BUSAN[®] 94_{NA}

A MICROBIOCIDAL BACTERICIDE, FUNGICIDE, ALGAECIDE AND SLIMICIDE, USED IN TREATING RECIRCULATING COOLING WATER IN INDUSTRIAL COOLING SYSTEMS, PAPER MILLS, BREWERY PASTEURIZER WATER, METALWORKING CUTTING FLUIDS, NON-POTABLE REVERSE OSMOSIS SYSTEMS, ENHANCED OIL RECOVERY SYSTEMS, AIR-WASHER SYSTEMS, INDUSTRIAL PRESERVATION APPLICATIONS AND PUBLICLY OWNED TREATMENT WORKS.

ACTIVE INGREDIENT(S):

2,2-Dibromo-3-nitrilopropionamide.....20%

OTHER INGREDIENTS:.....80%

TOTAL100%

10 pounds BUSAN[®] 94_{NA} liquid per gallon.

KEEP OUT OF REACH OF CHILDREN DANGER

FIRST AID	
If in Eyes	<ul style="list-style-type: none"> • Hold eye open and rinse slowly and gently with water for 15–20 min. • Remove contact lenses, if present, after first 5 min. then continue rinsing eye. • Call a poison control center or doctor for further treatment advice.
If on Skin, Clothes	<ul style="list-style-type: none"> • Take off contaminated clothing. • Rinse skin immediately with plenty of water for 15–20 minutes. • Call a poison control center or doctor for treatment advice.
If Swallowed	<ul style="list-style-type: none"> • Call a poison control center or doctor immediately for treatment advice. • Have person sip a glass of water if able to swallow. • Do not induce vomiting unless told to do so by a poison control center or doctor. • Do not give anything by mouth to an unconscious person.
If Inhaled	<ul style="list-style-type: none"> • Move person to fresh air. • If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible. • Call a poison control center or doctor for further treatment advice.
<p>Have the product container or label with you when calling a Poison Control Center or doctor, or going for treatment. You may also contact CHEMTREC at 1-703-741-5970 for emergency medical treatment information.</p>	
<p>NOTE TO PHYSICIAN</p> <p>Probable mucosal damage may contraindicate the use of gastric lavage.</p>	

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

DANGER: Corrosive. Causes irreversible eye damage. Causes skin burns. May be fatal if swallowed. Harmful absorbed through skin or if inhaled. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals.

Do not get in eyes, on skin, or on clothing. In case of contact immediately rinse skin with plenty of water. Get medical attention if irritation persists. Use with adequate ventilation. Wash thoroughly with soap and water after handling and before eating drinking using tobacco or using the toilet. Remove contaminated clothing and wash clothing before reuse.

PERSONAL PROTECTION EQUIPMENT (PPE):

Applicators and other handlers must wear:

- Coveralls worn over long sleeved shirt and long pants.
- Chemical resistant footwear plus socks.
- Goggles or face shield.
- Chemical-resistant gloves (such as barrier laminate, butyl rubber, neoprene rubber, nitrile rubber, polyvinyl chloride (PVC and viton).
- For mixing/loading: Wear a chemical resistant apron.
- For cleaning equipment: Wear a chemical resistant apron.

Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions exist for washables, use detergent and hot water. Keep and wash PPE separately from other laundry.

User Safety Recommendations:

Users must wash hands before eating, drinking, chewing gum, using tobacco, or using the toilet. Users must remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users must remove personal protective equipment immediately after handling this product. Wash outside of gloves before removing. Wash thoroughly as soon as possible.

General Precautions and Restrictions: Do not apply this product in a way that will contact workers or other persons.

ENVIRONMENTAL HAZARDS: The pesticide is toxic to fish and aquatic organisms. Do not contaminate water by cleaning of equipment or disposal of waste. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the local sewage treatment plant authority. For guidance, contact your State Water Board or Regional Office of the EPA.

PHYSICAL OR CHEMICAL HAZARDS: Reaction with strong reducing agents may be explosive. Avoid misting.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling. Read entire label and use strictly in accordance with precautionary statements and directions.

INDUSTRIAL RECIRCULATING COOLING WATER IN INDUSTRIAL SYSTEMS: Add this product separately to the system. Do not mix it with other additives, so as to avoid decomposition of this product due to the high pH of many additive formulations. Add this product to the basin (or any other point of uniform mixing). Additions must be made via a metering pump; it may be continuous or intermittent, depending on the severity of the contamination when treatment is begun, and the in-system retention time. Optimum performance with this product is achieved by continuous or intermittent treatment. If "shock" treatment is used, the blowdown must be discontinued for 24-48 hours.

FOR CONTROL OF BACTERIA

Add 0.00095-0.0095 gal. of this product/1,000 gal. of water in the system depending on the severity of contamination.

INTERMITTENT OR SLUG METHOD

Initial Dose: When the system is noticeably fouled, add 0.0048-0.0095 gal. of this product/1,000 gal. of water in the system. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 0.0024-0.0095 gal. of this product/1,000 gal. of water in the system every 4 days, or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD

Initial Dose: When the system is noticeably fouled, add 0.0048-0.0095 gal. of this product/1,000 gal. of water in the system.

Subsequent Dose: Maintain this level by pumping a continuous feed of 0.00095-0.0048 gal. of this product/1,000 gal. of water in the system lost by blowdown. Badly fouled systems must be cleaned before treatment is begun.

FOR CONTROL OF FUNGI AND ALGAE

Add 0.029-0.095 gal. of this product/1,000 gal. of water in the system, depending on the severity of contamination.

INTERMITTENT OR SLUG METHOD

Initial Dose: When the system is noticeably fouled, add 0.048-0.095 gal. of this product/1,000 gal. of water in the system. Repeat until control is achieved. **Subsequent Dose:** When microbial control is evident, add 0.029-0.095 gal. of this product/1,000 gal. of water in the system daily, or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD

Initial Dose: When the system is noticeably fouled, add 0.048-0.095 gal. of this product/1,000 gal. of water in the system.

Subsequent Dose: Maintain this treatment level by pumping a continuous feed of 0.029-0.095 gal. of this product/1,000 gal. of water in the system per day. Badly fouled systems must be cleaned before treatment is begun.

PULP AND PAPER MILL SYSTEMS: Add this product separately to the system. Do not mix with other additives, so as to avoid decomposition of this product due to the high pH of many additive formulations. For the control of slime-forming bacterial, fungal, and yeast growth in pulp, paper and paperboard mills add this product at levels of 0.15-0.50 lbs./ton (dry) of pulp or paper produced. Additions must be continuous or intermittent, depending upon the type of system and the severity of contamination. Additions are made via a metering pump at a point in the system that will ensure uniform distribution of this product in the mass of fiber and water, such as the

beaters, Jordan inlet or discharge, broke chests, furnish chests, save-alls and white-water tanks. **Heavily fouled systems** must first be boiled out, then treated with 0.15-0.35 lbs. of this product/ton (dry) of paper or pulp as necessary for control. **Moderately fouled systems** must be treated continuously with 0.35-0.50 lbs. of this product/ton (dry) of paper or pulp until the slime accumulation is controlled. Subsequent rates must then be reduced to 0.15-0.35 lbs. of this product/ton (dry) of paper on a continuous or intermittent basis as needed for control. Dislodged slime may cause breaks in the paper and a clean-up of the paper machine may be advisable. **Slightly fouled systems** must be treated continuously with 0.15-0.35 lbs. of this product/ton (dry) of paper or pulp, until the slime is controlled, then added on an intermittent basis to maintain control.

NON-POTABLE REVERSE OSMOSIS SYSTEMS: For controlling bacteria, fungi and algae slimes in non-potable reverse osmosis systems and peripheral equipment, add this product to the system inlet water or before any other contamination area ahead of the reverse osmosis unit. This product may be added with a metering pump on an intermittent or continuous basis depending on the severity of contamination and the guidelines specified by the membrane manufacturer for this product. For continuous use, add this product at the rate of 0.01 - 1.0 lbs. (1 - 120 ppm) per 1,000 gal. of feedwater. For cleaning off-line systems, add this product at 50 - 170 ppm per 1,000 gal. of feedwater to the off-line cleaning feed tank and re-circulate for 30 minutes - 3 hours. Once off-line treatment is completed, rinsing with feedwater must continue until conductivity values in the permeate are at or below values before treatment with this product. Badly fouled systems must be cleaned before treatment is begun. For industrial systems that cannot tolerate this product's residuals, a slug or intermittent feed process must be employed where the permeate and concentrate streams are directed to waste during the additions of this product and for 30 minutes - 1 hour following this product's additions.

FOR CONTROL OF BACTERIA

Initial Dose: When the system is noticeably fouled, add this product at the rate of 0.05 - 0.1 lbs. (6 - 12 ppm) per 1,000 gal. of feedwater. Minimum treatment intervals must be 15 minutes. Repeat until control is achieved or as specified by guidelines recommended by the membrane manufacturer.

Subsequent Dose: When microbial control is achieved, add this product at the rate of 0.025 - 0.1 lbs. (3 - 12 ppm) per 1,000 gal. of feedwater as needed to maintain control or as specified by guidelines recommended by the membrane manufacturer.

FOR CONTROL OF FUNGI AND ALGAE

Initial Dose: When the system is noticeably fouled, add this product at the rate of 0.5 - 1.0 lbs. (60 - 120 ppm) per 1,000 gal. of feedwater. Minimum treatment intervals must be 15 minutes. Repeat until control is achieved or as specified by guidelines recommended by the membrane manufacturer.

Subsequent Dose: When microbial control is achieved, add this product at the rate of 0.3 - 1.0 lbs. (36 - 120 ppm) per 1,000 gal. of feedwater as needed to maintain control or as specified by guidelines recommended by the membrane manufacturer.

METALWORKING FLUIDS CONTAINING WATER This product is effective in metalworking fluid concentrates which have been diluted in water at ratios of 1:100 to 1:4. For controlling (or inhibiting) the growth of bacteria, fungi and yeasts that may deteriorate metalworking fluids containing water, add this product to the fluid in the collection tank. Additions must be made with a metering pump.

Initial or Slug Dose: When the system is noticeably fouled, add this product at the rate of 0.25 gal. (2.65 lbs.) per 1,000 gal. of metalworking fluid in the system. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add this product at the rate of 0.1 - 0.2 gal. (1.06 - 2.12 lbs.) per 1,000 gal. of metalworking fluid per day, or as needed to maintain control. Additions of this product must be made continuously or intermittently. Slug the system as required.

BREWERY PASTEURIZER WATER: For controlling (or inhibiting) the growth of bacteria, fungi and yeasts in brewery pasteurizing water systems, add this product at a point in the system to insure uniform mixing.

Initial or Slug Dose: When the system is noticeably fouled, add this product at the rate of 0.25 gal. (2.65 lbs.) per 1,000 gal. of water in the system. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add this product at the rate of 0.1 - 0.2 gal. (1.06 - 2.12 lbs.) per 1,000 gal. of water per day, or as needed to maintain control. Additions of this product must be made continuously or intermittently. Slug the system as required. Badly fouled systems must be cleaned before treatment is begun.

ENHANCED OIL RECOVERY SYSTEMS: Add this product separately to the system. Do not mix it with other additives so as to avoid decomposition of this product due to the high pH of many additive formulations. Additions of this product may be made at the free water knockouts, before or after the injection pumps and injection well headers. For controlling slime-forming bacteria, sulfide-producing bacteria, yeasts, and fungi in oil field water, polymer or micellar floods, water disposal systems, or other oil field water systems, add 1-80 ppm of this product (0.1-6.4 gal. of this product per 2,400 barrels of water) depending on the severity of contamination. Additions must be made with a metering pump either continuously or intermittently.

CONTINUOUS FEED METHOD: When the system is noticeably fouled, add 10-80 ppm of this product (0.8-6.4 gal. of this product per 2,400 barrels of water) continuously until the desired degree of control is achieved. Subsequently, treat with 1-15 ppm of this product (0.1-1.2 gal. of this product per 2,400 barrels of water) continuously or as needed to maintain control.

INTERMITTENT OR SLUG METHOD: When the system is noticeably fouled or to maintain control of the system, add 10-80 ppm of the product (0.86-4 gal. of this product per 2,400 barrels of water) intermittently for 4-8 hours per day and from 1-4 times per week, or as needed depending on the severity of contamination. For control of bacteria, yeast, and fungi in aqueous solutions of biopolymer used in flooding operations, add 15-80 ppm of this product (1.2-6.4 gal. of this product per 2,400 barrels of water). Additions of this product must be made with a metering pump immediately after preparation of the aqueous biopolymer solution to reduce loss of viscosity.

AIR-WASHER SYSTEMS: Add 0.0015-0.095 gal. of this product/1,000 gal. of water in the system, depending on the severity of contamination, to control slime-forming bacteria and fungi in industrial air washing systems.

INTERMITTENT OR SLUG METHOD

Initial Dose: When the system is noticeably fouled, add 0.003-0.095 gal. of this product/1,000 gal. of water in the system. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 0.0015-0.047 gal. of this product/1,000 gal. of water in the system every 2 days, or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

CONTINUOUS FEED METHOD

Initial Dose: When the system is noticeably fouled, add 0.003-0.095 gal. of this product/1,000 gal. of water in the system.

Subsequent Dose: Maintain this level by pumping a continuous feed of 0.0015-0.047 gal. of this product/1,000 gal. of water in the system per day. Badly fouled systems must be cleaned

before treatment is begun. For use only in industrial air-washer systems that maintain effective mist eliminating components.

INDUSTRIAL PRESERVATION APPLICATIONS: This product may be used to reduce microbiological contamination in raw materials and/or products such as: aqueous paints and coatings, polymers, slurries, adhesives, latex and resin emulsions, sizing, caulk, process water, along with specialty industrial products including: inks, polishes, waxes, detergents, and cleansers.

To Reduce Microbiological Contamination: Add this product to the material or product at a concentration of 25 - 2,000 ppm by weight. This concentration is equivalent to 2.8 - 224.0 fluid ounces of this product per 1,000 gal. or 21.4 – 1,712.0 mL of this product per 1,000 L. The required concentration will depend on the material being treated and the level of contamination present.

PUBLICLY-OWNED TREATMENT WORKS TO CONTROL COLIFORM AND OTHER BACTERIA: Add this product at a concentration of 1.0 - 10.0 ppm by weight of water being treated, depending on the severity and contamination in the system. Additions must be CONTINUOUS and must be made with a metering pump at a point in the system where mixing will be rapid and thorough. Add this product to the system in a location where contact time will be 30 minutes or greater before reaching the outfall.

To Use As A Co-Treatment With Chlorine: Add 0.4-1.5 ppm of this product by weight of water treated. Chlorination must result in a minimum detectable residual (i.e., greater than zero but less than the NPDES permit level). Additions must be CONTINUOUS and made at a point just after initial chlorine mixing. Rapid mixing is necessary for maximum effectiveness. This product must be added at a location where a contact time of 10 minutes or longer will be provided before reaching the outfall.

OILFIELD AND PETROCHEMICAL SYSTEMS: This product may be used either in slug treatment or in continuous application. Dosages may vary from as much as 200 ppm of this product in slug application to 10 - 50 ppm of this product in continuous treatment (1/4 pint of this product per 1,000 gal. of water equals approximately 30 ppm). A typical slug treatment is to add 1 pint of this product per 1,000 gal. at intervals as needed to prevent growth of microbial slime. Badly fouled systems may be slug treated to establish control, followed by continuous treatment to maintain control.

EQUIPMENT CLEANING: This product kills microorganisms present in solution or growing on the surfaces of process equipment such as reaction vessels, storage tanks and containers, piping, and hoses. For standard cleaning of equipment, add 50 – 250 ppm of this product in an aqueous solution to process piping and equipment. Heavily fouled solutions or equipment may be treated with up to 2,000 ppm of this product. After treating process equipment with this product, allow the solution to be in contact with surfaces for up to four hours. If bleach is being used for cleaning purposes at 50 – 250 ppm available chlorine, this product must be used as part of a dual treatment program at 50 – 100 ppm by weight, in combination with sodium hypochlorite. Treat process equipment with chlorine first. Follow that treatment with this product and do not combine concentrated sodium hypochlorite solution with this product. **THIS PRODUCT IS NOT REGISTERED FOR THIS USE IN THE STATE OF CALIFORNIA**

FRACTURING FLUIDS: The product reduces bacterial contamination and degradation of fracturing fluids and gels used in oil and gas well stimulations. This product must be added to the water storage tanks before gelling and circulated to ensure mixing. If applicable, this product must be added at the well head for "on-the-fly" fracturing jobs.

Frequency and Dose: The product must be added at a rate of 90 – 270 ppm depending on water quality. Retreat after 48 hours if the frac job is delayed. **THIS PRODUCT IS NOT REGISTERED FOR THIS USE IN THE STATE OF CALIFORNIA**

STORAGE AND DISPOSAL

Do not contaminate water, food, or feed by storage or disposal.

PESTICIDE STORAGE: Store in a dark, cool, dry, well-ventilated area, below 104°F (40°C), in well-closed original containers, away from energy sources, combustible organic materials, oxidizers and moisture.

PESTICIDE DISPOSAL: Pesticide wastes are acutely hazardous. Improper disposal of excess pesticide, spray mixture or rinsate is a violation of Federal law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER HANDLING: NONREFILLABLE CONTAINER. Do not reuse or refill this container. Offer for recycling, if available. Triple rinse container (or equivalent) promptly after emptying.

(Capacity of 5 gallons or less) Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank and drain for 10 seconds after the flow begins to drip. Fill the container ¼ full with water and recap. Shake for 10 seconds. Pour rinsate into application equipment or a mix tank or store rinsate for the later use or disposal. Drain for 10 seconds after the flow begins to drip. Repeat this procedure two more times.

(Capacity of greater than 5 gallons) Triple rinse as follows: Empty the remaining contents into application equipment or a mix tank. Fill the container ¼ full with water. Replace and tighten closures. Tip container on its side and roll it back and forth, ensuring at least one complete revolution, for 30 seconds. Stand the container on its end and tip it back and forth several times. Empty the rinsate into application equipment or a mix tank or store rinsate for later use or disposal. Repeat this procedure two more times.

(All) Then offer for recycling if available or reconditioning, if appropriate, or puncture and dispose of in a sanitary landfill, or, if allowed by state and local authorities by burning. If burned, stay out of smoke. If metal container, do not puncture or burn.

SPILLS When handling or dealing with spills, use goggles with side-shields or face shield; wear protective clothing, including chemical-resistant gloves and boots; use a respirator if misting occurs. Cover wet spills with 10% sodium bicarbonate solution, water and then an inert absorbent before sweeping up and disposing of as described for pesticide disposal. If container contents are contaminated or decomposing, isolate unsealed container in the open or in a well-ventilated area: flood with 10% sodium bicarbonate solution and large volumes of water if necessary.

Sold by:

Buckman Laboratories, Inc.

1256 N. McLean Blvd., Memphis, Tennessee 38108, U.S.A.
(901) 278-0330 or 1-800-282-5626

EPA Reg. No. 1448-_____

o EPA Est. No. 72714-TN-1 o EPA Est. No. 1448-TN-1

Product Weight: 10 lbs/gal 4.54 kg/l

NET CONTENTS MARKED ON CONTAINER

Revised: 06/16/20