

# Copper Naphthenate 8%

## COPPER NAPHTHENATE 8%

ISOTROL CN-8  
For Control of Fungal Rot and Decay

Active Ingredient	
COPPER NAPHTHENATE . . . . .	80%
Inert Ingredient	
MINERAL SPIRITS . . . . .	20%
Total . . . . .	100%

Of the total 8% is metallic copper equivalent

### DANGER!

KEEP OUT OF REACH OF CHILDREN. HARMFUL  
IF SWALLOWED.

Causes eye damage and skin irritation. Wear goggles or face shield when handling. Do not get in eyes or on skin or clothing. Avoid inhalation of vapor or spray mist. In case of skin contact, flush with plenty of water; for eyes get immediate medical attention. Do not contaminate water by cleaning of equipment or disposal of wastes. Do not reuse empty drum. Return to drum reconditioner or destroy by perforating or crushing and burying in a safe place.

EPA REG. NO. 1486-8      NET WT. 450 LBS.  
Do not brush, spray or apply near open flame

**FERRO**  **CHEMICAL**  
CORPORATION      DIVISION

**BEDFORD, OHIO** 12-3-71  
1486-8

### CAUTION! HARMFUL IF TAKEN INTERNALLY - KEEP OUT OF REACH OF CHILDREN

For the control of fungal rot and decay

Treatment of textiles or rope: Dip, spray or brush a petroleum solvent solution of sufficient concentration to deposit at least 6% Isotrol CN-8 (0.5% metallic copper). Such items should be free of sizing or any other materials which would interfere with thorough impregnation of the fibers. Wooden objects should be dipped in a 25% solution of Isotrol CN-8 (2% metallic copper) for at least 2 minutes (longer for large posts or timbers) or given two or more flowing coats by brush or spray method.

USDA REG. NO. 1486-8

Do not brush, spray or apply near open flame