



MOORWOOD

penetrating

CAST

WOOD PRESERVATIVE

08800
1 GALLON 3.785 LITERS

EPA REG. NO. 160915 EPA EST. NO. 9268-NJ-01

MOORWOOD

REPLACEMENT
37



ADP-1000-1001



MOORWOOD PENETRATING CLEAR WOOD FINISH AND PRESERVATIVE

A clear sealer that penetrates deeply into uncoated woods to prolong or restore a new wood appearance. It contains a preservative to protect against wood rot. MOORWOOD Penetrating Clear Wood Finish resists mildew growth and its sealing action reduces the swelling and cracking of wood caused by normal weathering. It is intended for application

to wood siding, shakes, shingles, etc. MOORWOOD Clear is a water-based product that meets the requirements of Federal Specification 37. Use MOORWOOD Clear in accordance with the directions.

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH THE LABEL.

Surface Preparation: Surfaces must be clean and dry. Remove dirt, mildew or other contaminants.

New or Unpainted Wood: Use on rough sawn redwood, cedar, fir or pine shakes, shingles, siding, wooden tools and fences. New smooth lumber and siding must be weathered 16 months or sanded to remove new wood glaze. Test a small area of plywood and wood particle board to insure that a full coat of MOORWOOD Clear produces desired effect.

Weathered Bare Wood: One full coat of MOORWOOD Clear imparts a rich amber or honey color to wood that has weathered to a silvery gray. This natural color will last an extended time. When the silvery gray color reappears, it is time for another application.

Mildewed Wood: When new wood weathers, it may turn black from mildew. Mildew must be removed with a solution of chlorine bleach* in a 1 to 1 ratio with water. Rinsed clean and allowed to dry. If all mildew is not killed, a second bleach application is necessary. MOORWOOD Clear may then be applied. *Note: Plants and painted surfaces near mildewed areas should be protected from splashes of the bleach solution recommended for killing mildew. Protective

clothing and goggles must be worn.

Previously Stained, Varnished or Painted Surfaces: MOORWOOD Clear may NOT be applied over a surface unless the varnish is completely removed and the surface is properly prepared.

How To Apply: Stir well before use. Use brush, roller or spray. Spread to fill grain and pores, but 100-250% over the surface. The generous coat is essential to set up or dry before another application.

Drying Time: 4-48 hours of good ventilation.

Clean-up: Clean tools with mineral spirits.

Note: Moisture, metal or paint on surfaces may be stained by spray. Normal spray application will not stain clothing or trousers.

MOORWOOD CLEAR IS A TRADE MARK OF BURLINGTON INDUSTRIES, INC.

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS: KEEP OUT OF REACH OF CHILDREN.

WARNING! CONTAINS PETROLEUM DISTILLATES. Causes eye and skin irritation. Harmful if swallowed. Do not breathe vapors or spray mist.

FIRST AID: If swallowed, do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY.

ENVIRONMENTAL HAZARDS: This product is toxic to fish. Keep out of lakes, streams, rivers, etc. Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL OR CHEMICAL HAZARDS: Do not use, pour, spill or store near heat or flame.

COMBUSTIBLE: This product may ignite.

DISPOSAL: DO NOT REUSE EMPTY CONTAINER. WRAP CONTAINER AND PUT IN TRASH COLLECTION.

SEE INSTRUCTIONS FOR USE ON THE CONTAINER.

MOORWOOD PENETRATING CLEAR WOOD FINISH AND PRESERVATIVE Exterior Use Only

A clear sealer that penetrates deeply into uncoated woods to prolong or restore a new wood appearance. It contains a preservative to protect against wood rot. MOORWOOD Penetrating Clear Wood Finish resists mildew growth and its sealing action reduces the swelling and cracking of wood caused by normal weathering. It is intended for application

to wood siding, shakes, shingles and textured plywood. MOORWOOD Clear is a water-repellant coating which passes requirements of Federal Specification TT-W-572b par. 3.7. Use MOORWOOD Clear as received. Do not tint or intermix

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING.

Surface Preparation: Surfaces must be clean and dry. Remove dirt, mildew or other contaminants

New or Unpainted Wood: Use on rough sawn redwood, cedar, fir or pine shakes, shingles, siding, wooden roofs and fences. New smooth lumber and siding must be weathered 6 months or sanded to remove new wood glaze. Test a small area of plywood and wood particle board to insure that a full coat of MOORWOOD Clear produces desired effect.

Weathered Bare Wood: One full coat of MOORWOOD Clear imparts a rich amber or honey color to wood that has weathered to a silvery gray. This natural color will last an extended time. When the silvery gray color reappears, it is time for another application

Mildewed Wood: When new wood weathers, it may turn black from mildew. Mildew must be removed with household chlorine bleach* in a 1 to 1 ratio with water, rinsed clean and allowed to dry. If all mildew is not killed, a second bleach application is necessary. MOORWOOD Clear may then be applied. *Note: Plants and painted surfaces near mildewed areas should be protected from splashes of the bleach solution recommended for killing mildew. Protective

clothing and goggles must be worn when using bleach.

Previously Stained, Varnished or Painted Wood: MOORWOOD Clear may NOT be used unless stain, paint or varnish is completely removed and fresh wood exposed. The properly prepared surface can then be treated as New Wood.

How To Apply: Stir well before and occasionally during use. Use brush, roller or spray. Spreading rate will vary with wood texture and porosity, but 100-250 sq. ft. (9-23 sq. meters/gal.) is typical. If one generous coat is absorbed quickly, another must be applied immediately. DO NOT ALLOW MOORWOOD CLEAR TO SET UP OR DRY BETWEEN APPLICATIONS or a non-uniform gloss will result. Close container after each use. Use only with adequate ventilation.

Drying Time: 24-48 hours of good drying weather.

Cleanup: Clean tools with mineral spirits.

Note: Masonry, metal or painted surfaces should be covered to prevent their being stained by MOORWOOD Clear. When applying by spray, normal spraying precautions should be taken, i.e. mask, long trousers and a long-sleeved shirt should be worn

MOORWOOD is a registered trademark of BENJAMIN MOORE & CO., MONTVALE, N.J. 07645

PRECAUTIONARY STATEMENTS

HAZARDS TO HUMANS AND DOMESTIC ANIMALS: KEEP OUT OF REACH OF CHILDREN

WARNING! CONTAINS PETROLEUM DISTILLATES. Causes eye and skin irritation. Do not get in eyes, on skin or on clothing. Harmful if swallowed. Do not breathe vapors or spray mist.

FIRST AID: If swallowed, do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY.

ENVIRONMENTAL HAZARDS: This product is toxic to fish. Keep out of lakes, streams or ponds. Do not contaminate water by cleaning of equipment or disposal of wastes.

PHYSICAL OR CHEMICAL HAZARDS: Do not use, pour, spill or store near heat or open flame.

COMBUSTIBLE. This product may ignite.

**DISPOSAL: DO NOT REUSE EMPTY CONTAINER
WRAP CONTAINER AND PUT IN TRASH COLLECTION**

MOORWOOD Clear is a registered trademark of Benjamin Moore & Co., Montvale, N.J. 07645. © 1988 Benjamin Moore & Co. All rights reserved. For more information, call 1-800-4-A-MOORE. This product is not for sale in California, New York, and New Jersey. See label for restrictions. MOORWOOD Clear is not a warranty. See label for restrictions. MOORWOOD Clear is not a warranty. See label for restrictions.