

LIQUID CHLORINE

USDA REG. NO. 1616-X

Active Ingredient-Chlorine 99.7%

Inert Ingredients 0.3%

100.0%

NET WEIGHT _____



POISON



DANGER!



POISON



LIQUID WITHOUT LIQUID VAPOR UNDER NORMAL PRESSURE

In Red



- KEEP OUT OF REACH OF CHILDREN
- Do not heat cylinders
- Have available suitable gas masks for chlorine service.
- In case of exposure move patient to fresh air, lie down and quiet call doctor.
- Do not breathe vapors
- Do not get in eyes or on skin

Packed By

WARREN-DOUGLAS CHEMICAL CO., INC.

3002 "F" Street/Omaha, Nebraska 68107

LIQUID CHLORINE

- Before using ton containers, position cylinder so that the two outlet valves are directly above and below each other.
- Top valve delivers vapor, bottom valve delivers liquid on ton containers.
- Valve outlets on cylinders are designed for compression type fitting. Do not use tapered thread fittings (standard pipe fittings). Use only approved adaptors.
- Operate cylinder valves only with wrench designed for this type valve. Use of oversize wrench may result in excessive tightening resulting in damage to valve stem and seat, causing leak to develop.
- After repeated valve operations, the packing may loosen slightly, resulting in small chlorine leak around valve stem. In such case, tighten packing nut slightly to stop leak. Do not overtighten.
- Upon emptying container, close both valves securely, replace outlet caps and valve protection bonnet, designate container as empty.
- In case of container defect or leak that cannot be stopped, promptly contact:

WARREN-DOUGLAS CHEMICAL CO., INC.

3002 "F" Street / Omaha, Nebraska 68107 / AC402-733-3266

ACCEPTED

MAY 24 1958

UNDER FEDERAL ORDER
FOR CONTROL OF
POISON BOTTLES
ED UNDER NO. 1616-101 SUBJECT
TO ATTACHED COMMENTS