

COPPERSOTE

READY-TO-USE

WOOD PRESERVER

- Easy to use . . .
- Makes timber last longer . . .
- Can be painted over when dry . . .

Active Ingredients:
Copper Naphthenate
Copper Metallic F.
Petroleum Distillate

AC-10	1953
INC. 10% CUPPER NAPHTHENATE	10%
INC. 10% COPPER METALLIC F.	10%
INC. 80% PETROLEUM DISTILLATE	80%

90%

100%

This ready-to-use copper naphthenate complies with all requirements of the General Standards GS-152-48, as developed by the trade in cooperation with the National Bureau of Standards of the U. S. Department of Commerce.

DIRECTIONS

FOR PREVENTION OF DECAY AND PROTECTION AGAINST TERMITES

For interior or exterior use, spray, paint or dip as follows: For exterior application, two or more coats should be applied to wood as required. After treating, apply the usual treatments against insects. After drying, paint. Generally two applications are recommended. It should be applied to wood in a thin, even coat. Allow to penetrate for 15 to 48 hours.

CAUTION

KEEP OUT OF REACH OF CHILDREN

Extremely dangerous if taken internally. Harmful if taken internally. Avoid contact with eyes, skin, and clothing.

Georgia-Carolina Oil Company
Macon, Georgia

© 1953 Georgia-Carolina Oil Company