



NALCO 2210

FUNGAL AND BACTERIAL MICROORGANISM
CONTROL CHEMICAL FOR DIESEL FUEL OIL

ACTIVE INGREDIENT:

1-(2-hydroxyethyl)-2-alkyl
(C-18)*-2-imidazoline 25.0%

INERT INGREDIENTS: 75.0%

Total 100.0%

USDA Registration No. 1706-101

*As in Tall Oil Fatty Acids.

NALCO CHEMICAL COMPANY

6216 WEST 66TH PLACE CHICAGO, ILLINOIS 60638

NET CONTENTS SHOWN ELSEWHERE ON CONTAINER

DIRECTIONS:

To inhibit sludge formation, to disperse existing sludge and to control filter-plugging bacteria and fungi in fuel oil storage tanks and feedlines, use 40 to 80 ppm of Nalco 2210 based on fuel oil. Higher dosage may be required to completely inhibit some bacteria not considered to be factors in filter plugging.

Feed Nalco 2210 by means of proportioning pump or syphon type feeder directly from drum or other container to the fuel oil as it is pumped into storage tanks.

NOTE: NALCO 2210 IS INTENDED FOR INDUSTRIAL USE ONLY.

DANGER:

HARMFUL IF SWALLOWED, INHALED, OR ABSORBED THROUGH THE SKIN, CAUSES SEVERE EYE AND SKIN DAMAGE.

Do not get in eyes, on skin, or on clothing. Wear goggles or face shield and rubber gloves when handling. Keep away from heat and open flame. Keep container closed when not in use. Avoid breathing of vapor. Use with adequate ventilation. Do not take internally. In case of contact, immediately flush with large amounts of water for at least 15 minutes; for eyes, also get medical attention. Remove contaminated clothing. If swallowed, do not induce vomiting, drink large quantities of fluid and call a physician immediately.

