

**PRECAUTIONARY STATEMENTS  
HAZARDS TO HUMANS AND  
DOMESTIC ANIMALS**

**DANGER:**

**CORROSIVE. MAY BE HARMFUL OR  
FATAL IF SWALLOWED OR ABSORBED  
THROUGH THE SKIN. CAUSES SEVERE  
SKIN AND EYE DAMAGE.**

Do not get in eyes, on skin, or on clothing. Wear  
goggles or face shield and rubber gloves when  
handling. Keep container closed when not in use.

**ENVIRONMENTAL HAZARDS**

This pesticide is toxic to fish. Do not discharge  
into lakes, streams, ponds or public waters  
unless in accordance with an NPDES permit. For  
guidance contact your Regional Office of the EPA.

**STORAGE AND DISPOSAL**

Do not contaminate water, food, or feed by  
storage or disposal.

Pesticide wastes are acutely hazardous. Improper  
disposal of excess pesticide, spray mixture, or  
residue is a violation of Federal Law. If these  
wastes cannot be disposed of by use according to  
label instructions, contact your State Pesticide  
Control Agency, or the Hazardous  
Waste representative at the nearest EPA Regional  
Office for guidance.

**EMPTY CONTAINERS**

Triple rinse (or equivalent). Then offer for  
recycling or reconditioning, or puncture and  
dispose of in a sanitary landfill, or by other  
procedures approved by state & local authorities.

**PLASTIC CONTAINERS**

Triple rinse (or equivalent). Then offer for  
recycling and reconditioning, or puncture and  
dispose of in a sanitary landfill, or if allowed  
by state and local authorities, by burning. If  
burned, stay out of smoke.

EPA Reg. No. 1706-112  
EPA Est. No. 1706-1L-1

NET CONTENTS SHOWN ELSEWHERE ON CONTAINER

ACCEPTED

SEP 19 1991

Under the Federal Insecticide,  
Fungicide, and Fertilizer Act  
as amended, for the pesticide  
registered under  
EPA Reg. No. 1706-112

**NALCO®**

**NALCON®  
7620-WB**

**MICROORGANISM CONTROL CHEMICAL  
FOR CONTROL OF BACTERIAL AND FUNGAL SLIME**

ACTIVE INGREDIENT:	
Methylene bis(thiocyanate).....	10%
INERT INGREDIENTS:.....	90%
Total.....	100%

Weight per gallon=0.5 lbs.

**KEEP OUT OF REACH OF CHILDREN**

**DANGER:**

**STATEMENT OF PRACTICAL TREATMENT**

**IF SWALLOWED:** Feed gruel, or bread soaked in milk. Follow with milk or milk  
of magnesia or beaten eggs. CALL A PHYSICIAN.

**IN CASE OF PERSONAL CONTACT:** Remove excess material and flush skin or eyes  
with cold water for at least 15 minutes. **FOR EYES:** Get medical attention.  
Remove and wash contaminated clothing before reuse.

**NOTE TO PHYSICIAN:** Probable mucosal damage may contraindicate the use of  
gastric lavage. Measures against circulatory shock, respiratory depression  
and convulsions may be required.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

**NALCO CHEMICAL COMPANY**  
6216 WEST 66TH PLACE CHICAGO, IL 60638

EMERGENCY TELEPHONE NUMBER  
(708) 920-1510

**DIRECTIONS FOR USE:**

It is a violation of Federal Law to use this product in a  
manner inconsistent with its labeling.

**PULP AND PAPERMILL SYSTEMS**

For slime (bacterial and fungal) control in pulp, paper  
and paperboard mills, use 0.05 to 1.0 lbs. of NALCON  
7620-WB per ton of pulp or paper, dry basis, depending  
upon degree of contamination.

NALCON 7620-WB may be added anywhere in the system prior  
to the sheet forming area or in the recirculating white  
water system.

**FUEL OIL STORAGE TANKS**

For control of bacterial and fungal growth in distillate  
fuel oil storage tank bottom water add a slug dose of  
50-100 ppm NALCON 7620-WB. Repeat as needed to gain  
control.

To maintain control feed 25-50 ppm NALCON 7620-WB once  
a month or as needed.

Should disposal of tank bottom water become necessary wait  
at least 48 hours after last NALCON 7620-WB treatment  
before draining tank. Do not discharge water directly to  
ground where it can enter streams, lakes or ponds.

**PRESERVATIVE APPLICATIONS**

NALCON 7620-WB is an effective preservative at use levels  
between 75 and 750 ppm based on the total formulation in  
slurries of starch, clay, calcium carbonate or titanium  
dioxide; paper coatings, high viscosity suspensions (e.g.  
polymers; silica-polymer combinations; SBR latexes);  
polyvinyl alcohol/polyvinyl acetate based adhesives, starch  
based adhesives, dextrin based adhesives and refractory  
starches.

The exact dosage necessary for preservation of any given  
formulation will depend upon the components, storage time,  
temperature, etc., and can best be determined by actual test.

For preservation of slurries and high viscosity suspensions,  
NALCON 7620-WB should be added at a point in the processing  
where there will be sufficient time and agitation for good  
dispersion.

**FEEDING**

Feed NALCON 7620-WB directly from drum. Materials of con-  
struction should be stainless steel, Teflon, Penton or  
aluminum. Polyethylene or polypropylene are suitable for  
feed tubing. Application may be continuous or intermittent  
depending upon system characteristics. Technical assist-  
ance on individual site problems can be obtained from your  
Nalco Representative.

**KEEP FROM FREEZING**

BEST AVAILABLE COPY