

DANGER: CORROSIVE. CAUSES EYE DAMAGE AND SKIN BURNS. MAY CAUSE ALLERGIC SKIN REACTION. MAY BE HARMFUL IF INHALED. MAY BE FATAL IF SWALLOWED OR ABSORBED THROUGH THE SKIN. Do not get in eyes, on skin or on clothing. Wear goggles or face shield and rubber gloves when handling. Avoid breathing vapor or mist. Avoid contamination of food. Do not take internally. Wash thoroughly after handling.

ENVIRONMENTAL HAZARDS

This pesticide is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or public waters unless this product is specifically identified and addressed in an NPDES permit. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label.

STORAGE AND DISPOSAL

STORAGE: Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

PESTICIDE DISPOSAL: Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions, contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

CONTAINER DISPOSAL:
Metal Containers: Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

Plastic Containers: Do not reuse empty container. Triple rinse (or equivalent). Then puncture and dispose of in a sanitary landfill, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

EPA Reg. No. 1706-153
EPA Est. No. 1706-LA-1

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS

NALCO CHEMICAL COMPANY

RIVER ROAD (P. O. DRAWER 1) GARYVILLE, LOUISIANA 70051
D.O.T. SHIPPING NAME: CORROSIVE LIQUID, N.O.S. UN1760
(Contains 5-Chloro-2-methyl-4-isothiazolin-3-one, Cupric nitrate)



MICROBIOCIDES FOR USE IN INDUSTRIAL RECIRCULATING COOLING WATER SYSTEMS

ACTIVE INGREDIENTS:

5-Chloro-2-methyl-4-isothiazolin-3-one	1.15%
2-Methyl-4-isothiazolin-3-one	0.35%
INERT INGREDIENTS	98.50%
Total	100.00%

Weight/gallon = 8.5 lbs

KEEP OUT OF REACH OF CHILDREN

DANGER:

STATEMENT OF PRACTICAL TREATMENT

If swallowed: Do not induce vomiting. Drink promptly a large quantity of milk, egg whites, gelatin solution or, if these are not available, drink large quantities of water. Avoid alcohol. Call a physician immediately.

If inhaled: Remove immediately to fresh air. If not breathing, apply artificial respiration. If breathing is difficult, give oxygen. Call a physician.

If on skin: Wash thoroughly with soap and water. Remove and wash contaminated clothing before reuse.

If in eyes: Flush with plenty of water for at least 15 minutes. Call a physician.

NOTE TO PHYSICIAN: Probably mucosal damage may contraindicate the use of gastric lavage. Measures against circulatory shock, respiratory depression and convulsions may be needed.

DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

COOLING TOWER SYSTEMS

For control of bacteria, fungi and algae add NALCO 7330 to the tower basin, distribution box or some other point to insure uniform mixing. Badly fouled systems must be precleaned before treatment is begun.

Initial Dose: When the system is noticeably fouled, apply 2.46 to 7.46 lbs (37 to 113 fluid ounces) of NALCO 7330 per 1000 gallons of water in the system. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 1.26 to 1.86 lbs (19 to 28 fluid ounces) of NALCO 7330 per 1000 gallons of water in the system weekly or as needed to maintain control.

AIR WASHER SYSTEMS

For control of bacteria, algae and fungi add NALCO 7330 to a point in the system where uniform mixing can occur such as the basin. For use in industrial air washer systems that maintain effective mist eliminating components. Badly fouled systems must be precleaned before treatment is begun.

Initial Dose: When the system is noticeably fouled, add 1.26 to 7.46 lbs (19 to 113 fluid ounces) of NALCO 7330 per 1000 gallons of system water. Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 0.3 to 1.86 lbs (4.5 to 28 fluid ounces) of NALCO 7330 per 1000 gallons system water weekly or as needed to maintain control.

BREWERY PASTEURIZERS

For control of bacteria, fungi and algae in brewery pasteurizers, add 1.26 to 7.46 lbs (19 to 113 fluid ounces) of NALCO 7330 per 1000 gallons of system water to achieve initial control. Repeat as needed to achieve control. To maintain control add 0.3 to 1.86 (4.5 to 28 fluid ounces) of NALCO 7330 per 1000 gallons system water weekly or as needed.

INDUSTRIAL RECIRCULATING CLOSED LOOP WATER COOLING SYSTEMS

For the control of bacteria algae and fungi, add NALCO 7330 to the reservoir, recirculating line or some other point in the system to insure uniform mixing.

Initial Dose: When the system is noticeably fouled, apply 148 to 883 ppm NALCO 7330 (1.26 to 7.46 pounds or 19 to 113 fluid ounces of NALCO 7330 per 1,000 gallons of water in the system). Repeat until control is achieved.

Subsequent Dose: When microbial control is evident, add 35 to 219 ppm NALCO 7330 (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of NALCO 7330 per 1,000 gallons of water in the system) weekly or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

NALCO 7330 weighs 8.4 lbs per gallon.

ACCEPTED
OCT 17 1986
Under Fungicide, Fungicide Act, as amended, the pesticide registered under EPA Reg. No. 1706-153