

**PRECAUTIONARY STATEMENTS: HAZARDS TO HUMANS  
AND DOMESTIC ANIMALS**

**DANGER. CORROSIVE. CAUSES IRREVERSIBLE EYE DAMAGE OR SKIN BURNS. HARMFUL IF INHALED, SWALLOWED OR ABSORBED THROUGH SKIN.** Do not get in eyes, on skin or on clothing. Prolonged or frequently repeated skin contact may cause allergic reaction in some individuals. Mixers, loaders, and others exposed to this product must wear: long-sleeved shirt and long pants; chemical resistant gloves such as nitrile or butyl rubber; shoes plus socks; goggles and face shield; and chemical resistant apron. Discard clothing or other absorbent materials that have been drenched or heavily contaminated with this product's concentrate. Do not reuse them. Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry. Users should wash hands before eating, drinking, chewing gum, using tobacco or using the toilet. Users should remove clothing immediately if pesticide gets inside. Then wash thoroughly and put on clean clothing. Users should remove PPE immediately after handling the product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly. Do not apply this product in a way that will contact workers or other persons.

**ENVIRONMENTAL HAZARDS**

This pesticide is toxic to fish and wildlife. Do not discharge effluent containing this product into lakes, streams, ponds, estuaries, oceans, or other waters unless in accordance with the requirements of a National Pollutant Discharge Elimination System (NPDES) permit and the permitting authority has been notified in writing prior to discharge. Do not discharge effluent containing this product to sewer systems without previously notifying the sewage treatment plant authority. For guidance contact your State Water Board or Regional Office of the EPA. Do not contaminate water by cleaning of equipment or disposal of waste. Apply this pesticide only as specified on this label.

**PHYSICAL AND CHEMICAL HAZARDS**

This product is corrosive to mild steel. Do not store or transport in unlined metal containers.

**STORAGE AND DISPOSAL**

**STORAGE:** Do not contaminate water, food, or feed by storage or disposal. Open dumping is prohibited.

**DISPOSAL:** Pesticide wastes are toxic. Improper disposal of excess pesticide, spray mixture, or rinsate is a violation of Federal Law. If these wastes cannot be disposed of by use according to label instructions contact your State Pesticide or Environmental Control Agency, or the Hazardous Waste representative at the nearest EPA Regional Office for guidance.

**METAL CONTAINERS:** Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or by other procedures approved by state and local authorities.

**PLASTIC CONTAINERS:** Do not reuse empty container. Triple rinse (or equivalent). Then puncture and dispose of in sanitary landfill, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

Net Contents Shown Elsewhere on Container

Rev.: 3/27/2003

Corrosive Liquid, Acidic, Organic, N.O.S. (Isothiazolinone Microbiocide), 8, UN 3265, II



# Nalco 7330

A MICROBIOCIDICIDE FOR CONTROL OF BACTERIA, FUNGI AND ALGAE IN INDUSTRIAL RECIRCULATING WATER COOLING TOWERS, INDUSTRIAL PROCESS WATER SYSTEMS, AIR WASHER SYSTEMS AND BREWERY PASTEURIZERS.

<b>ACTIVE INGREDIENTS:</b>	
5-Chloro-2-methyl-4-isothiazolin-3-one.....	1.11%
2-Methyl-4-isothiazolin-3-one.....	0.39%
<b>INERT INGREDIENTS:</b> .....	<u>98.50%</u>
<b>TOTAL:</b> .....	100.00%

This product contains the active ingredients at 0.127 pounds per gallon

**KEEP OUT OF REACH OF CHILDREN  
DANGER PELIGRO**

**FIRST AID**

**If swallowed:**

- Call a poison control center or a doctor immediately for treatment advice.
- **DO NOT INDUCE VOMITING.**
- Do not give anything to drink.

**If in eyes:**

- Hold eye open and rinse slowly and gently with water for 15-20 minutes.
- After at least 15 minutes of rinsing or after it is judged that nearly all of the contamination has been removed. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing.
- Call a poison control center or a doctor immediately for treatment advice.

**If on skin or clothing:**

- Take off contaminated clothing.
- Rinse skin immediately with plenty of water for 15-20 minutes.
- Call a poison control center or a doctor for treatment advice.

**If inhaled:**

- Move person to fresh air.
- If person is not breathing, call 911 or an ambulance, and then give artificial respiration, preferably mouth-to-mouth if possible.
- Call a poison control center or a doctor for further treatment advice.

**NOTE TO PHYSICIAN:**

Aspiration may cause lung damage. Probable mucosal damage may contraindicate the use of gastric lavage. Have the MSDS and, if available, the product container or label with you when calling a poison control center or a doctor, or going for treatment.

SEE SIDE PANEL FOR ADDITIONAL PRECAUTIONARY STATEMENTS.

EPA REG. NO. 1706-153      EPA EST. NO. 1706-LA-1 (GV)  
EPA EST. NO. 1706-PA-1 (E)      EPA EST. NO. 1706-CN-1 (BV)  
Letter in () that matches first letter in batch number identifies the establishment number.

ONDEO Nalco Company  
Ondeo Nalco Center  
Naperville, IL 60563-1198  
EMERGENCY PHONE NO. (800) 424-9300

## DIRECTIONS FOR USE

It is a violation of Federal Law to use this product in a manner inconsistent with its labeling.

### INDUSTRIAL COOLING TOWER SYSTEMS AND PROCESS WATER SYSTEMS

(Such as pretreatment systems and process waters used for washing metal or plastic parts and/or paint reduction.) For control of bacteria fungi and algae, add NALCO 7330 to the tower basin, distribution box or some other point in the system to insure uniform mixing. Badly fouled systems must be precleaned before treatment is begun.

**INITIAL DOSE:** When the system is noticeably fouled apply 2.46 to 7.46 lbs. (37 to 113 fluid ounces) of NALCO 7330 per 1000 gallons of water in the system. Repeat until control is achieved.

**SUBSEQUENT DOSE:** When microbial control is evident, add 1.26 to 1.86 lbs. (19 to 28 fluid ounces) of NALCO 7330 per 1000 gallons of water in the system weekly or as needed to maintain control.

### INDUSTRIAL RECIRCULATING CLOSED LOOP WATER COOLING SYSTEMS

For the control of bacteria, algae and fungi add NALCO 7330 to the reservoir, recirculating line or some other point in the system to insure uniform mixing.

**INITIAL DOSE:** When the system is noticeably fouled, apply 1.26 to 7.46 lbs. (19 to 113 fluid ounces) of NALCO 7330 per 1000 gallons of water in the system. Repeat until control is achieved.


**SUBSEQUENT DOSE:** When microbial control is evident, add 35 to 219 ppm NALCO 7330 (0.3 to 1.86 pounds or 4.5 to 28 fluid ounces of NALCO 7330 per 1000 gallons of in the system) weekly or as needed to maintain control. Badly fouled systems must be cleaned before treatment is begun.

### AIR WASHER SYSTEMS AND BREWERY PASTEURIZERS

For control of bacteria, algae and fungi, add NALCO 7330 to a point in the system where uniform mixing can occur such as the basin. FOR USE IN INDUSTRIAL AIR WASHER SYSTEMS THAT MAINTAIN EFFECTIVE MIST ELIMINATING COMPONENTS. Badly fouled systems must be precleaned before treatment is begun.

**INITIAL DOSE:** When the system is noticeably fouled, add 1.26 to 7.46 lbs. (19 to 113 fluid ounces) of NALCO 7330 per 1000 gallons of system water. Repeat until control is achieved.

**SUBSEQUENT DOSE:** When microbial control is evident, add 0.3 to 1.86 lbs. (4.5 to 28 fluid ounces) of NALCO 7330 per 1000 gallons system water weekly or as needed to maintain control.



1706-153

4/25/2003

Page 121